

भारत सरकार/Government of India

तार पर पर विवर्णनाम के नाम त्यां के साम त्यां के स

ट्रैक्टरनगर, सिरसारोड, हिसार) हरियाणा(⁄ Tractor Nagar, Sirsa Road, Hisar (Haryana)- 125 001

Website: http://nrfmtti.gov.in E-mail: fmti-nr@nic.in Tel./Fax: 01662276984 GSTIN:06AAAGN0273PIZ3

[ISO - 9001 : 2015 CERTIFIED]

TECHNICAL SPECIFICATIONS FOR INTERNAL COMBUSTION ENGINE

| 1 | General: | | |
|---|--|-------|------------|
| | Make | : | |
| | Model | : | |
| | Туре | : | |
| | Name & address of manufacturer | : | |
| | Name & address of applicant | : | |
| | Country of origin | : | |
| | Year of manufacture | : | |
| | Engine serial No | : | |
| | Max. Torque, Nm | : | |
| | Speed at max. Torque, rpm | : | |
| | Maximum Power, kW | : | |
| | | | |
| | Rated power, kW | : | |
| | , rpm | : | |
| | Maximum torque, N-m | : | |
| | Engine speed (Manufacturer's Recommended s | ettii | ngs), rpm: |
| | Maximum speed at no load | : | |
| | Rated speed | : | |
| | Low idle speed | : | |
| | Engine speed corresponding to Max. Power | : | |
| | Engine speed corresponding to Rated Power | : | |
| | Engine speed corresponding to maximum torque | : | |
| | Max. Engine oil temperature, °C | : | |
| | Max. Coolant/liner wall temperature, °C | : | |
| | Compliance with Emission Norms | : | |
| 2 | Cylinder and cylinder head: | | |
| | Number | : | |
| | Disposition | : | |
| | Bore/Stroke ,mm | : | |
| | Capacity , cc | : | |
| | | | |

| Name of the Manufacturer/ Applicant | Document No, if any Revision status | Name of the Test Agency: NRFMTTI, Hisar |
|-------------------------------------|-------------------------------------|---|
| Signature : | Make : | Signature : |
| Name : | Model : | Name : |
| Designation : | Sheet No of | Designation : |
| Date : | | Date : |

| | Compression ratio : | | : | | |
|-----------|---------------------------------------|---------------------------------|------|---|---|
| | Type of cylinder head | | : | | |
| | Type of cylinder liner | | : | | |
| | Type of combustion cha | mber | : | | |
| | Arrangement of valves | | : | | |
| | Valve clearance, mm: | | | | |
| | -Inlet | | : | | |
| | -Exhaust | | : | | |
| 3 | Fuel system: | | : | | |
| | Type of fuel system | | : | | |
| | Capacity of fuel tank, l | | : | | |
| 3.1 | Fuel feed pump: | | | | |
| | Туре | | : | | |
| | Make & model/group co | ombination number of | | | |
| | feed pump | | | | |
| | Provision of sediment be | owl | : | | |
| 3.2 | Fuel filter: | | | | |
| | Туре | | : | | |
| | Make & model/group co | ombination number of | : | | |
| | fuel filter | | | | |
| | Numbers | | : | | |
| | Type of element | | : | | |
| | Capacity of final stage f | ilter, l | : | | |
| 3.3 | Ignition: | | | | |
| | Туре | | : | | |
| | Magneto contact breake | r point gap, mm | : | | |
| | Ignition timing | | : | | |
| 3.4 | Fuel Injection pump: | | | | |
| | Make & model group co | ombination number | : | | |
| | Туре | | : | | |
| | Serial number | | : | | |
| | Method of drive | | : | | |
| 3.5 | Fuel injector: | | : | | |
| | Make & Model group combination number | | : | | |
| | Туре | | : | | |
| Name of + | he Manufacturer/ Applicant | Document No. if any Povision of | atus | 1 | Name of the Test Agency: NRFMTTI, Hisar |
| Signature | : | Make : | aius | | Signature : |
| Name | : | Model : | | | Name : |

Designation

•

| | Manufacturer's production pressure setting, Mpa | : | | |
|-----|--|---|-----------------|-------------------|
| | Injection timing | : | | |
| | Firing order | : | | |
| 3.6 | Governor: | : | | |
| | Make & Model | : | | |
| | Туре | : | | |
| | Governed range of engine speed, rpm | : | | |
| | Rated speed, rpm | : | | |
| 3.7 | Spark plug (if applicable): | | | |
| | Make | : | | |
| | Electrode gap, mm | : | | |
| 3.8 | Carburettor (if applicable): | | | |
| | Make | : | | |
| | Туре | : | | |
| 4 | Air intake system: | : | | |
| | Туре | : | | |
| 4.1 | Pre-cleaner: | | | |
| | Туре | : | | |
| | Make & model | : | | |
| | Number | : | | |
| | Location | : | | |
| 4.2 | Air cleaner: | | | |
| | Туре | : | | |
| | Make & model | : | | |
| | Number | : | | |
| | Location | : | | |
| | No. & type of element | : | | |
| | Oil capacity (Oil bath type),l | : | | |
| | Recommended grade of oil | : | | |
| | Recommended service schedule, h | : | | |
| | Size of element (dry type), mm: | | Primary (outer) | Secondary (inner) |
| | -ID/OD | : | | |
| | -Length | | | |
| | Provision of service indicator | : | | |

| Name of the Manufacturer/ Applicant Document No, if any Revision status | | Name of the Test Agency: NRFMTTI, Hisar |
|---|---------|---|
| Signature : | Make : | Signature : |
| Name : Designation : | Model : | Name : |

| | Provision of dust unload | ling valve | : | |
|-----------|--------------------------------|---------------------------------|------|---|
| | Range of suction pressu | re at maximum power, | : | |
| | kPa | | | |
| 5 | Exhaust: | | | |
| | Туре | | : | |
| | Make & model | | : | |
| | Number | | : | |
| | Location | | : | |
| | Shape & Size of muffler | | : | |
| | Provision of spark arrest | ting device/any other | : | |
| | device | | | |
| | Range of exhaust gas pr | essure at maximum | : | |
| | power, kPa | | | |
| 5.1 | Details of turbo charge | er: | | |
| | Make & model | | : | |
| | Part No. | | : | |
| | No. of fan/wheel | | : | |
| | No. of blades: | | | |
| | -Turbine wheel | | : | |
| | -Compressor wheel | | : | |
| | Method of drive | | : | |
| | Means of lubrication | | : | |
| 5.2 | Charged air cooler (CAC) unit: | | | |
| | Туре | | : | |
| | Make | | : | |
| | Size(L×W×H), mm | | : | |
| | No of Tubes | | : | |
| 5.3 | EGR: | | | |
| | Make | | : | |
| | Туре | | : | |
| | Part No. | | : | |
| 5.4 | Exhaust treatment syst | tem: | | |
| 5.4.1 | Diesel Oxidation Catal | yst (DOC): | | |
| | Make | | : | |
| | DOC description | | : | |
| Name of t | he Manufacturer/ Applicant | Document No. if any Revision of | atus | Name of the Test Agency: NRFMTTI, Hisar |
| Signature | : | Make : | | Signature : |

Name :

Model :

Name

Designation :

:

| | Part No. | : | |
|-------|---|---|--|
| | Location | : | |
| 5.4.2 | Selective catalyst Reduction (SCR): | | |
| | Make | : | |
| | Description | : | |
| | Location | : | |
| 5.4.3 | Details of diesel exhaust fluid tank: | | |
| | Capacity, l | : | |
| | Location | : | |
| | Material of construction | : | |
| | Provision of draining | : | |
| | Recommended diesel exhaust fluid | : | |
| 6 | Lubrication system: | : | |
| | Туре | : | |
| | Type of lubricating oil pump | : | |
| | Lubricating oil pump speed corresponding to rated engine speed, rpm | | |
| | Capacity of lubricating oil pump at rated engine speed, l/min | : | |
| | Relief valve pressure setting, kg/cm ² | : | |
| | Oil sump capacity, l | | |
| | Recommended grade of lubricating oil | : | |
| | Oil change period, h | : | First change afterhrs then subsequent changes after every hours of operation |
| | Minimum permissible lubricating oil pressure, kg/cm ² | : | |
| | Maximum permissible lubricating oil temperature, °C | : | |
| | Method of oil cooling | : | |
| 6.1 | Oil cooler: | | |
| | Туре | : | |
| | Make & model | | |
| | Part No. | : | |
| | No. of plates | : | |
| 6.2 | Filter: | | |
| | Туре | : | |
| | Number | : | |
| | Location | : | |

| Name of the Manufacturer/ Applicant | Document No, if any Revision status | Name of the Test Agency: NRFMTTI, Hisar |
|-------------------------------------|-------------------------------------|---|
| Signature : | Make : | Signature : |
| Name : Designation : | Model : | Name : |

| | Type of element | | : | | |
|------------|---|---------------------------------|------|--|---|
| 7 | Cooling System: | | | | |
| | Туре | | : | | |
| 7.1 | Water pump/blower: | | | | |
| | Туре | | : | | |
| | Make | | : | | |
| | Size of impeller/blower, | mm | : | | |
| | No. of vanes/blades | | : | | |
| | Method of drive | | : | | |
| 7.2 | Details of fan: | | | | |
| | Туре | | : | | |
| | Material | | : | | |
| | No. of blades | | : | | |
| | Diameter, mm | | : | | |
| 7.3 | Radiator: | | | | |
| | Make | | : | | |
| | Part No. | | : | | |
| | Sr. No. | | : | | |
| | Size of radiator (W × H > | × T), mm | : | | |
| | No. of tubes | | : | | |
| | Type of radiator cap | | : | | |
| | Radiator cap pressure | | : | | |
| | Means of temperature co | ntrol | : | | |
| | Type of thermostat | | : | | |
| | Bare radiator capacity, 1 | | : | | |
| | Total coolant capacity | | : | | |
| | Type of coolant recomm | ended | : | | |
| | Coolant water ratio recor | nmended | : | | |
| | Type of radiator grill | | : | | |
| | Means of grill cleaning | | : | | |
| | Maximum permissible coolant temperature, °C : | | | | |
| 8 | Air compressor | | : | | |
| 9 | Starting system: | | | | |
| | Туре | | : | | |
| | Aid for cold starting | | : | | |
| Name of th | he Manufacturer/ Applicant | Document No, if any Revision st | atus | | Name of the Test Agency: NRFMTTI, Hisar |
| Signature | : | Make : | | | Signature : |
| Name | Name : Model : | | | | Name : |

| | Any other device for easy starting | : | |
|----------|------------------------------------|---|--|
| 10 | Electrical System: | | |
| 10.1 | Battery: | | |
| | Make & model | : | |
| | Number & Type | : | |
| | Capacity & rating | : | |
| | Location | : | |
| 10.2 | Starter motor: | | |
| | Make | : | |
| | Туре | : | |
| | Model | : | |
| | Capacity/power | : | |
| | Sr. No./Part No. | : | |
| | Location | : | |
| 10.3 | Alternator: | | |
| | Make | : | |
| | Туре | : | |
| | Model | : | |
| | Output rating | : | |
| | Sr. No./Part No. | : | |
| | Location | : | |
| | Method of drive | : | |
| 11 | Overall dimensions, mm: | | |
| | -Length | : | |
| | -Width | : | |
| | -Height | : | |
| 12 | Weight, kg | : | |
| 13 | Colour | : | |
| 14 | Labelling plate: | | |
| <u> </u> | | | |

| Name of the Manufacturer/ Applicant | Document No, if any Revision status | Name of the Test Agency: NRFMTTI, Hisar |
|-------------------------------------|-------------------------------------|---|
| Signature : | Make : | Signature : |
| Name : Designation : | Model : | Name : |

SELECTED PERFORMANCE AND OTHER CHARACTERISTICS AS PER IS 15806-2018

| (TO BE DECLARED BY THE APPLICANT IF THE INTENDED USE OF ENGINE IS FOR |
|---|
| COMBINE HARVESTER) |

| S. No | Characteristics | | Category (Evaluative/ Non evaluative) | Requirement | Tolerance | Declarati- on by applicant | Remarks |
|----------|-----------------|--|--|--------------------------------------|--|----------------------------------|---------|
| 1 | | 2 | 3 | 4 | 5 | 6 | 7 |
| 1. | Prin | ne mover performance: | | | | | |
| | a) | Max. Power (absolute) - Average max. power observed during 2 hrs. max. power test in natural ambient condition, kW | Evaluative | To be declared by manufacturer | Declared value to be achieved with a tolerance of $\pm 5\%$ | | |
| | b) | Max. power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW | Evaluative | To be declared by manufacturer | -do- | | |
| | c) | Power at rated engine speed, kW (under natural ambient condition) | Non- Evaluative | To be declared by manufacturer | -do- | | |
| | d) | Specific fuel consumption corresponding to average maximum power under 2h maximum power test, g/kWh. | Evaluative | -do- | +5%(Max.) | | |
| | e) | Max. smoke density (Bosch no.) at 80 percent load between the speed at max. power and 55 percent of speed at max. power or 1000 rpm whichever is higher. | Evaluative | As per CMV rules. | Nil | - | |
| | f) | Max. crank shaft torque, (Nm) observed during the test after no load engine speed is adjusted as per manufacturer's recommendation for field work | Evaluative | To be declared by manufacturer | ±8% | | |
| | g) | Back up torque, % | Evaluative | 7 percent, (Min.) | Nil | - | |

| Name of the Manufacturer/ Applicant | Document No, if any Revision status | Name of the Test Agency: NRFMTTI, Hisar |
|-------------------------------------|-------------------------------------|---|
| Signature : | Make : | Signature : |
| Name : Designation : | Model : | Name : |

| 1 | | 2 | 3 | 4 | 5 | 6 | 7 |
|-------|-------------------------------|--|------------|---|-----|---|--|
| | h) | h) Max. Operating temperature, 0C: | | | | | |
| | i) | Engine oil | Evaluative | To be declared by manufacturer | Nil | | The observed value under the high ambient condition should not exceed maximum safe value specified by the oil company which will be provided by the applicant |
| | ii) | Coolant | Evaluative | To be declared by manufacturer | Nil | | The declared value should not exceed the boiling temperature of coolant under the pressurized or otherwise and the observed value under high ambient condition should not exceed the declaration. |
| | i) | Lubrication oil consumption, g/kWh | Evaluative | Not exceeding 1 % of specific fuel consumption at maximum power under high ambient condition | Nil | | The value would be based on the test conducted under high ambient condition |
| 2. Ai | 2. Air cleaner oil pull over: | | | | | | |
| | i) | Max. oil pull over in percentage when tested in accordance with IS: 8122. (Part-2)-2000 | Evaluative | 0.20% max. | Nil | | |

Place:

Date:

Signature-----

Name of the applicant-----

Designation-----

Address-----

| Name of the Manufacturer/ Applicant | Document No, if any Revision status | Name of the Test Agency: NRFMTTI, Hisar | | |
|-------------------------------------|-------------------------------------|---|--|--|
| Signature : | Make : | Signature : | | |
| Name : Designation : | Model : | Name : | | |