



### भारत सरकार /GOVERNMENT OF INDIA

# उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान Northern Region Farm Machinery Training and Testing Institute ट्रैक्टर नगर, सिरसा रोड, हिसार )हरियाणा—(125001 TRACTOR NAGAR, SIRSA ROAD, HISAR (HARYANA)- 125 001

Website: http://nrfmtti.gov.in E-mail: fmti-nr@nic.in GSTIN:06AAAGN0273PIZ3

Tele./FAX: 01662-276984

#### TECHNICAL SPECIFICATIONS FOR TRACTOR OPERATED COMBINE HARVESTER

1.1	General:		
	Name & address of manufacturer	:	
	Name & address of applicant/importer	:	
	Make	:	
	Model	:	
	Brand name (if any)	:	
	Type	:	
	Year of manufacture	:	
	Serial No./Chassis No.	:	
	Country of origin	:	
	Type of crops recommended for	:	
	harvesting		
1.2	Prime mover:		
1.2.1	Tractor:		
	Make	:	
	Model	:	
	Type	:	
	Chassis No.		
1.2.2	Engine:		
	Make	:	
	Model	:	
	Type	:	
	Serial No.	:	
	Engine speed (rpm) (Manufacturer's reco	mmer	ided setting)
	Maximum speed at no load, rpm	:	
	Rated speed, rpm	:	
	No load engine speed recommended for	:	
	field operation, rpm		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation :	Sheet No of	Designation:		
Date :		Date:		

I	Low idle speed, rpm	:	
Ī	Location	:	
(	Country of origin	:	
	Whether the tractor has already been	:	
	tested by authorized testing centre		
	(Yes/No)		
	If yes, then specify valid test report No.	:	
T	and upload copy of the test report Details of Emission Certificate (if any)	:	
	Cylinder and cylinder head:	•	
	Number		
	Disposition	:	
	_	:	
	Bore/Stroke, mm	:	
	Capacity, cm <sup>3</sup>	:	
	Compression ratio	:	
	Arrangement of valves	:	
	Type of cylinder liners	:	
	Гуре of head	:	
	Type of combustion chamber	:	
	Valve clearance in cold (mm):		
<u> </u>	- Inlet valve	:	
	-Exhaust valve	:	
	Fuel system:		
7	Гуре of fuel system	:	
1.2.2.1 I	Fuel tank:		
N	Material	:	
S	Size, mm	:	
(	Capacity, 1	:	
1.2.2.2 I	Fuel feed pump:		
N	Make	:	
7	Гуре	:	
N	Model/Group combination number	:	
F	Provision of sediment bowl	:	
1.2.2.3 I	Fuel filters:		
N	Make	:	
N	Model/Group combination No.	:	
1	Number (s)	:	
7	Type of element:		
	Primary	:	
	Secondary	:	
(	Capacity of final stage filter, l	:	
	Provision of water separator	:	
	Make	:	
I	Location	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

1.2.2.4	Fuel injection pump;			
	Make	:		
	Model/Group combination No.	:		
	Туре	:		
	Method of drive	:		
1.2.2.5	Fuel injectors:			
	Make	:		
	Туре	:		
	Model/Group combination No.	:		
	Injection opening pressure, kgf/cm <sup>2</sup>	:		
	Injection timing, degree	:		
	Firing order	:		
1.2.3	Governor:			
	Make	:		
	Туре	:		
	Model/Group combination	:		
	number/Designation			
	Governed range of engine speed, rpm	:		
1.2.4	Air Intake System:			
	Type	:		
1.2.4.1	Pre-cleaner:			
	Make	:		
	Type	:		
	Number	:		
	Location	:		
1.2.4.2	Air cleaner:			
	Make	:		
	Type	:		
	Number	:		
	Location	:		
	Type of element	:		
	Size of filter element, mm:		Primary (outer)	Secondary (inner)
	Inner dia.	:		
	Outer dia.	:		
	Length	:		
	Service indicator	:		
	Dust unloading valve	:		
	Recommended service Schedule, h	:		
	Suction pressure at max. power, kPa	:		
1.2.5	Exhaust:			
	Make	:		
	Туре	:		
	Pressure at max. power, kPa	:		
	A /			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature :		
Name :	Model:	Name:		
Designation :	Sheet No of	Designation:		
Date :		Date:		

	Provision of spark arresting device/any	:	
	other device		
1.2.5.1	Details of turbocharger		
	Make	:	
	Model	:	
	Number of fan/wheels	:	
	Number of blades:		
	Turbine wheel	:	
	Compressor fan	:	
	Method of drive	:	
	Means of lubrication	:	
1.2.5.2	Charged air cooler (CAC) unit		
	Туре	:	
	Make	:	
	Size( LXWXH), mm	:	
	No. of tubes	:	
1.2.5.3	EGR:		
	Make	:	
	Туре	:	
	Part No.	:	
1.2.5.4	Exhaust treatment system:		
1.2.5.4.1	Diesel Oxidation Catalyst (DOC):		
	Make	:	
	DOC description	:	
	Part No.	:	
	Location	••	
1.2.5.4.2	Selective catalyst Reduction (SCR):		
	Make	••	
	Description	••	
	Location	:	
	Details of diesel exhaust fluid tank:		
	Capacity, 1	••	
	Location	:	
	Material of construction	:	
	Provision of draining	••	
	Recommended diesel exhaust fluid	:	
1.2.6	Lubrication system	:	
	Туре	:	
	Type of oil pump	:	
	Method of drive	:	
	Lube oil pump rpm corresponding to rated	:	
	rpm of engine, rpm		
	Oil sump capacity, l	:	
	1		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hısar	
Signature :	Make:	Signature :	l
Name :	Model:	Name:	l
Designation:	Sheet No of	Designation:	l
Date :		Date:	l

	Oil change period, h	:	
	Recommended grade of oil	:	
1.2.6.1	Filters:		
	Make	:	
	Numbers	:	
	Type of oil filters	:	
	Relief valve pressure setting, kgf/cm <sup>2</sup> ,	:	
	Minimum permissible pressure, kgf/cm <sup>2</sup>	:	
1.2.6.2	Provision of oil cooler:		
	Туре	:	
	Make	:	
	Part No.	:	
	No. of plates	:	
1.2.7	Cooling system:	•	
1,2,,	Type	:	
1.2.7.1	Water pump:		
	Make	:	
	Туре	:	
	No. of vanes	:	
	Dia. of impeller	:	
	Method of drive	:	
1.2.7.2	Details of fan:		
	Material & type	:	
	No. of blade	:	
	Size, mm	:	
1.2.7.3	Radiator:		
	Make	:	
	Type of radiator cap	:	
	Radiator cap pressure, kgf/cm <sup>2</sup>		
	Means of temperature control	:	
	Type of thermostat	:	
	Bare radiator capacity, 1	:	
	Total coolant capacity, l	:	
	Means of grill cleaning, if any	:	
	Recommended grade of coolant	:	
	Coolant water ratio	:	
1.2.8	Details of Air Compressor if any	:	
1.2.9	Starting system:		
	Type	:	
	Any aid for cold starting	:	
	Any other device provided for easy starting	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar	
Signature :	Make:	Signature :	
Name :	Model:	Name:	
Designation:	Sheet No of	Designation:	
Date :		Date:	

1.2.10	Electrical syst	em:				
1.2.10.1	Starter motor	:				
	Make		:			
	Type		:			
	Model/ Group	combination No.	:			
	Capacity/Powe	er, kW	:			
	Location		:			
1.2.10.2	Alternator:					
	Make		:			
	Model/Group o	combination No.	:			
	Output rating		:			
	Location		:			
	Method of driv	ve .	:			
1.2.10.3	Voltage regula	ator	:			
1.2.10.4	Battery:					
	Make		:			
	Model/Type N	0.	:			
	Type Capacity		:			
			:			
	No. & location		:			
1.2.10.5	Details of light	ts:				
Description	on	No. & capacity of bulb		bove ground to the e of beam (mm)	Size of beam. (mm)	Distance from centre of the

Description	No. & capacity of	Height above ground to the		Size of	Distance from
	bulb	centre of beam (mm)		beam, (mm)	centre of the
		As per	As		beam to outside
		requirements	observed		edge of combine
		of CMVR			(mm)
Head lights		3000 (Max.)			
Front turn indicator light		2100 (Max.)			
Front parking light		2100 (Max.)			
Front field working lights		Not applicable			
Grain unloading light		Not applicable			
Side inspection light		Not applicable			
Engine inspection light		Not applicable			
Top rear light		Not applicable			
Rear turn indicator light		2100 (Max.)			
Rear parking cum		2100 (Max.)			
position light					
Rear brake light		2100 (Max.)			
Reverse gear indicator		2100 (Max.)			
light					
Number plate light		2100 (Max.)			
Straw walker inspection		2100 (Max.)			
light					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation:	Sheet No of	Designation:		
Date :		Date:		

	:									
Front reflec	Front reflectors			00 (Ma	ax.)					
Rear reflect	Lear reflectors			00 (Ma	ax.)					
Side reflecte	Side reflectors			Not applicable						
SMVE			Not	applic	able					
Trailer ligh	ht:									
Brake light			21	00 (Ma	ax.)					
Turn indica	tor light		21	00 (Ma	ax.)					
Parking co	um position		21	00 (Ma	ax.)					
light										
Reverse ge	ear indicator		21	00 (Ma	ax.)					
light										
Number pla	_		21	00 (Ma	ax.)					
Reflectors:										
Rear reflect	tor		21	00 (Ma	ax.)					
Side reflecte	or		21	00 (Ma	ax.)					
SMVE			Not	applic	able					
			- 1 100	чррич						
l —	Horn:									
l —	Make			:						
	Type			:						
	Numbers			:						
	Location			:						
	Combine:	,								
	Wheel equipm	ents:								
l	Drive wheel:									
	Make			:						
	Type Location			:						
		Dly matin a		:						
_	Number, Size &			:						
L	Track width, m	tyre pressure, kPa		:						
		ty at recommended tyre		:						
		ty at recommended tyre		•						
	pressure, kg 1.3.1.2 Steered wheel:									
l —	Make			:						
L	Туре			:						
	Location			:						
Number/size & ply rating			:							
Track width (mm)			:							
Recommended tyre pressure, kPa			:							
L		ty at recommended tyre		:						
	pressure, kg	i, at recommended tyle		•						
1 1	p. 500010, NG				1					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

1.3.1.3		base, mn		:			
1.3.2	Transn	nission sy	ystem:				
1.3.2.1	Clutch	:				Main clutch	PTO clutch
	Make			:			
	Type			:			
	Size, m	m		:			
	No. of	friction di	iscs	:			
	Locatio	Location					
	Method	Method of operation					
1.3.2.2	Gear b	ox:					
	Make			:			
	Type			:			
	Locatio			:			
			orward & Reverse)	:			
		l of drive		:			
		l of gear s	shifting	:			
	Oil cap			:			
			grade of oil	:			
	Oil change period, h		:				
1.3.2.3	Final drive:						
	Make			:			
	Type			:			
		ion ratio		:			
	Locatio			:			
	Oil cap			:			
			grade of oil	:			
		nge perio		:			
1.3.2.4		ntial uni	<u>t:</u>				
	Type			:			
		ion ratio		:			
	Oil cap			:			
			grade of oil	:			
		nge perio		:			
1.3.2.5	l .	al speed:					
			No. of engine revolutions for one revolution of driving wheel		rpm when fitte	rated engine speed of ed with size n radius index. (kmph)	
Forward		1					
		2					
		3					
		4					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar	
Signature :	Make:	Signature:	
Name :	Model:	Name:	
Designation:	Sheet No of	Designation:	
Date :		Date:	

Reverse		1			
		2			
1.3.3	Brak	es:			
1.3.3.1	Servi	ce brake	:		
	Make	;		:-	
	Туре		:		
			noe at each wheel side	:	
	(cm <sup>2</sup> )				
	Locat			:	
		od of ope		:	
1.3.3.2		ing brake	e:		
	Make			:	
		and locat		:	
		od of ope		:	
1.3.4		ing syste	m:		
	Make			:	
	Type			:	
			combination number	:	
		diameter	of steering control wheel,	:	
	mm	1 0			
105		od of ope		:	
1.3.5		aulic sys			
1.3.5.1		aulic pui	mp:		
	Type			:	
	Make			:	
		el/Part No		:	
	Numl			:	
1252	Locat		C	:	
1.3.5.2			mp for steering:		
	Type			:	
	Make			:	
	Mode			:	
	Numl			:	
	Locat	od of driv	70	:	
1.3.5.3	l l			:	
1.3.5.3			lic cylinders	:	
1.3.0		assembly	· · · · · · · · · · · · · · · · · · ·		
	Type		ahar of tina hara	:	
			nber of tine bars rs (mm):	:	
	-Dia.	or une da	1.2 (mm):		
		rth		:	
	-Leng		ng width of roal man	:	
	D1a. a	ına workı	ng width of reel, mm	:	

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

	Range of speed corresponding to	:	
	recommended no load speed of engine		
	for field work, rpm		
	Number of tines on each bar and their	:	
	spacing, mm		
	Maximum distance ahead of cutter bar	:	
	points, mm		
	Maximum distance behind of cutter bar	:	
	points, mm		
	Maximum vertical distance above the	:	
	cutter bar points from the centre of reel,		
	mm		
	Arrangement for raising and lowering	:	
	the reel assembly		
	Arrangement for forward and backward	:	
	movement of reel		
	Arrangement for variation of angle of	:	
	tine		
	Type of reel drive	:	
	Method of tensioning	:	
	Safety device in reel drive	:	
1.3.7	Cutter bar assembly:		
	Working width, cm	:	
	Effective cutter bar width, cm	:	
	No. & spacing of knife guards, mm	:	
1.3.7.1	Knife blades		
	No. & type of knife blades	:	
	Marking:		
	Marking of manufacturer's name or	:	
	recognized trade mark		
	Marking of batch or code number	:	
	Type and thickness	:	
	Details of knife drive	:	
	Knife drive safety arrangement	:	
	Knife stroke, mm	:	
	Knife frequency per minute	:	
	Knife speed corresponding to	:	
	recommended no load speed of engine		
	for field work, rpm		
	No. & type of crop dividers	:	
4075	Arrangement for lifting lodged crop	:	
1.3.7.2	Knife guard:		
	No. & type of knife guard	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar	
Signature :	Make:	Signature:	
Name :	Model:	Name:	
Designation:	Sheet No of	Designation:	
Date :		Date:	

	Provision of anti corrosive coating	:	
	Marking:		
	Manufacturer's name or recognized trade mark	:	
	Batch or code number	:	
	Type	•	
1.3.7.3	Knife back:	•	
	Type	:	
	Marking:		
	Manufacturer's name or recognized	:	
	trade mark	•	
	Batch or code number		
1.2.0		:	
1.3.8	Cutting platform auger:		
	Type of crop conveyor Size of auger (Dia., Pitch & Width), mm	<u>:</u> :	
	Speed of auger corresponding to	•	
	recommended no load speed of engine	•	
	for field work, rpm		
	Arrangement for adjusting the clearance	:	
	of crop auger		
	Auger drive safety arrangement	:	
	Height of header assembly in the	:	
	transport position, cm		
	Arrangement for locking the header	:	
	assembly in raised position		
	Arrangement for side way tilting the	:	
	cutter bar		
1.3.9	Details of retractable fingers:		
	Number(s)	:	
	Range of throw out, mm	:	
	Axial spacing between the fingers, mm	:	
	Peripheral distance between the fingers,	:	
	mm	•	
	Arrangement for adjustment of fingers	:	
	length		
1.3.10	Undershot conveyor:		
	Type of feeder conveyor	:	
	No. size and spacing of comb bar	:	
	Conveyor drive safety arrangement	:	
	Arrangement for adjusting clearance	:	
	between comb and platform and		
	tensioning the chain		
	Speed corresponding to recommended	:	
	no load engine speed of engine for field		
	work, rpm		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

	No. & type of bearings	:		
1.3.11	Threshing drum:		For Wheat	For Paddy
	Type	:		
	Outer diameter and width, mm	:		
	Range of speed corresponding to	:		
	recommended no load speed of engine			
	for field work, rpm			
	No. of bars	:		
	No. of pegs and their spacing on each bar	:		
	No. of hub plate	:		
	Length of rasp bar/peg bar, mm	:		
	Height of pegs, mm	:		
	No. of rasps/100 mm	:		
	No. of rasps on each bar	•		
	Arrangement of bars	:		
	No. & type of bearings			
	Method of speed variation	:		
	Provision of stone trap	•		
	Safety device	:		
.3.12	Concave:	•	For Wheat	For Paddy
.5.12	Overall width of concave, mm	:	101 Wheat	ror raddy
	Effective width, mm	•		
	Type of concave	•		
	No. of bars	•		
		:		
	No. of pegs per bar & spacing	:		
	Height/ Spacing of the pegs, mm	:		
	Peripheral length, mm	:		
	Peripheral effective length, mm	:		
	Effective area, sq. cm.	:		
	Details of extension	:		
	Range of clearance (mm_:			
	-Front	:		
	-Rear	:		
	Method of adjusting the clearance	:		
	between drum and concave			
1.3.13	Rear beater:			
	Туре	:		
	Size of beater, length and width, mm	:		
	Speed corresponding to recommended	:		
	no load speed of engine for field work,	•		
	rpm			
1.3.14	Baffle plate (Deflector):			
	Type	•		
	No. of flap	:		
	Size of baffle plate, mm	:		
	Method of flap adjustment			
	Memod of map adjustifient	:		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

1.3.15	Separating mechanism:			
1.3.15.1	Straw walkers:			
	Number(s)	:		
	Type	:		
	Size of each straw walker (mm):			
	-Length	:		
	-Width	:		
	Area of each walker, sq. m	:		
	Lift/throw, mm	:		
	Oscillations per minutes corresponding to	:		
	recommended no load speed of engine for			
	field work, rpm			
	Provision for varying oscillations of straw	:		
	walkar			
	Type of extension	:		
	No. & type of bearings	:		
1.3.15.2	Stepped grain pan:			
	Туре	:		
	Size, mm	:		
	Effective area of pan, m <sup>2</sup>	:		
	Details of extension	:		
	Location	:		
	Inclination (degree)	:		
1.3.15.3	Cleaning sieves:			
1.3.15.3.1	Top sieve:			
	No. of sieve	:		
	Туре	:		
	Overall size of sieve (mm):		<u>Front</u>	Rear
	-Length	:		
	-Width	:		
	Effective cleaning area, mm <sup>2</sup>	:		
	Area of extension, mm <sup>2</sup>	:		
	Oscillation per minute corresponding to	:		
	recommended no load speed of engine for			
	field work			
	Lift/throw, mm	:		
	Arrangement for varying the opening of the sieve	:		
	Height of lips at max. opening, mm	:		
	Method of varying oscillation	:		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

	Method of drive	:	
1.3.15.3.2	Bottom sieve:		
	No. of sieve	:	
	Type	:	
	Overall size of sieve (mm):		
	-Length	:	
	-Width	:	
	Effective cleaning area, mm <sup>2</sup>	:	
	Oscillation per minute corresponding to recommended no load speed of engine for field work	•	
	Method of varying oscillation	:	
	Arrangement for varying the opening of the sieve	••	
1.3.15.4	Blower:		
	Dia. mm	:	
	Effective width, mm	:	
	No. & type of blade	:	
	Size of blade, mm:		
	Length	:	
	Width	:	
	Thickness	:	
	Type of drive	:	
	Method of varying the blower speed	:	
	Range of Speed corresponding to recommended no load speed of engine for field work, rpm	:	
	Method of controlling the air blast	••	
	No. & type of bearings	:	
1.3.15.5	Grain pan:		
	Type	:	
	Size, mm	:	
	Area, sq. m	:	
	Location	:	
	Inclination (degree) and method of adjustment (if any)	•	
1.3.15.6	Tailing pan:		
	Type	:	
	Number	:	
	Size, mm	:	
	Location Inclination, (degree) and method of	:	
	Inclination, (degree) and method of adjustment (if any)	:	
1.3.16	Grain conveying mechanism:		
1.3.16.1	Bottom grain conveyor:		
	Туре	:	

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI,Hisar	
Signature :	Make:	Signature :	
Name :	Model:	Name:	
Designation:	Sheet No of	Designation:	
Date :		Date:	

	Size of conveyor ( length Dia. and Pitch), mm		
	Speed corresponding to recommended no	:	
	load speed of engine for field work, rpm		
	Type of drive	:	
	No. & type of bearings	:	
1.3.16.2	Grain elevator:		
	Туре	:	
	Length of elevator, mm	:	
	Outside section, mm	:	
	No. & type of pad	:	
	Size of pads, mm	:	
	Spacing of pads, mm	:	
	Speed corresponding to recommended no	:	
	load speed of engine for field work, rpm		
	Type of chain	:	
	Size of chain (length, roller dia. &	:	
	pitch), mm		
	No. of roller	:	
	Elevator drive safety arrangement	:	
	Method of tensioning the chain	:	
	Type of drive	:	
	No. & type of bearings	:	
1.3.16.3	Upper grain auger:		
	Type	:	
	Size of auger (length, dia. and pitch), mm	:	
	Speed corresponding to recommended no	:	
	load speed of engine for field work, rpm		
	Drive safety arrangement	:	
	Type of drive	:	
	No. & type of bearings	:	
1.3.17	Tailing conveying mechanism:		
1.3.17.1	Bottom tailing auger:		
	Туре	:	
	Size of auger (length, dia. and pitch), mm	:	
	Speed corresponding to recommended no	:	
	load speed of engine for field work, rpm Type of drive		
	No. & type of bearings	:	
	Drive safety		
1.3.17.2	Tailing elevator:		
	Туре	:	
	Length of elevator box, mm	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

	Outer section, mm	:	
	No. & type of pads	:	
	Size of pads, mm	:	
	Spacing of pads, mm	:	
	Type of chain	:	
	Size of chain (length, roller dia. &	:	
	pitch), mm		
	No. of rollers	:	
	Method of tensioning the chain	:	
	Elevator drive safety arrangement	:	
	Type of drive	:	
	Speed corresponding to recommended no		
	load speed of engine for field work, rpm		
1.3.17.3	Upper tailing auger:		
	Type	:	
	Size (length, dia. and pitch), mm	:	
	Speed corresponding to recommended no load speed of engine for field work, rpm	•	
	Type of drive	:	
	No. & type of bearings	:	
	Drive safety	:	
1.3.18	Grain tank:		
	Location	:	
	Capacity:		
	Volume basis, m <sup>3</sup>	:	
	Method of agitating the grains in tank	:	
	Size of grain tank opening, mm	:	
	Provision of grain tank cover	:	
	Provision for indication of grain tank	:	
	filling		
1.3.18.1	Grain conveying auger (Bottom of grain ta	ank)	):
	Туре	:	
	Size (length, dia. & pitch), mm	:	
	Speed corresponding to recommended	:	
	field operation rpm of engine for field		
	work, rpm Type of drive		
	No. & type of bearings	:	
	Safety device	:	
1 2 10 2	· ·	•	
1.3.18.2	Grain unloading auger:		
	Type	:	
	Size (length Dia. and pitch), mm	:	
	Horizontal reach, cm	:	
	Discharge height above ground level, cm	:	
	Clearance height, cm	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

	Speed corresponding to recommended no load speed of engine for field work, rpm	:		
	Type of drive	:		
	No. & type of bearings	:		
	Safety device	:		
1.4	Safety devices provided on the machine:	•		
i)	Surety devices provided on the machine.			
ii)				
iii)				
iv)				
v)				
vi)				
vii) 1.5	Details of Operating controls gauges and	inat		
	<b>Details of Operating controls, gauges and</b>	inst	ruments:	
i)				
ii)				
iii)				
iv)				
v)				
vi)				
vii)	S4.	1		
1.6	Seat:			
	Make	:		
	Type	:		
	Type of suspension	:		
	Type of dampening	:		
	Horizontal adjustment, mm	:		
	Adjustment of back rest, mm	:		
1.7	Canopy:			
	Type	:		
	Canopy size, mm	:		
	Height from operator's platform, mm	:		
1.8	Overall dimensions of combine		Working Distriction	<u>Transport</u>
	harvester, cm Length		Position	<u>position</u>
	Width	:		
	Height	:		
1.9	Mass:	٠		
1.7	Mass of combine harvester with			
	coolant, fuel, lubricants & grain tank			
	(wheat) full and 75 kg mass on the			
	operator's seat, kg			
	Total	:		
	Front Rear	:		
	Rear	•		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

1.10	Ground clearance, mm		:		
1.11	Total number of lubricating	points:			
	Grease Nipples/grease holes		:		
	Greasing cups		:		
	Oiling		:		
2.12	Colour of combine:				
	Reel and chassis		:		
	Header unit and lower sheet	metal	:		
	Upper sheet metal		:		
	Wheel rim		:		
1.13	Header transport trailer				
	Type		••		
	Size(LxWxH), mm		••		
	No. & type of wheel		••		
	Make		••		
	Size & Ply rating		:		
	Track width, mm		:		
	Height of trailer hitch in transp	port position,	:		
	mm				
1.14	Details of labelling plate:				
1.15	Lubricants:				
Sr. No.	Particulars	As recomi	men	ded by the applicant	Oil change period (h)
1.	Engine oil	110 10001111		aca by the applicant	on enumer periou (II)
2.	Hydraulic oil and Power				
	steering oil				

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar			
Signature :	Make:	Signature:			
Name :	Model:	Name:			
Designation:	Sheet No of	Designation:			
Date :		Date:			

Transmission and final

drive housing oil

Grease

3.

4.

# 2. TECHNICAL SPECIFICATIONS FOR STRAW CHOPPER CUM SPREADER (SMS) (IF FITTED)

2.1	General:		
	Make of SMS	:	
	Model of SMS	:	
	Type of SMS	:	
	Name and complete Address of the	:	
	manufacturer of SMS including		
	PIN/Mob./email etc.		
2.2	Rotor:		
	Rotor Diameter, mm	:	
	No. of lugs on rotor in a row	:	
	No. of rows in a periphery	:	
	Width of flail, mm	:	
	Thickness of flail, mm	:	
	No. of flail in one set	:	
	Spacing between flail of one set, mm	:	
	Distance between adjacent flail unit,	:	
	mm		
	Rotor dia with blade, mm	:	
	No. of Rows/bar of serrated blade	:	
	No. of serrated blade in a row	:	
	Spacing between serrated blades, mm	:	
	Clearance between pivotal blade and	:	
	concave		
	Overlapping of pivotal blade on serrated	:	
	blade, mm		
	Rotor rpm	:	
2.3	Transmission:	:	
	Diameter of Drive Pulley	:	
	Diameter of Driven pulley	:	
2.4	Spreader:		
	Total no of flap, mm	:	
	Length of flap, cm	:	
	Distance between flaps (left to right)	:	
	Spreader angle with horizontal, Degree	:	
	Spreader angle with line of travel,	:	
	degree		
	Spreader sheet thickness, mm	:	
_	SMS sheet thickness, mm	:	
2.5	Overall dimensions (mm):		
	-Length	:	
	-Width	:	
	-Height	:	
2.6	Overall Mass (kg)	:	
2.7	SAFETY REQUIREMENT FOR SMS:		
	Guards over all moving parts	:	
	RPM indicator of rotor	:	
]	Overlapping of flail and fixed serrated	1:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation :	Sheet No of	Designation:		
Date :		Date:		

blade (The clearance should be					
adjustable)					
Details of labelling plate:					
		•			
	blade (The clearance should be adjustable)  Details of labelling plate:	adjustable)	adjustable)	adjustable)	adjustable)

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation:	Sheet No of	Designation :
Date :		Date:

## SELECTED PERFORMANCE AND OTHER CHARACTERISTICS AS PER IS 15806-2018

### (TO BE DECLARED BY THE APPLICANT)

S. No			Characteristics Category (Evaluative/ Non evaluative)		Tolerance	Declaration by applicant	Remarks
1		2	3	4	5	6	7
1.	Prin	ne mover performance:				<del>.</del>	
	a)	Max. Power (absolute) - Average max. power observed during 2 hrs. max. power test in natural ambient condition, kW	Evaluative	To be declared by manufacturer	Declared value to be achieved with a tolerance of ±5%		
	b)	Max. power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW	Evaluative	To be declared by manufacturer	-do-		
	c)	Power at rated engine speed, kW (under natural ambient condition)	Non- Evaluative	To be declared by manufacturer	-do-		
	d)	Specific fuel consumption corresponding to average maximum power under 2h maximum power test, g/kWh.	Evaluative	-do-	+5% (Max.)		
	e)	Max. smoke density (Bosch no.) at 80 percent load between the speed at max. power and 55 percent of speed at max. power 1000 rpm whichever is higher.	Evaluative	As per CMV rules.	Nil	-	
	f)	Max. crank shaft torque, (Nm) observed during the test after no load engine speed is adjusted as per manufacturer's recommendation for field work	Evaluative	To be declared by manufacturer	±8%		
	g)	Back up torque, %	Evaluative	7 percent, (Min.)	Nil	-	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar			
Signature :	Make:	Signature:			
Name :	Model:	Name:			
Designation:	Sheet No of	Designation:			
Date :		Date:			

1		2	3	4	5	6 7
	h)	Max. Operating temperatur	re, 0C:	<u>.                                      </u>		·
	i)	Engine oil	Evaluative	To be declared by manufacturer	Nil	The observed value under the high ambient condition should not exceed maximum safe value specified by the oil company which will be provided by the applicant
	ii)	Coolant	Evaluative	To be declared by manufacturer	Nil	The declared value should not exceed the boiling temperature of coolant under the pressurized or otherwise and the observed value under high ambient condition should not exceed the declaration.
	i)	Lubrication oil consumption, g/kWh	Evaluative	Not exceeding 1 % of specific fuel consumption at maximum power under high ambient condition	Nil	The value would be based on the test conducted under high ambient condition
2. B	rake r	oerformance at 24km/h or Ma	ximum Speed			
	a)	Max. Stopping distance at a force equal to or less than 600 N on brake pedal (m) – (cold brake and hot brake)	Evaluative	As per CMV rules.	Nil	
	b)	Max. Force exerted on brake pedal to achieve a deceleration of 2.5 m/sec <sup>2</sup>	Evaluative	≤ 600 N	Nil	
	c)	Effectiveness of parking brake at a force of 600 N at foot pedal or 400 N at Hand lever	Evaluative	As per CMV rules.	Nil	Based on the test conducted, Yes/No as the case may be indicated
3. M		ical vibration:	T			
	i)	Operator's platform	Non evaluative	120 μm max.	Nil	

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation:	Sheet No of	Designation:		
Date :		Date:		

1		2	3		4		5	6	7					
	ii)	Steering wheel	Non	150	μm	max.	Nil							
			evaluative											
	iii)	Seat with driver seated	Non	120	μm	max.	Nil							
			evaluative											
<b>4.</b> Ai		ner oil pull over:		1										
	i)	Max. oil pull over in percentage when tested in accordance with IS: 8122. (Part-2)-2000	Evaluative	0.20	% r	nax.	Nil							
5. No	oise m	easurement:		l			L							
	i)	Max. ambient noise emitted by combine at by-stander's position, dB (A)	Evaluative	As pe	er C	MVR	Nil		As per road transport condition					
	ii)	Max. noise at operator's ear level, dB (A)	Evaluative	As per CMVR		As per CMVR		As per CMVR		As per CMVR		Nil		In actual field condition
6. H	eader	Lifting Test:												
		Satisfactory completion of header lifting test	Evaluative	Satis com		etory tion	Nil		The observed Hydraulic oil temp should not exceed maximum safe value specified by the oil company which will be provided by the applicant.					
7. Di		limit:		1			2 714							
	a)	Thickness of brake lining	Evaluative	-	-do-	-	Nil							
	b)	Thickness of clutch plate	Evaluative	-	-do-	-	Nil							
8. Fi	eld pe	erformance:												
	a)	Suitability for crops	Evaluative	(Wheel	typ	paddy e) Paddy type)	Nil							
	b)	Processing losses (%)	Evaluative	Wheat Barley Rice Sorghum Maize Oil seed rape Soya- beans	: : :	Max 3% Max 4% Max 4% Max 3% Max 4% Max 4% Max 4%	Nil							
	c)	Threshing efficiency	Evaluative	-	:	≥ 98 % for wheat and paddy	Nil							

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation:	Sheet No of	Designation:		
Date :		Date:		

1		2	3		4	ļ	5	6	7
	d)	Cleaning efficiency	Evaluative	-	:	≥96 %	Nil		
						for wheat			
						and paddy	2.714		
	e)	Grain breakage in main grain tank	Evaluative	-	:	≤ 2.5 %	Nil		
	f)	Non collectable losses	Evaluative	-	:	≤ 2.5 %	Nil		
						for wheat,			
						paddy and			
						gram ≤ 4.0 %			
						for			
						soyabean			
9. Fi	eld pe	erformance for Straw Manag	ement System	(If fitted):		J		I	•
	a)	Uniformity of straw spread, CV (Percent)	Evaluative	-	:	20, Max.	-		
	b)	Weighted mean size of	Evaluative	-	:	20, Max.	-		
		chopped straw, cm							
10. S	Safety	requirements:		1			T	1	
	a)	Guards against all moving	Evaluative			hain drives,			As per IS
		parts/drives and hot part			hyc	lraulic pipes			12239 (Part
				(around workplace	(د.	operators			1)
	b)	Lighting arrangement	Evaluative			l as per	_		
	<i>D)</i>	Lighting arrangement	Lvardative			VR			
	c)	Grain tank cover	Evaluative	Е	sse	ntial	-		
	d)	Spark arrester in engine's	Evaluative	E	sse	ntial	-		
		exhaust in case naturally							
		aspirated engine							
	e)	Stone trap before concave	Evaluative			ntial	-		
	f)	Rear view mirror	Evaluative			ntial	-		
	g)	Fire extinguisher	Evaluative	E	sse	ntial	-		
	h)	Slip clutch at following drives –					-		
			Evaluative	F	sse	ntial			
		ii) Undershot conveyor	2,010.01		22.5				
		drive	Non		)pti	onal			
		iii) Grain & tailing elevator	evaluative		-				
			Non		)nti	onal			
			evaluative	Optional					
	i)	Anti slip surfaces at	Evaluative	E	sse	ntial			As per IS
		operator platform & ladder							12239 (Part
		& proper gripping for the							1)
	•.	control levers.	- ·						
	j)	Working clearance around	Evaluative	Essential 70mm, min		-		As per IS	
		the controls							12239 (Part
	k)	Labelling of control and	Evaluative		000	ntial			1) As per IS
	K)	gauges and operating	Lvaruative		SSC	116161	_		6283(Part
		controls							1)
	l		İ	I			<u> </u>	I .	-/

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation:	Sheet No of	Designation:		
Date :		Date:		

	1	2	3	4	5	6	7	
11.		Material of blades for guards, knife blades and knife back	Non evaluative	Conforming to IS 6024, IS 6025 and IS 10378 respectively	-			
12.		Material of blades for Straw Management System (SMS)		The flail and fixed blades shall be manufactured from steel having the following chemical composition or such other composition as shall be agreed between the supplier and the purchaser:  a) Carbon: 0.70 to 0.1 %  b) Manganese: 0.6 to 0.97 % c) Chrome: 0.1 % d) Nickle: 0.1 %	-			
13.		Bushes for flail blades	Non- Evaluative	Mild steel	1			
14.		Hardness of flail blades for Straw Management System (SMS)	Non- Evaluative	Bush section: 20 to 35 HRC Edge section(Hardened zone): 48 to 48 HRC Remainder zone: 20 to 35 HRC	-			
15.		Hardness of serrated blades for Straw Management System (SMS)	Non- Evaluative	Bush section: 20 to 35 HRC Edge section(Hardened zone): 48 to 58 HRC Remainder zone: 20 to 35 HRC	-			
16.		Safety Requirements for Straw Management System(if Fitted):						
	a)	Guards against all moving parts/drives and hot parts	Evaluative	Essential	-			
	b)	RPM indicator for rotor	Evaluative	Desirable	-			
	c)	Overlapping of flail and fixed serrated blades	Evaluative	Essential	-		The clearance of the flail and fixed serrated blades should be adjustable	

Place:	Signature
Date:	Name of the applicant
	Designation
	Address

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature : Name : Designation : Date :	Make :  Model : Sheet No of	Signature : Name : Designation : Date :