



भारत सरकार /GOVERNMENT OF INDIA

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान Northern Region Farm Machinery Training and Testing Institute ट्रैक्टर नगर, सिरसा रोड, हिसार)हरियाणा—(125001 TRACTOR NAGAR, SIRSA ROAD, HISAR (HARYANA)- 125 001 Website: http://nrfmtti.gov.in E-mail: fmti-nr@nic.in GSTIN:06AAAGN0273PIZ3 Tele./FAX: 01662-276984

TECHNICAL SPECIFICATIONS FOR TRACTOR OPERATED COMBINE HARVESTER FOR BATCH/VARIANT/ADMINISTRATIVE/TECHNICAL EXTENSION

Sr. No.	Particulars		Previous sample as per test report No	Present sample	Remarks
1	2	3	4	5	6
1.1	General: Name & address of manufacturer	:			
	Name & address of applicant/importer	:			
	Make	:			
	Model	:			
	Brand name (if any)	:			
	Туре	:			
	Year of manufacture	:			
	Serial No./Chassis No.	:			
	Country of origin	:			
	Type of crops recommended for harvesting	:			
1.2	Prime mover:				
1.2.1	Tractor:				
	Make	:			
	Model	:			
	Туре	:			
	Chassis No.				
1.2.2	Engine:				
	Make	:			
	Model	:			1
	Туре	:			
	Serial No.	:			1

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar	
Signature : Name :	Make : Model :	Signature : Name :	
Designation : Date :	Sheet No of	Designation : Date :	

1	2	3	4	5	6
	Engine speed (rpm) (Manufacturer's	reco	mmended setting):		
	Maximum speed at no load, rpm	:			
	Rated speed, rpm	:			
	No load engine speed recommended	:			
	for field operation, rpm				
	Low idle speed, rpm	:			
	Location	:			
	Country of origin	:			
	Whether the tractor has already been	:			
	tested by authorized testing centre (Yes/No)				
	If yes, then specify valid test report	:			
	No. and upload copy of the test report				
	Details of Emission Certificate if any	:			
1.2.1	Cylinder and cylinder head:				
	Number	:			
	Disposition	:			
	Bore/Stroke, mm	:			
	Capacity, cm ³	:			
	Compression ratio	:			
	Arrangement of valves	:			
	Type of cylinder liners	:			
	Type of head	:			
	Type of combustion chamber	:			
	Valve clearance in cold (mm):				
	-Inlet valve	:			
	-Exhaust valve	:			
1.2.2	Fuel system:				
	Type of fuel system	:			
1.2.2.1	Fuel tank:				
	Material	:			
	Size, mm	:			
	Capacity, 1				
		:			
1.2.2.2	Fuel feed pump:				
	Make	:			
	Туре	:			
	Model/Group combination number	:			
	Provision of sediment bowl	:			
1.2.2.3	Fuel filters:				
	Make	:			
	Model/Group combination No.	:			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3		4		5	6
	Number (s)	:					
	Type of element:						
	Primary	:					
	Secondary	:					
	Capacity of final stage filter, 1	:					
	Provision of water separator	:					
	Make	:					
	Location	:					
1.2.2.4	Fuel injection pump:						
	Make	:					
	Model/Group combination No.	:					
	Туре	:					
	Method of drive	:					
1.2.2.5	Fuel injectors:	1					
	Make	:					
	Туре	:					
	Model/Group combination No.	:					
	Injection opening pressure, kgf/cm ²	:					
	Injection timing, degree	:					
	Firing order	:					
1.2.3	Governor:						
	Make	:					
	Туре	:					
	Model/Group combination	:					
	number/Designation						
	Governed range of engine speed, rpm	:					
1.2.4	Air Intake System:						
	Туре	:					
1.2.4.1	Pre-cleaner:						
	Make	:					
	Туре	:					
	Number	:					
	Location	:					
1.2.4.2	Air cleaner:						
	Make	:					
	Туре	:					
	Number	:					
	Location	:					
	Type of element	:					
	Size of filter element (mm):		Primary (outer)	Secondary (inner)	Primary (outer)	Secondary (inner)	
	Inner dia.	:					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name :	Make : Model :	Signature : Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
	Outer dia.	:			
	Length	:			
	Service indicator	:			
	Dust unloading valve	:			
	Recommended service Schedule, h	:			
	Suction pressure at max. power, kPa	:			
1.2.5	Exhaust:				
	Make	:			
	Туре	:			
	Pressure at max. power, kPa	:			
	Provision of spark arresting device/any	:			
	other device				
1.2.5.1	Details of turbocharger:				
	Make	:			
	Model	:			
	Number of fan/wheels	:			
	Number of blades:				
	-Turbine wheel	:			
	-Compressor fan	:			
	Method of drive	:			
	Means of lubrication	:			
1.2.5.2	Charged air cooler (CAC) unit:				
	Туре	:			
	Make	:			
	Size(LXWXH), mm	:			
	No of Tubes	:			
1.2.5.3	EGR:				
	Make	:			
	Туре	:			
	Part No.	:			
1.2.5.4	Exhaust treatment system:				
1.2.5.4.1	Diesel Oxidation Catalyst (DOC):				
	Make	:			
	DOC description	:			
	Part No.	:			
	Location	:			
1.2.5.4.2	Selective catalyst Reduction (SCR):				
	Make	:			
	Description	:			
	Location	:			
	Details of diesel exhaust fluid tank:				

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
	Capacity, 1	:			
	Location	:			
	Material of construction	:			
	Provision of draining	:			
	Recommended diesel exhaust fluid	:			
1.2.6	Lubrication system:				
	Туре	:			
	Type of oil pump	:			
	Method of drive	:			
	Lube oil pump rpm corresponding to	:			
	rated rpm of engine, rpm				
	Oil sump capacity, l	:			
	Oil change period, h	:			
	Recommended grade of oil	:			
1.2.6.1	Filters:				
	Make	:			
	Numbers	:			
	Type of oil filters	:			
	Relief valve pressure setting, kgf/cm ² ,	:			
	Minimum permissible pressure,	:			
	kgf/cm ²				
1.2.6.2	Provision of oil cooler:				
	Туре	:			
	Make	:			
	Part No.	:			
	No. of plates	:			
1.2.7	Cooling system:				
1.2.7	Туре	:			
1.2.7.1	Water pump:	ŀ			
	Make	:			
	Туре	:			
	No. of vanes	:			
	Dia. of impeller	:			
	Method of drive	:			
1.2.7.2	Details of fan:				
-	Material & type	:			
	No. of blade	:			
	Size, mm	:			
1.2.7.3	Radiator:				
	Make	:			1

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
	Type of radiator cap	:			
	Radiator cap pressure, kgf/cm ²				
	Means of temperature control	:			
	Type of thermostat	:			
	Bare radiator capacity, 1	:			
	Total coolant capacity, l	:			
	Means of grill cleaning, if any	:			
	Recommended grade of coolant	:			
	Coolant water ratio	:			
1.2.8	Details of Air Compressor (if any)	:			
1.2.9	Starting system:				
	Туре	:			
	Any aid for cold starting	:			
	Any other device provided for easy	:			
	starting				
1.2.10	Electrical system:				
1.2.10.1	Starter motor:				
	Make	:			
	Туре	:			
	Model/ Group combination No.	:			
	Capacity/Power, kW	:			
	Location	:			
1.2.10.2	Alternator:				
	Make	:			
	Model/Group combination No.	:			
	Output rating	:			
	Location	:			
	Method of drive	:			
1.2.10.3	Voltage regulator	:			
1.2.10.4	Battery:				
	Make	:			
	Model/Type No.	:			
	Туре	:			
	Capacity	:			
	No. & location	:			
1.2.10.5	Details of lights:				

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1		2	3		4	5		6
1.2.10.5.1	Previous sam	ple:						
Description		No. & capacity of bulb	rec	Height above ground to tcentre of beam (mm)As perAs perrequirementsobserve		beam, (mm) columnation		stance from entre of the m to outside e of combine
Head lights				f CMVR 00 (Max.)				(mm)
÷	ndicator light			00 (Max.)				
Front parkin	6			00 (Max.)				
-	working lights			applicable				
Grain unloa				applicable				
Side inspec				applicable				
	bection light			applicable				
Top rear lig	\$			applicable				
· · ·	,			~ ~				
	ndicator light arking cum ht			00 (Max.) 00 (Max.)				
Rear brake			21	00 (Max.)				
Reverse g light	gear indicator		21	00 (Max.)				
Number pla				00 (Max.)				
	er inspection		21	00 (Max.)				
light 1.2.10.5.2	Ducasut comm						<u> </u>	
	Present samp			1, 1	1, ,1	<u> </u>		
Description	l	No. & capacity of bulb		ght above gr centre of bea	ım (mm)	Size of beam, (mm)	ce	stance from entre of the
				As per uirements f CMVR	As observed			m to outside e of combine (mm)
Head lights			30	00 (Max.)				
Front turn i	ndicator light		21	00 (Max.)				
Front parking	ng light		21	00 (Max.)				
Front field	working lights		Not	applicable				
Grain unloa	ading light		Not	applicable				
Side inspec	tion light		Not	applicable				
Engine insp	bection light		Not	applicable				
Top rear lig	,ht		Not	applicable				
Rear turn in	ndicator light		21	00 (Max.)				
position lig				00 (Max.)				
Rear brake				00 (Max.)				
Reverse g light				00 (Max.)				
Number pla	ate light		21	00 (Max.)				

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

Straw wall	ker inspection			2100 (Max.)					
light	I I I I I I I I I I I I I I I I I I I								
Reflectors	5:							-	
Front reflectors				2100 (Max.)					
Rear reflect	ctors			2100 (Max.)					
Side reflec	ctors		1	Not applicable					
SMVE			١	Not applicable					
Trailer lig	ght:	I	I			I			
Brake ligh	t			2100 (Max.)					
Turn indic	ator light			2100 (Max.)					
Parking	cum position			2100 (Max.)					
light									
Reverse	gear indicator			2100 (Max.)					
light									
Number pl	-			2100 (Max.)					
Reflectors		I			T			1	
Rear reflec	ctor			2100 (Max.)					
Side reflec	ctor			2100 (Max.)					
SMVE			١	Not applicable					
1		2	3	4			5	(6
1.2.10.6	Horn:			Previous sau asper test ro No		Pre	sent sample	Rema	rks
	Make		:	110					
	Туре		:						
	Numbers		:						
	Location		:						
1.3	Combine:								
1.3.1	Wheel equipn	nents:							
1.3.1.1	Drive wheel:								
	Make		:						
	Туре		:						
	Location		:						
	Number, Size	& Ply rating	:						
	Track width, n	nm	:						
		tyre pressure, kPa	:						
		ity at recommended	:						
	tyre pressure (1								
1.3.1.2	Steered wheel	:							
	Make		:						
	Туре								
	Location								

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3		4		5	6
	Number/size & ply rating	:					
	Track width (mm)	:					
	Recommended tyre pressure, kPa	:					
	Loading capacity at recommended	:					
	tyre pressure (kg)						
1.3.1.3	Wheel base, mm	:					
1.3.2	Transmission system:						
1.3.2.1	Clutch:		<u>Main</u> clutch	PTO clutch	<u>Main clutch</u>	PTO clutch	
	Make	:					
	Туре	:					
	Size, mm	:					
	No. of friction discs	:					
	Location	:					
	Method of operation	:					
1.3.2.2	Gear box:						
	Make	:					
	Туре	:					
	Location	:					
	No. of speeds (Forward & Reverse)	:					
	Method of drive	:					
	Method of gear shifting	:					
	Oil capacity, 1	:					
	Recommended grade of oil	:					
	Oil change period, h	:					
1.3.2.3	Final drive:						
	Make	:					
	Туре	:					
	Reduction ratio	:					
	Location	:					
	Oil capacity, 1	:					
	Recommended grade of oil	:					
	Oil change period, h	:					
1.3.2.4	Differential unit:						
	Туре	:					
	Reduction ratio	:					
	Oil capacity, l	:					
	Recommended grade of oil	:					
	Oil change period, h	:					
1.3.2.5	Nominal speed:	1					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2		3 4			5	6			
1.3.2.5.1	Previou	ıs sample	2:	_						
Moven	nent	Gear No.	No. of engine rev revolution of drivi				Nominal speed at rated engine speed of rpm when fitted with size of tyre of mm radius index. (kmph)			
Forward		1								
		2								
		3								
		4								
Reverse		1								
		2							-	
1.3.2.5.1	Present	t sample:								
Mover	nent	Gear No.	No. of engine rev revolution of drivi				rp	hal speed at rated engine m when fitted with of mm radius in	size	
Forward		1								
		2								
		3								
		4								
Reverse		1								
		2						1		
1.3.3	Brakes	:				Previous sa asper test re No	-	Present sample	Remarks	
1.3.3.1	Service	brake:								
	Make			:						
	Туре			:						
	Area of disc/shoe at each wheel side		e at each wheel side	:						
	(cm ²) Location			<u> </u>						
	Method of operation		:	_						
1.3.3.2	Parking brake:		•							
	Make	5		:						
	Type ar	nd locatio	n	:						
	Method	of operation	tion	:						
1.3.4		g system	•							
	Make			:						
	Туре			:						

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature : Name :	Make : Model :	Signature : Name :		
Name :	Model .	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3	4	5	6
	Model/Group combination number	:			
	Outer diameter of steering control	:			
	wheel, mm				
	Method of operation	:			
1.3.5	Hydraulic system:				
1.3.5.1	Hydraulic pump:				
	Туре	:			
	Make	:			
	Model/Part No.	:			
	Number(s)	:			
	Location	:			
1.3.5.2	Hydraulic pump for steering:				
	Туре	:			
	Make	:			
	Model	:			
	Number(s)	:			
	Location	:			
	Method of drive	:			
1.3.5.3	No. of hydraulic cylinders	:			
1.3.6	Reel assembly:				
	Туре	:			
	Type and Number of tine bars	:			
	Size of tine bars, mm:				
	Dia.	:			
	Length	:			
	Dia. and working width of reel, mm	:			
	Range of speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	Number of tines on each bar and	:			
	their spacing, mm				
	Maximum distance ahead of cutter	:			
	bar points, mm				
	Maximum distance behind of cutter	:			
	bar points, mm				
	Maximum vertical distance above	:			
	the cutter bar points from the centre				
	of reel, mm				
	Arrangement for raising and	:			
	lowering the reel assembly				

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3	4	5	6
	Arrangement for forward and	:			
	backward movement of reel				
	Arrangement for variation of angle	:			
	of tine				
	Type of reel drive	:			
	Method of tensioning	:			
	Safety device in reel drive	:			
1.3.7	Cutter bar assembly:				
	Working width, cm	:			
	Effective cutter bar width, cm	:			
	No. & spacing of knife guards, mm	:			
1.3.7.1	Knife blades				
	No. & type of knife blades	:			
	Marking:				
	Marking of manufacturer's name	:			
	or recognized trade mark				
	Marking of batch or code number	:			
	Type and thickness	:			
	Details of knife drive	:			
	Knife drive safety arrangement	:			
	Knife stroke, mm	:			
	Knife frequency per minute	:			
	Knife speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	No. & type of crop dividers	:			
	Arrangement for lifting lodged crop	:			
1.3.7.2	Knife guard:				
	No. & type of knife guard	:			
	Provision of anti corrosive coating	:			
	Marking:				
	Manufacturer's name or	:			
	recognized trade mark				
	Batch or code number	:			
1070	Type	:			
1.3.7.3	Knife back: Type	:			
	Marking:	•			
		-			
		:			
	recognized trade mark				
	Batch or code number	:			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3		4		5	6
1.3.8	Cutting platform auger:						
	Type of crop conveyor	:					
	Size of auger (Dia., Pitch & Width),	:					
	mm						
	Speed of auger corresponding to	:					
	recommended no load speed of						
	engine for field work, rpm						
	Arrangement for adjusting the	:					
	clearance of crop auger						
	Auger drive safety arrangement	:					
	Height of header assembly in the	:					
	transport position, cm						
	Arrangement for locking the	:					
	header assembly in raised						
	position						
	Arrangement for side way tilting	-					
	••••	:					
	the cutter bar						
1.3.9	Details of retractable fingers:						
	Number(s)	:					
	Range of throw out, mm	:					
	Axial spacing between the fingers,	:					
	mm Desighters 1 distances hadress on the						
	Peripheral distance between the	:					
	fingers, mm Arrangement for adjustment of	:					
	fingers length	·					
1.3.10	Undershot conveyor:						
1.5.10	Type of feeder conveyor	:					
	No. size and spacing of comb bar	:					
	Conveyor drive safety arrangement	:					
	Arrangement for adjusting	:					
	clearance between comb and						
	platform and tensioning the chain						
	Speed corresponding to	:					
	recommended no load engine speed						
	of engine for field work, rpm						
1.3.11	No. & type of bearings Threshing drum:	:	For Wheat	For Paddy	For Wheat	For Paddy	
1.3.11	Type	:	<u></u> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u> muuj</u>	<u></u> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u> uuuj</u>	
	Outer diameter and width, mm	•					
	Range of speed corresponding to	:					
	recommended no load speed of	•					
	engine for field work, rpm						
	No. of bars	:					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3		4		5	6
*	No. of pegs and their spacing on	:		-		-	, , , , , , , , , , , , , , , , , , ,
	each bar	•					
	No. of hub plate	:					
	Length of rasp bar/peg bar, mm	:					
	Height of pegs, mm	:					
	No. of rasps/100 mm	:					
	No. of rasps on each bar	:					
	Arrangement of bars	:					
	No. & type of bearings	:					
	Method of speed variation	:					
	Provision of stone trap	:					
	Safety device	•					
1.3.12	Concave:	•	For Wheat	For Paddy	For Wheat	For Paddy	
1.0.14	Overall width of concave, mm	:		<u> </u>			
	Effective width, mm	•					
	Type of concave	•					
	No. of bars	•					
	No. of pegs per bar & spacing	:					
	Height/ Spacing of the pegs, mm	:					
	Peripheral length, mm	:					
	Peripheral effective length, mm	:					
	Effective area, sq. cm.	:					
	Details of extension	:					
	Range of clearance, mm:						
	Front	:					
	Rear	:					
	Method of adjusting the clearance	:					
	between drum and concave						
1.3.13	Rear beater:						
	Туре	:					
	Size of beater, length and width,	:					
	mm						
	Speed corresponding to	:					
	recommended no load speed of						
	engine for field work, rpm						
1.3.14	Baffle plate (Deflector):						
	Туре	:					
	No. of flap	:					
	Size of baffle plate, mm	:					
	Method of flap adjustment	:					
1.3.15	Separating mechanism:						
1.3.15.1	Straw walkers:						
	Number(s)	:					
	Туре	:					
	Size of each straw walker(mm):	-					
	-Length	•					
	-Lengui	:					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3		4		5	6
	-Width	:		-		-	
	Area of each walker, sq. m	:					
	Lift/throw, mm	:					
	Oscillations per minutes	:					
	corresponding to recommended no						
	load speed of engine for field work,						
	rpm						
	Provision for varying oscillations of	:					
	straw walkar						
	Type of extension	:					
	No. & type of bearings	:					
1.3.15.2	Stepped grain pan:						
	Туре						
	Size, mm	:					
	Effective area of pan, m ²	:					
	Details of extension	:					
	Location	:					
	Inclination (degree)	:					
1.3.15.3	Cleaning sieves:						
1.3.15.3.	Top sieve:						
1	No. of sieve	:					
	Туре	:					
	Overall size of sieve (mm):		Front	<u>Rear</u>	Front	<u>Rear</u>	
	-Length	:					
	-Width	:					
	Effective cleaning area, mm ²	:					
	Area of extension, mm ²	:					
	Oscillation per minute corresponding to recommended no load speed of engine for field work	:					
	Lift/throw, mm	:			1		
	Arrangement for varying the opening of the sieve	:					
	Height of lips at max. opening,	:					
	mm						
	Method of varying oscillation	:					
	Method of drive						

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
1.3.15.3.2	Bottom sieve:				
	No. of sieve	:			
	Туре	:			
	Overall size of sieve, mm:				
	Length	:			
	Width	:			
	Effective cleaning area, mm ²	:			
	Oscillation per minute corresponding to recommended no load speed of engine for field work	:			
	Method of varying oscillation	:			
	Arrangement for varying the opening of the sieve	:			
1.3.15.4	Blower:				
	Dia. mm	:			
	Effective width, mm	:			
	No. & type of blade	:			
	Size of blade, mm:				
	Length	:			
	Width	:			
	Thickness	:			
	Type of drive	:			
	Method of varying the blower speed	:			
	Range of speed corresponding to recommended no load speed of engine for field work, rpm	:			
	Method of controlling the air blast	:			
	No. & type of bearings	:			
1.3.15.5	Grain pan:				
	Туре	:			
	Size, mm	:			
	Area, sq. m	:			
	Location	:			
	Inclination (degree) and method of adjustment (if any)	:			
1.3.15.6	Tailing pan:				
	Туре	:			
	Number	:			
	Size, mm	:			
	Location	:			
	Inclination, (degree) and method of adjustment (if any)	:			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
1.3.16	Grain conveying mechanism:				
1.3.16.1	Bottom grain conveyor:				
	Туре	:			
	Size of conveyor (length, dia. and				
	pitch), mm Speed corresponding to	:			
	recommended no load speed of	•			
	engine for field work, rpm				
	Type of drive				
		:			
1 2 1 (2	No. & type of bearings	:			
1.3.16.2	Grain elevator:				
	Туре	:			
	Length of elevator, mm	:			
	Outside section, mm	:			
	No. & type of pad	:			
	Size of pads, mm	:			
	Spacing of pads, mm	:			
	Speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	Type of chain	:			
	Size of chain (Length, Roller Dia.	:			
	& Pitch), mm	, ,			
	No. of roller	:			
	Elevator drive safety arrangement	:			
	Method of tensioning the chain	:			
	Type of drive	•			
	No. & type of bearings	•			
1.3.16.3	Upper grain auger:	•			
1.5.10.5	Type	:			
	Size of auger (length, dia. and	•			
	pitch), mm	•			
	Speed corresponding to				
	recommended no load speed of	:			
	engine for field work , rpm				
	Drive safety arrangement				
		:			
	Type of drive	•			
1 2 17	No. & type of bearings	:			
1.3.17	Tailing conveying mechanism:				
1.3.17.1	Bottom tailing auger:				
	Туре	:			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3	4	5	6
	Size of auger (length, Dia. and	:			
	pitch), mm				
	Speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	Type of drive	:			
	No. & type of bearings	:			
	Drive safety	:			
1.3.17.2	Tailing elevator:				
	Туре	:			
	Length of elevator box, mm	:			
	Outer section , mm	:			
	No. & type of pads	:			
	Size of pads, mm	:			
	Spacing of pads, mm	:			
	Type of chain	:			
	Size of chain (Length, Roller	:			
	dia. & Pitch), mm				
	No. of rollers	:			
	Method of tensioning the chain	:			
	Elevator drive safety	:			
	arrangement	-			
	Type of drive	:			
	Speed corresponding to	•			
	recommended no load speed of				
	engine for field work, rpm				
1.3.17.3	Upper tailing auger:				
	Туре	:			
	Size (length, dia. and pitch), mm	:			
	Speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	Type of drive	:			
	No. & type of bearings	:			
	Drive safety	:			
1.3.18	Grain tank:				
	Location	:			
	Capacity:				
	Volume basis, m ³	:			
	Method of agitating the grains	:			
	in tank				
	Size of grain tank opening, mm	:			
	Provision of grain tank cover	:			
	Provision for indication of grain	:			
	tank filling				

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1	2	3	4	5	6
1.3.18.1	Grain conveying auger (Bottom of	gra	in tank):		
	Туре	:			
	Size (length, dia. & pitch), mm	:			
	Speed corresponding to	:			
	recommended field operation rpm				
	of engine for field work, rpm				
	Type of drive	:			
	No. & type of bearings	:			
	Safety device	:			
1.3.18.2	Grain unloading auger:				
	Туре	:			
	Size (length Dia. and pitch), mm	:			
	Horizontal reach, cm	:			
	Discharge height above ground level, cm	:			
	Clearance height, cm	:			
	Speed corresponding to	:			
	recommended no load speed of				
	engine for field work, rpm				
	Type of drive	:			
	No. & type of bearings	:			
	Safety device	:			
1.4	Safety devices provided on the ma	chin	e;		
1.4.1	Previous sample:				
i)					
ii)					
iii)					
iv)					
v)					
vi)					
vii)				1	1
1.4.2	Present sample:				
i)					
ii)					
iii)					
iv)					
v)					
vi)					
vii)			1		
1.5 1.5.1	Details of operating controls, gaug	es a	nd instruments		
	Previous sample:				
i)					
ii)					
iii) iv)					
v)					
• /					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name : Designation :	Make : Model : Sheet No of	Signature : Name : Designation :
Date :		Date :

vi)							
vii)							
1.5.2	Present sample:						
i)							
ii)							
iii)							
iv)							
v)							
vi)							
vii)							
1.6	Seat:		Previous asper tes No	-	Present	sample	Remarks
	Make	:					
	Туре	:					
	Type of suspension	:					
	Type of dampening	:					
	Horizontal adjustment, mm	:					
	Adjustment of back rest, mm	:					
1.7	Canopy:						
	Туре	:					
	Canopy size, mm	:					
	Height from operator's platform, mm	:					
1.8	Overall dimensions of combine		Working	Transport	Working	Transport	
	harvester, cm		Position	<u>position</u>	Position	position	
	Length	:					
	Width	:					
	Height	:					
1.9	Mass:						
	Mass of combine harvester with coolant, fuel, lubricants & grain tank (wheat) full and 75 kg mass on the operator's seat, kg						
	Total	:					
	Front	:					
	Rear	:					
1.10	Ground clearance, mm	:					
1.11	Total number of lubricating points						
1.11	Grease Nipples/grease holes	:					
1.11	Grease Nipples/grease holes Greasing cups	:					
	Grease Nipples/grease holes Greasing cups Oiling	:					
2.12	Grease Nipples/grease holes Greasing cups Oiling Colour of combine:	::					
	Grease Nipples/grease holesGreasing cupsOilingColour of combine:Reel and chassis	: : :					
	Grease Nipples/grease holesGreasing cupsOilingColour of combine:Reel and chassisHeader unit and lower sheetmetal	::					
	Grease Nipples/grease holesGreasing cupsOilingColour of combine:Reel and chassisHeader unit and lower sheet	: : :					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1	2	3	4	5	6
1.13	Header transport trailer				
	Туре	:			
	Size (L×W×H), mm	:			
	No. & type of wheel	:			
	Make	:			
	Size & Ply rating	:			
	Track width (mm)	:			
	Height of trailer hitch in transport	:			
	position, mm				
1.14	Details of labelling plate:				
1.15	Lubricants:				
1.15.1	Previous sample:				
Sr. No.	Particulars		As recommended b	by Oil chang	ge period (h)
			the applicant		
1.	Engine oil		the applicant		
		oil	the applicant		
2.	Hydraulic oil and Power steering				
	Hydraulic oil and Power steering Transmission and final drive ho				
2.	Hydraulic oil and Power steering				
2. 3.	Hydraulic oil and Power steering Transmission and final drive ho oil				
2. 3. 4.	Hydraulic oil and Power steering Transmission and final drive ho oil Grease		As recommended b	by Oil chan	ge period (h)
2. 3. 4. 1.15.2	Hydraulic oil and Power steering Transmission and final drive ho oil Grease Present sample:			by Oil chan	
2. 3. 4. 1.15.2 Sr. No. 1.	Hydraulic oil and Power steering Transmission and final drive ho oil Grease Present sample: Particulars Engine oil	pusing	As recommended b	by Oil chan	
2. 3. 4. 1.15.2 Sr. No.	Hydraulic oil and Power steering Transmission and final drive ho oil Grease Present sample: Particulars	oil	As recommended b the applicant	by Oil chan	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

2. TECHNICAL SPECIFICATIONS FOR STRAW CHOPPER CUM SPREADER (SMS) (IF FITTED)

2.1	General:		
	Make of SMS	:	
	Model of SMS	:	
	Type of SMS	:	
	Name and complete Address of the	:	
	manufacturer of SMS including		
	PIN/Mob./email etc.		
2.2	Rotor:		
	Rotor Diameter, mm	:	
	No. of lugs on rotor in a row	:	
	No. of rows in a periphery	:	
	Width of flail, mm	:	
	Thickness of flail, mm	:	
	No. of flail in one set	:	
	Spacing between flail of one set, mm	:	
	Distance between adjacent flail unit,	:	
	mm		
	Rotor dia with blade, mm	:	
	No. of Rows/bar of serrated blade	:	
	No. of serrated blade in a row	:	
	Spacing between serrated blades, mm		
	Clearance between pivotal blade and	:	
	concave	•	
	Overlapping of pivotal blade on serrated	:	
	blade, mm	•	
	Rotor rpm	:	
2.3	Transmission:		
2.0	Diameter of Drive Pulley	:	
	Diameter of Driven pulley	•	
2.4	Spreader:	•	
2.7	Total no of flap, mm	:	
	Length of flap, cm	•	
	Distance between flaps (left to right)	•	
	Spreader angle with horizontal, Degree	:	
	Spreader angle with horizontal, Degree	•	
		:	
	degree		
	Spreader sheet thickness, mm	:	
2.5	SMS sheet thickness, mm	:	
2.5	Overall dimensions (mm):		
	Length	:	
	Width	:	
A <i>i</i>	Height	:	
2.6	Overall Mass (kg)	:	<u> </u>
2.7	SAFETY REQUIREMENT FOR SMS:		
	Guards over all moving parts	:	
	RPM indicator of rotor	:	<u> </u>
	Overlapping of flail and fixed serrated	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name : Designation :	Make : Model : Sheet No of	Signature : Name : Designation :
Date :		Date :

	blade (The clearance should be adjustable)	
2.10	Details of labelling plate:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name :	Make : Model :	Signature : Name :
Designation : Date :	Sheet No of	Designation : Date :

SELECTED PERFORMANCE AND OTHER CHARACTERISTICS AS PER IS 15806-2018 (TO BE DECLARED BY THE APPLICANT)

S. No		Characteristics	Category (Evaluative/ Non evaluative)	Requirement	Tolerance	Declarati- on by applicant (Previous/ Present sample	Remarks
1		2	3	4	5	6	7
1.		ne mover performance:				Г — Г	
	a)	Max. Power (absolute)- Average max. power observed during 2 hrs. max. power test in natural ambient condition, kW	Evaluative	To be declared by manufacturer	Declared value to be achieved with a tolerance of $\pm 5\%$		
	b)	Max. power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW	Evaluative	To be declared by manufacturer	-do-		
	c)	Power at rated engine speed, kW (under natural ambient condition)	Non- Evaluative	To be declared by manufacturer	-do-		
	d)	Specific fuel consumption corresponding to average maximum power under 2h maximum power test, g/kWh.	Evaluative	-do-	+5% (Max.)		
	e)	Max. smoke density (Bosch no.) at 80 percent load between the speed at max. power and 55 percent of speed at max. power or 1000 rpm whichever is higher.	Evaluative	As per CMV rules.	Nil	-	
	f)	Max. crank shaft torque, (Nm) observed during the test after no load engine speed is adjusted as per manufacturer's recommendation for field work	Evaluative	To be declared by manufacturer	±8%		
	g)	Back up torque, %	Evaluative	7 percent, (Min.)	Nil	-	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make :	Signature :
Name :	Model :	Name :
Designation :	Sheet No of	Designation :
Date :		Date :

1		2	3	4	5	6	7
	h)	Max. Operating temperature	re, 0C:				
	i)	Engine oil	Evaluative	To be declared by manufacturer	Nil		The observed value under the high ambient condition should not exceed maximum safe value specified by the oil company which will be provided by the applicant
	ii)	Coolant	Evaluative	To be declared by manufacturer	Nil		The declared value should not exceed the boiling temperature of coolant under the pressurized or otherwise and the observed value under high ambient condition should not exceed the declaration.
	i)	Lubrication oil consumption, g/kWh	Evaluative	Not exceeding 1 % of specific fuel consumption at maximum power under high ambient condition	Nil		The value would be based on the test conducted under high ambient condition
2. B	rake p	performance at 24km/h or Ma	ximum Speed	whichever is less	I		•
	a)	Max. Stopping distance at a force equal to or less than 600 N on brake pedal (m) – (cold brake and hot brake)	Evaluative	As per CMV rules.	Nil		
	b)	Max. Force exerted on brake pedal to achieve a deceleration of 2.5 m/sec ²	Evaluative	≤ 600 N	Nil		
	c)	Effectiveness of parking brake at a force of 600 N at foot pedal or 400 N at Hand lever	Evaluative	As per CMV rules.	Nil		Based on the test conducted, Yes/No as the case may be indicated

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1		2	3	4	5	6	7
3. M	echan	nical vibration:					
	i)	Operator's platform	Non evaluative	120 µm max.	Nil		
	ii)	Steering wheel	Non evaluative	150 μm max.	Nil		
	iii)	Seat with driver seated	Non evaluative	120 µm max.	Nil		
4. Ai	r clea	ner oil pull over:					
	i)	Max. oil pull over in percentage when tested in accordance with IS: 8122. (Part-2)-2000	Evaluative	0.20% max.	Nil		
5. No	oise m	easurement:		·			
	i)	Max. ambient noise emitted by combine at by-stander's position, dB (A)	Evaluative	as per CMVR	Nil		As per road transport condition
	ii)	Max. noise at operator's ear level, dB (A)	Evaluative	as per CMVR	Nil		In actual field condition
6. He	eader	Lifting Test:			11		
		Satisfactory completion of header lifting test	Evaluative	Satisfactory completion	Nil		The observed Hydraulic oil temp should not exceed maximum safe value specified by the oil company which will be provided by the applicant.
7. Di	scard	limit:					
	a)	Thickness of brake lining	Evaluative	-do-	Nil		
	b)	Thickness of clutch plate	Evaluative	-do-	Nil		
8. Fi	eld pe	erformance:					
	a)	Suitability for crops	Evaluative	Wheat & paddy (Wheel type) Paddy (Track type)	Nil		
	b)	Processing losses (%)	Evaluative	Wheat:Max 3%Barley:Max 4%Rice:Max 4%Sorghum:Max 3%Maize:Max 4%OilMax 4%seed.rape:Max 5%Soyabeans.	Nil		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1		2	3		4		5	6	7
	c)	Threshing efficiency	Evaluative	-	••	\geq 98 % for wheat and paddy	Nil		
	d)	Cleaning efficiency	Evaluative	-	••	\geq 96 % for wheat and paddy	Nil		
	e)	Grain breakage in main grain tank	Evaluative	-	:	\leq 2.5 %	Nil		
	f)	Non collectable losses	Evaluative	-	•	$\leq 2.5 \%$ for wheat, paddy and gram $\leq 4.0 \%$ for soyabean	Nil		
9. Fi	ield po	erformance for Straw Mana	gement System	(If fitted):	:				
	a)	Uniformity of straw spread, CV (Percent)	Evaluative	-	:	20, Max.	-		
	b)	Weighted mean size of chopped straw, cm	Evaluative	-	:	20, Max.	-		
10. \$	Safety	requirements:							_
	a)	Guards against all moving parts/drives and hot part	Evaluative	pulleys, pipes		ain drives, hydraulic (around orkplace)			As per IS 12239 (Part 1)
	b)	Lighting arrangement	Evaluative			as per √R	-		
	c)	Grain tank cover	Evaluative	Es	ser	ntial	-		
	d)	Spark arrester in engine's exhaust in case naturally aspirated engine	Evaluative			ıtial	-		
	e)	Stone trap before concave	Evaluative			ntial	-		
	f)	Rear view mirror	Evaluative			itial	-		
	<u>g)</u> h)	Fire extinguisher Slip clutch at following drives – i) Cutting platform auger	Evaluative Evaluative			ntial	-		
		ii) Undershot conveyor drive iii) Grain & tailing elevator	Non evaluative Non			onal onal			
			evaluative						
	i)	Anti slip surfaces at operator platform & ladder & proper gripping for the control levers.	Evaluative	Es	ser	tial	-		As per IS 12239 (Part 1)

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		

1		2	3	4	5	6	7
	j)	Working clearance around the controls	Evaluative	Essential 70mm, min	-		As per IS 12239 (Part 1)
	k)	Labelling of control and gauges and operating controls	Evaluative	Essential	-		As per IS 6283(Part 1)
11.		Material of blades for guards, knife blades and knife back	Non evaluative	tive Conforming to IS 6024, IS 6025 and IS 10378 respectively		-	-
12.		Material of blades for Straw Management System (SMS)	Non- Evaluative	The flail and fixed blades shall be manufactured from steel having the following chemical composition or such other composition as shall be agreed between the supplier and the purchaser: a) Carbon : 0.70 to 0.1 % b) Manganese : 0.6 to 0.97 % c) Chrome : 0.1 % d) Nickle : 0.1 %	-		
13.		Bushes for flail blades	Non- Evaluative	Mild steel	-		
14.		Hardness of flail blades for Straw Management System (SMS)	Non- Evaluative	Bush section : 20 to 35 HRC Edge section(Hardened zone) : 48 to 48 HRC Remainder zone: 20 to 35 HRC	-		
15.		Hardness of serrated blades for Straw Management System (SMS)	Non- Evaluative	Bush section : 20 to 35 HRC Edge section(Hardened zone) : 48 to 58 HRC Remainder zone: 20 to 35 HRC	-		
16.		Safety Requirements for St	traw Managem	ent System (if Fitted):			•
	a)	Guards against all moving parts/drives and hot parts	Evaluative	Essential	-		
	b)	RPM indicator for rotor	Evaluative	Desirable	-		
	c)	Overlapping of flail and fixed serrated blades	Evaluative	Essential	-		The clearance of the flail and fixed serrated blades should be adjustable

Place:

Date:

Signature-----

Name of the applicant-----

Designation------Address------

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make :	Signature :		
Name :	Model :	Name :		
Designation :	Sheet No of	Designation :		
Date :		Date :		