



भारत सरकार /GOVERNMENT OF INDIA

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute ट्रैक्टर नगर, सिरसा रोड, हिसार)हरियाणा—(125001 TRACTOR NAGAR, SIRSA ROAD, HISAR (HARYANA)-125001 Website: http://nrfmtti.gov.in E-mail: fmti-nr@nic.in GSTIN:06AAAGN0273PIZ3 Tele./FAX: 01662-276984

TECHNICAL SPECIFICATIONS FOR SELF PROPELLED COMBINE HARVESTER (WHEEL TYPE) FOR BATCH/ADMINISTRATIVE/TECHNICAL EXTENSION

Sr. No.	Particulars		Previous sample as per test report No	Present sample	Remarks
1	2	3	4	5	6
1.1	General:			<u> </u>	
	Name & address of manufacturer	:			
	Name & address of applicant/importer	:			
	Make	:			
	Model	:			
	Brand name (if any)	:			
	Туре	:			
	Year of manufacture	:			
	Serial No./Chassis No.	:			
	Country of origin	:			
	Type of crops recommended for harvesting	:			
1.2	Prime mover:				
	Make	:			
	Model	:			
	Туре	:			
	Serial No.	:			
	Engine speed (rpm) (Manufacturer's red	com	mended setting):	•	•
	Maximum speed at no load, rpm	:			
	Rated speed, rpm	:			
	No load engine speed recommended for field operation, rpm	:			
	Low idle speed, rpm	:			
	Location	:			
	Country of origin	:			
	Whether the prime mover has already been tested by authorized testing centre (Yes/No)	:			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	4	5	6
	If yes, then specify valid test report No.	:			
	and upload copy of the test report				
	Details of Emission Certificate if any	:			
1.2.1	Cylinder and cylinder head:				
	Number	:			
	Disposition	:			
	Bore/Stroke, mm	:			
	Capacity, cm ³	:			
	Compression ratio	:			
	Arrangement of valves	:			
	Type of cylinder liners	:			
	Type of head	:			
	Type of combustion chamber	:			
	Valve clearance in cold (mm):				
	-Inlet valve	:			
	-Exhaust valve	:			
1.2.2	Fuel system:				
	Type of fuel system	:			
1.2.2.1	Fuel tank:				
	Material				
	Size, mm	:			
	Capacity, 1	:			
1.2.2.2	Fuel feed pump:				
1.2.2.2	Make	:			
	Type	:			
	Model/Group combination number	:			
	Provision of sediment bowl	:			
1.2.2.3	Fuel filters:	•			
1.2.2.3	Make	1.1			
		:			
	Model/Group combination No. Number (s)	-			
	. ,	•			
	Type of element:	1.1			
	Primary	:			
	Secondary Consider Screen to the Street	:			
	Capacity of final stage filter, l	:			
	Provision of water separator	:			
	Make	:			
1001	Location	:			
1.2.2.4	Fuel injection pump	1 1			
	Make	:			
	Model/Group combination No.	:			
	Туре	:			
	Method of drive	:			
1.2.2.5	Fuel injectors:				
	Make	:			
	Туре	:			
Name of the Mo	anufacturer/ Applicant Document No, if any Revi	ision et	ratus Name of the T	Sest Agency: NRFMTTI, Hisar	
01 1110 1716			areas I raine or the l		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name : Designation : Date :	Make: Model: Sheet Noof	Signature : Name : Designation : Date :

1	2	3	4	1		5	6
	Model/Group combination No.	:					
	Injection opening pressure, kgf/cm ²	:					
	Injection timing, degree	:					
	Firing order	:					
1.2.3	Governor:			•			
	Make	:					
	Type	:					
	Model/Group combination	:					
	number/Designation						
	Governed range of engine speed, rpm	:					
1.2.4	Air Intake System:						
1011	Туре	:					
1.2.4.1	Pre-cleaner:						
	Make	:					
	Type	:					
	Number	:					
1010	Location	:					
1.2.4.2	Air cleaner:	1					
	Make	:					
	Type	:					
	Number	:					
	Location	:					
	Type of element	:		I.a		1 ~ .	
	Size of filter element, mm:		Primary (outer)	Secondary (inner)	Primary (outer)	Secondary (inner)	
	Inner dia.	:			· · ·		
	Outer dia.	:					
	Length	:					
	Service indicator	:		ı		•	
	Dust unloading valve	:					
	Recommended service Schedule, h	:					
	Suction pressure at max. power, kPa	:					
1.2.5	Exhaust:	1					
	Make	:					
	Type	:					
	Pressure at max. power, kPa	:					
	Provision of spark arresting device/any	:					
	other device						
1.2.5.1	Details of turbocharger;	1					
1.2.5.1				I			
1.2.5.1	Make	:					
1.2.5.1		:					
1.2.3.1	Make						
1.2.5.1	Make Model	:					
1.2.5.1	Make Model Number of fan/wheels	:					
1.2.5.1	Make Model Number of fan/wheels Number of blades: -Turbine wheel	:					
1.2.5.1	Make Model Number of fan/wheels Number of blades:	:					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

	I			ı					
1	2		3	4		5	6		
	Means of lubrication		:						
1.2.5.2	Charged air cooler (CAC) unit				1			
	Type		:						
	Make		:						
	Size(LXWXH), mm		:						
	No of Tubes		:						
1.2.5.3	EGR:			T		1			
	Make		:						
	Type		:						
	Part No.		:						
1.2.5.4	Exhaust treatment s								
1.2.5.4.1	Diesel Oxidation Cat	talyst (DOC):		T		1			
	Make		:						
	DOC description		:						
	Part No.		:						
	Location		:						
1.2.5.4.2	Selective catalyst Re	duction (SCR):				,			
	Make		:						
	Description		:						
	Location		:						
		Details of diesel exhaust fluid tank:							
	Capacity, l		:						
	Location		:						
	Material of constructi	on	:						
	Provision of draining		:						
	Recommended diesel	exhaust fluid	:						
1.2.6	Lubrication system:		1	T					
	Туре		:						
	Type of oil pump		:						
	Method of drive		:						
	Lube oil pump rpm co	orresponding to	:						
	rated rpm of engine, r	pm							
	Oil sump capacity, l		:						
	Oil change period, h		:						
	Recommended grade	of oil	:						
1.2.6.1	Filters:								
	Make		:						
	Numbers		:						
	Type of oil filters		:						
	Relief valve pressure	setting, kgf/cm ² ,	:						
	Minimum permissible	pressure, kgf/cm ²	:						
1.2.6.2	Provision of oil coole								
	Туре		:						
	Make		:						
			+						
V Cd 3.5	Part No.	D(NI 'C B '	:		N 04 5	Park A annua NID EN (EEE) 11'			
	ufacturer/ Applicant	Document No, if any Revi	sion s	ıacıs		Test Agency: NRFMTTI,Hisar			
Signature : Name :		Make : Model :			Signature : Name :				
		Sheet Noof			Designation :				

1	2	2	3	4		5	6
	No. of plates		:				
1.2.7	Cooling system:						
	Туре		:				
1.2.7.1	Water pump:		,				
	Make		:				
	Type		:				
	No. of vanes		:				
	Dia. of impeller		:				
	Method of drive		:				
1.2.7.2	Details of fan:		1				
	Material & type		:				
	No. of blade		:				
	Size, mm		:				
1.2.7.3	Radiator:		1 -				
	Make		:				
	Type of radiator cap		:				
	Radiator cap pressure	. kgf/cm ²	 				
	Means of temperature	_	:				
	Type of thermostat		•				
	Bare radiator capacity	v. 1	:				
	Total coolant capacity		:				
	Means of grill cleaning		:				
	Recommended grade		:				
	Coolant water ratio	or coorain	+				
1.2.8	Details of Air Comp	massam (if any)	:				
		oressor (ii aliy)					
1.2.9	Starting system:		1				
	Type		:				
	Any aid for cold starts	ing	:				
	Any other device prov	vided for easy	:				
1 2 10	starting						
1.2.10	Electrical system:						
1.2.10.1	Starter motor:		1				
	Make		:				
	Туре		:				
	Model/ Group combin	nation No.	:				
	Capacity/Power, kW		:				
	Location		:				
1.2.10.2	Alternator:		1	T			
	Make		:				
	Model/Group combination No.		:				
	Output rating		:				
	Location		:				
	Method of drive		:				
1.2.10.3	Voltage regulator		:				
	nufacturer/ Applicant	Document No, if any Revis	sion s	tatus		Test Agency: NRFMTTI,Hisar	
Signature : Name : Designation : Date :		Make : Model : Sheet Noof	_		Signature : Name : Designation : Date :		

1.2.10.4	Battery:	2	3	4	5	6
1,4,10,4	Make		:			
	Model/Type N	0	•			
	Type	· · · · · · · · · · · · · · · · · · ·				
	Capacity		+ +			
	No. & location		:			
1.2.10.5	Details of ligh					
1.2.10.5.1						
Description		No. & capacity of bulb	Height above g centre of be As per	eam (mm) As	Size of beam, (mm)	Distance from centre of the beam to outside
			requirements of CMVR	observed		edge of combine (mm)
Head light	re.		3000 (Max.)	+		(111111)
	indicator light		2100 (Max.)	1		
			` ,			
Front park			2100 (Max.)			
Front field lights	working		Not applicable			
Grain unlo	oading light		Not applicable			
Side inspec	•		Not applicable			
Engine ins	pection light		Not applicable			
Top rear li	ght		Not applicable			
Rear turn i	ndicator light		2100 (Max.)			
position lig			2100 (Max.)			
Rear brake			2100 (Max.)			
Reverse g light	gear indicator		2100 (Max.)			
Number pl	late light		2100 (Max.)			
Straw wall light	ker inspection		2100 (Max.)			
Reflectors	S:					
Front refle	ectors		2100 (Max.)			
Rear reflec	etors		2100 (Max.)			
Side reflec	ctors		Not applicable			
SMVE			Not applicable			
Trailer lig	ght:			1	ı	
Brake ligh			2100 (Max.)			
Turn indic			2100 (Max.)			
	cum position		2100 (Max.)			
Reverse g	gear indicator		2100 (Max.)			
light	laka liala		2100 (34			
Number pl	•		2100 (Max.)			
Reflectors			2100 (34		1	
Rear reflec		T	2100 (Max.)			
	nufacturer/ Applicant	Document No, if an	y Revision status		Test Agency: NRFM	TTI,Hisar
Signature : Name : Designation : Date :		Make : Model : Sheet No	of	Signature : Name : Designation Date :	:	

Side reflector		2100 (Max.)			
SMVE		Not applicable			
1.2.10.5.2 Present san	nple:				
Description	No. & capacity of bulb	Height above go centre of bea As per		Size of beam, (mm)	Distance from centre of the beam to outside
		requirements of CMVR	observed		edge of combine (mm)
Head lights		3000 (Max.)			
Front turn indicator light	t	2100 (Max.)			
Front parking light		2100 (Max.)			
Front field working lights		Not applicable			
Grain unloading light		Not applicable			
Side inspection light		Not applicable			
Engine inspection light		Not applicable			
Top rear light		Not applicable			
Rear turn indicator light		2100 (Max.)			
Rear parking cum position light	n	2100 (Max.)			
Rear brake light		2100 (Max.)			
Reverse gear indicator light		2100 (Max.)			
Number plate light		2100 (Max.)			
Straw walker inspection light		2100 (Max.)			
Reflectors:				Γ	
Front reflectors		2100 (Max.)			
Rear reflectors		2100 (Max.)			
Side reflectors		Not applicable			
SMVA		Not applicable			
Trailer light:					
Brake light		2100 (Max.)			
Turn indicator light		2100 (Max.)			
Parking cum position	1	2100 (Max.)			
light					
Reverse gear indicator	•	2100 (Max.)			
light					
Number plate light		2100 (Max.)			
Reflectors:	T	1 240 - 5 - 1		Γ	
Rear reflector		2100 (Max.)			
Side reflector		2100 (Max.)			
SMVE		Not applicable			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name :
Designation:	Sheet Noof	Designation:
Date :		Date:

		г т			
1 2 10 (2	3	4	5	6
1.2.10.6	Horn:	1			
	Make	:			
	Type	:			
	Numbers	:			
	Location	:			
1.3	Combine:				
1.3.1	Wheel equipments:				
1.3.1.1	Drive wheel:				
	Make	:			
	Type	:			
	Location	:			
	Number, size & ply rating	:			
	Track width, mm	:			
	Recommended tyre pressure, kPa	:			
	Loading capacity at recommended tyre	:			
	pressure (kg)				
1.3.1.2	Steered wheel:				
	Make	:			
	Туре	:			
	Location	:			
	Number/size & ply rating	:			
	Track width (mm)	:			
	Recommended tyre pressure, kPa	:			
	Loading capacity at recommended tyre	:			
	pressure (kg)				
1.3.1.3	Wheel base, mm:			1	
1.3.2	Transmission system				
1.3.2.1	Clutch				
	Make	:			
	Туре	:			
	Size, mm	:			
	No. of friction discs	:			
	Location	:			
	Method of operation	:			
1.3.2.2	Gear box			1	
	Make	:			
	Туре	:			
	Location	:			
	No. of speeds (Forward & Reverse)	:			
	Method of drive	:			
	Method of gear shifting	:			
	Oil capacity, l	:			
	Recommended grade of oil	:			
	Oil change period, h	:			
James - £41 N.f.	nufacturer/ Applicant Document No, if any Revision	<u> </u>	NT C4	Test Agency: NRFMTTI,Hi	204
varme of the ivia	muracturer/ Appricant Document No, it any Revision	on St	maine of the	rest Agency. NKFWH H,A	341

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature : Name : Designation : Date :	Make: Model: Sheet Noof	Signature : Name : Designation : Date :

1			2		3		4	5		6
1.3.2.3	Final d	rive:							•	
	Make				:					
	Type				:					
	Reducti	on ratio			:					
	Locatio	n			:					
	Oil capa	acity, l			:					
	Recom	nended g	rade of oil		:					
	Oil chai	nge perio	d, h		:					
1.3.2.4	Nomina	al speed:								
1.3.2.4.1	Previou	ıs sampl	2:							
Mover	nent	Gear	No. of engine revo			r one	Nominal spe	ed at rated e	engine	speed of
		No.	revolution of driving	ng wneei			of mm			size of tyre h)
			Variator	r setting				Variator	setting	
			Minimum	Ma	хiı	mum	Minin	num	N	Maximum
Forward		1								
		2								
		3								
Reverse		R								
1.3.2.4.2	Present	t sample:								
Mover	nent	Gear No.	No. of engine revolution of driving			r one	Nominal speed at rated engine speed of rpm when fitted with size of type of mm radius index. (kmph)		size of tyre	
			Variator	r setting	Variator setting					
			Minimum	Ma	хiı	mum	Minin	num	ľ	Maximum
Forward		1								
		2								
		3								
Reverse		R								
1.3.3	Brakes	:					•			
1.3.3.1	Service	brake:								
	Make			:						
	Type			:						
		disc/sho	e at each wheel side	:						
	(cm ²)									
	Locatio			:						
		of opera	tion	:						
1.3.3.2		g brake:								
	Make		:							
	3.1		:	-						
10:		of opera		:	-					
1.3.4		g system	:							
	Make			:						

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar		
Signature : Name : Designation : Date :	Make: Model: Sheet Noof	Signature: Name: Designation: Date:		

1.3.5.1 harvester's

:

1	2	3	4	5	6
	Model	:			
	Number(s)	:			
	Location	:			
	Method of drive	:			
1.3.5.3	Hydraulic tank :				
	Type	:			
	Number(s)	:			
	Location	:			
	Size (L \times W \times H), mm	:			
	Capacity of hydraulic tank, l	:			
	No. & type of oil filters	:			
	Recommended grade of oil	:			
	Oil change period, h	:			
1.3.5.4	No. of hydraulic cylinders	:			
1.3.6	Reel assembly:		,		
	Type	:			
	Type and Number of tine bars	:			
	Size of tine bars, mm:				
	Dia.	:			
	Length	:			
	Dia. and working width of reel, mm	:			
	Range of speed corresponding to	:			
	recommended no load speed of engine				
	for field work, rpm				
	Number of tines on each bar and their	:			
	spacing, mm Maximum distance ahead of cutter bar				
	points, mm	:			
	Maximum distance behind of cutter bar	:			
	points, mm	•			
	Maximum vertical distance above the				
	cutter bar points from the centre of reel,	•			
	mm				
	Arrangement for raising and lowering the	:			
	reel assembly				
	Arrangement for forward and backward	:			
	movement of reel				
	Arrangement for variation of angle of tine	:			
	Type of reel drive	:			
	Method of tensioning	:			
	Safety device in reel drive	:			
1.3.7	Cutter bar assembly:				
	Working width, cm	:			
	Effective cutter bar width, cm	:			
	No. & spacing of knife guards, mm	:			
					·

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	4	5	6
1.3.7.1	Knife blades				
	No. & type of knife blades	:			
	Marking:				
	Marking of manufacturer's name or recognized trade mark	:			
	Marking of batch or code number	:			
	Type and thickness	:			
	Details of knife drive	:			
	Knife drive safety arrangement	:			
	Knife stroke, mm	:			
	Knife frequency per minute	:			
	Knife speed corresponding to	:			
	recommended no load speed of engine				
	for field work, rpm				
	No. & type of crop dividers	:			
	Arrangement for lifting lodged crop	:			
1.3.7.2	Knife guard:	ı			
	No. & type of knife guard	:			
	Provision of anti corrosive coating	:			
	Marking:				
	Manufacturer's name or recognized trade mark	:			
	Batch or code number	:			
	Type	:			
1.3.7.3	Knife back:	1	l .	I I	
	Type Marking:	:			
	Manufacturer's name or recognized	:			
	trade mark	•			
	Batch or code number	:			
1.3.8	Cutting platform auger:	•			
1.3.0	Type of crop conveyor	:			
	Size of auger (Dia., Pitch & Width), mm	:			
	Speed of auger corresponding to	:			
	recommended no load speed of engine				
	for field work, rpm				
	Arrangement for adjusting the clearance of crop auger	:			
	Auger drive safety arrangement	:			
	Height of header assembly in the	:			
	transport position, cm				
	Arrangement for locking the header	:			
	assembly in raised position				
	Arrangement for side way tilting the	:			
	cutter bar				

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI, Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name :		
Designation:	Sheet Noof	Designation:		
Date :		Date:		

1	2	3		4		5	6
1.3.9	Details of retractable fingers:						
	Number(s)	:					
	Range of throw out, mm	:					
	Axial spacing between the fingers, mm	:					
	Peripheral distance between the fingers,	:					
	mm						
	Arrangement for adjustment of fingers length	:					
1.3.10	Undershot conveyor:	<u> </u>					
1.5.10	Type of feeder conveyor	:					
	No. size and spacing of comb bar	:					
	Conveyor drive safety arrangement	:					
	Arrangement for adjusting clearance	:					
	between comb and platform and	·					
	tensioning the chain						
	9						
	Speed corresponding to recommended no load engine speed of engine for	:					
	field work, rpm						
	No. & type of bearings	:					
1.3.11	Threshing drum:	•	For	For	For	For	
1.3.11			Wheat	Paddy	Wheat	Paddy	
	Туре	:					
	Outer diameter and width, mm	:					
	Range of speed corresponding to	:					
	recommended no load speed of engine						
	for field work, rpm						
	No. of bars	:					
	No. of pegs and their spacing on each	:					
	bar						
	No. of hub plate	:					
	Length of rasp bar/peg bar, mm Height of pegs, mm	:					
	No. of rasps/100 mm	•					
	No. of rasps on each bar	•					
	Arrangement of bars	•					
	No. & type of bearings	:					
	Method of speed variation	:					
	Provision of stone trap	:					
	Safety device	:					
1.3.12	Concave:		For	For	For	For	
			Wheat	Paddy	Wheat	Paddy	
	Overall width of concave, mm	:		v		J	
	Effective width, mm	••					
	Type of concave	:					
	No. of bars	:					
	No. of pegs per bar & spacing	:					
	Height/ Spacing of the pegs, mm	:					
	Peripheral length, mm	:					
	Peripheral effective length, mm	:					
	Effective area, sq. cm.	:					
	Details of extension	:					
Jama of the Mann	facturer/ Applicant Document No. if any Revi	sion	etatue	Nama of the	Test Agency: NR	EMTTI Uicor	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	4	5	6			
	Range of clearance (mm):							
	Front	:						
	Rear	:						
	Method of adjusting the clearance	:						
	between drum and concave							
1.3.13	Rear beater:	1 1						
	Type	:						
	Size of beater, length and width, mm	:						
	Speed corresponding to recommended	:						
	no load speed of engine for field work, rpm							
1.3.14	Baffle plate (Deflector):							
1,011	Туре	:						
	No. of flap	:						
	Size of baffle plate, mm	:						
	Method of flap adjustment	:						
1.3.15	Separating mechanism:							
1.3.15.1	Straw walkers:							
	Number (s)	:						
	Type	:						
	Size of each straw walker (mm):	<u> </u>						
	Length	:						
	Width	:						
	Area of each walker, sq. m	:						
	Lift/throw, mm	:						
		•						
	Oscillations per minutes	•						
	correspondingto recommended no							
	load speed							
	of							
	engine for field work, rpm							
	Provision for varying oscillations of	:						
	straw walkar							
	Type of extension	:						
	No. & type of bearings	:						
1.3.15.2	Stepped grain pan:							
	Type	:						
	Size, mm	:						
	Effective area of pan, m ²	:						
	Details of extension	:						
	Location	:						
	Inclination (degree)	:						

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	3 4		5		6
1.3.15.3	Cleaning sieves:						
1.3.15.3.1	Top sieve:						
	No. of sieve	:					
	Туре	:					
	Overall size of sieve, mm:		Front	Rear	Front	Rear	
	Length	:					
	Width	:					
	Effective cleaning area, mm ²	:					
	Area of extension, mm ²	:					
	Oscillation per minute corresponding to	:					
	recommended no load speed of engine						
	for field work						
	Lift/throw, mm	:					
	Arrangement for varying the opening of	:					
	the sieve						
	Height of lips at max. opening, mm	:					
	Method of varying oscillation	:					
1.3.15.3.2	Method of drive Bottom sieve:	:					
1.3.15.3.2	No. of sieve						
	Type	:					
	Overall size of sieve, mm:	•					
	Length	:					
	Width	:					
	Effective cleaning area, mm ²	:					
	Oscillation per minute corresponding to	:					
	recommended no load speed of engine for field work						
	Method of varying oscillation	:					
	Arrangement for varying the opening of	:					
1 2 15 4	the sieve						
1.3.15.4	Blower: Dia. mm	:					
	Effective width, mm	•					
	No. & type of blade	:					
	Size of blade, mm:	,					
	Length	:					
	Width	:					
	Thickness	:					
	Type of drive	:					
	Method of varying the blower speed	••					
	Range of speed corresponding to	:					
	recommended no load speed of engine						
	for field work, rpm Method of controlling the air blast	:			-		
	No. & type of bearings	:					
	1.0. & type of ocarings	•			1		1

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	4	5	6
1.3.15.5	Grain pan:				
	Туре	:			
	Size, mm	:			
	Area, sq. m	:			
	Location	:			
	Inclination (degree) and method of	:			
12176	adjustment (if any)				
1.3.15.6	Tailing pan:				
	Type Number	:			
	Size, mm	:			
	Location	:			
	Inclination, (degree) and method of	:			
	adjustment (if any)	•			
	3 (3)				
1.3.16	Grain conveying mechanism:				
1.3.16.1	Bottom grain conveyor:				
	Туре	:			
	Size of conveyor (length, dia. and				
	pitch), mm				
	Speed corresponding to recommended	:			
	no load speed of engine for field				
	work,				
	rpm				
	Type of drive	:			
	No. & type of bearings	:			
1.3.16.2	Grain elevator:				_
	Type	:			
	Length of elevator, mm	:			
	Outside section, mm	:			
	No. & type of pad	:			
	Size of pads, mm	:			
	Spacing of pads, mm	:			
	Speed corresponding to recommended	:			
	no load speed of engine for field work,				
	rpm				
	Type of chain	:			
	Size of chain (Length, Roller Dia. &	:			
	Pitch), mm	•			
	No. of roller	+-			
		:			
	Elevator drive safety arrangement	:			
	Method of tensioning the chain	:			
	Type of drive	:			
	No. & type of bearings	:			
		•		-	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name :
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3	4	5	6
1.3.16.3	Upper grain auger:				
	Туре	:			
	Size of auger (Length, Dia. and Pitch),	:			
	mm				
	Speed corresponding to recommended	:			
	no load speed of engine for field work,				
	rpm				
	Drive safety arrangement	:			
	Type of drive	:			
	No. & type of bearings	:			
1.3.17	Tailing conveying mechanism:				
1.3.17.1	Bottom tailing auger:				
	Туре	:			
	Size of auger (length, dia. and pitch),	:			
	mm				
	Speed corresponding to recommended	:			
	no load speed of engine for field work,				
	rpm				
	Type of drive	:			
	No. & type of bearings	:			
1 2 17 2	Drive safety	:			
1.3.17.2	Tailing elevator: Type				
	Length of elevator box, mm	:			
	Outer section, mm	:			
	No. & type of pads	:			
	Size of pads, mm	:			
	Spacing of pads, mm	:			
	Type of chain	:			
	Size of chain (Length, Roller dia. &	:			
	Pitch), mm				
	No. of rollers	:			
	Method of tensioning the chain	:			
	Elevator drive safety arrangement	:			
	Type of drive	:			
	Speed corresponding to recommended				
	no load speed of engine for field work,				
1.3.17.3	rpm Upper tailing auger:				
1.3.17.3	Type	:			
	Size (length, dia. and pitch), mm	:			
	Speed corresponding to recommended	:			
	no load speed of engine for field work,				
	rpm				
	Type of drive	:			
	No. & type of bearings	:			
	Drive safety	:			
					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet Noof	Designation:
Date :		Date:

1	2	3		4	5	6
1.3.18	Grain tank:		T			
	Location	:				
	Capacity:					
	Volume basis, m ³	:				
	Method of agitating the grains in tank	:				
	Size of grain tank opening, mm	:				
	Provision of grain tank cover	:				
	Provision for indication of grain tank	:				
	filling					
1.3.18.1	Grain conveying auger (Bottom of grain	tai	1k):			
	Type	:				
	Size (Length, Dia. & Pitch), mm	:				
	Speed corresponding to recommended	:				
	field operation rpm of engine for field work, rpm					
	Type of drive	:				
	No. & type of bearings	:				
	Safety device	:				
1 2 10 2	•	•				
1.3.18.2	Grain unloading auger:	1	1			
	Туре	:				
	Size (length, dia. and pitch), mm	:				
	Horizontal reach, cm	:				
	Discharge height above ground level,	:				
	Clearance height, cm	+-				
		:				
	Speed corresponding to recommended no load speed of engine for field work,	:				
	rpm					
	Type of drive	:				
	No. & type of bearings	:				
	Safety device	:				
	Safety device	+				
1.4	C-f-4-1					
1.4	Safety devices provided on the machine Previous sample:					
i)	rrevious sample:					
ii)						
iii)						
iv)						
v)						
vi)						
vii)						
1.4.2 Present sample:						
i)						
ii)	,					
iii)						
iv)						
v)						
vi) vii)						
			1			
	ufacturer/ Applicant Document No, if any Revisi	on st	atus		Agency: NRFMTTI,Hisar	
Signature : Name :	Make : Model :			Signature : Name :		
Designation:	Sheet Noof	_		Designation:		
Date :				Date:		

1.5	Details of operating controls, gauges and instruments						
1.5.1	Previous sample:						
i) ii)							
ii)							
iii)							
iv)							
v)							
vi)							
vii)							
1.5.2	Present sample:						
i)							
ii)							
iii)							
iv)							
v)							
vi)							
vii)							
1	2	3	4		5		6
1.6	Seat:						
	Make	:					
	Type	:					
	Type of suspension	:					
	Type of dampening	:					
	Horizontal adjustment, mm	:					
	Adjustment of back rest, mm	:					
1.7	Canopy:						
	Type	:					
	Canopy size, mm	:					
1.0	Height from operator's platform, mm	:	W/l-:		W/Li		
1.8	Overall dimensions of combine		Working Position	<u>Tran</u>	Working Position	Trans	
	harvester, cm			<u>s port</u> positi		<u>port</u> position	
				on		position	
	Length	:					
	Width	:					
	Height	:					
1.9	Mass:	_					
**	Mass of combine harvester with						
	coolant, fuel, lubricants & grain tank						
	(wheat) full and 75 kg mass on the						
	operator's seat, kg						
	Total	:					
	Front	:					
	Rear	:					
1.10	Ground clearance, mm	:					
1.11	Total number of lubricating points:						
	Grease Nipples/grease holes	:					
	Greasing cups	:					
	Oiling	:					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

1	2	3	4		5	6
1.12	Colour of combine:					
	Reel and chassis	:				
	Header unit and lower sheet metal	:				
	Upper sheet metal	:				
	Wheel rim	:				
1.13	Header transport trailer					
	Type	:				
Size(L×W×H), mm						
	No. & type of wheel	:				
	Make	:				
	Size & Ply rating	:				
	Track width (mm)	:				
	Height of trailer hitch in transport	:				
	position, mm					
1.14	Details of labeling plate:					
1.14.1	Previous sample:					
1.1.1.0						
1.14.2	Present sample:					
1.15	Datails of labeling plate of prime marrow					
1.15	Details of labeling plate of prime mover: Previous sample:					
1.13.1	1 revious sample:					
1.15.2	Previous sample:					
1.17	Lubuicanto					
1.16	Lubricants:					
1.16.1	Previous sample:					
Sr. No.	Particulars	As r	ecommended b	y the	Oil change	period (h)
			applicant			
1	Engine oil					
2	Hydraulic oil and Power steering					
=	oil					
3	Transmission and final drive					
=	housing oil					
4	Grease					

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

1.16.2	Present sample:			
Sr. No.	Particulars	As re	nended by the Dicant	Oil change period (h)
1	Engine oil			
2	Hydraulic oil and Power steering oil			
3	Transmission and final drive housing oil			
4	Grease			

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

2. TECHNICAL SPECIFICATIONS FOR STRAW CHOPPER CUM SPREADER (SMS) (IF FITTED)

2.1	General:		
	Make of SMS	:	
	Model of SMS	:	
	Type of SMS	:	
	Name and complete Address of the	:	
	manufacturer of SMS including		
	PIN/Mob./email etc.		
2.2	Rotor:		
	Rotor Diameter, mm	:	
	No. of lugs on rotor in a row	:	
	No. of rows in a periphery	:	
	Width of flail, mm	:	
	Thickness of flail, mm	:	
	No. of flail in one set	:	
	Spacing between flail of one set, mm	:	
	Distance between adjacent flail unit,	:	
	mm		
	Rotor dia with blade, mm	:	
	No. of Rows/bar of serrated blade	:	
	No. of serrated blade in a row	:	
	Spacing between serrated blades, mm	:	
	Clearance between pivotal blade and	:	
	concave		
	Overlapping of pivotal blade on serrated blade, mm	:	
	Rotor rpm	:	
2.3	Transmission:	:	
	Diameter of Drive Pulley	:	
	Diameter of Driven pulley	:	
2.4	Spreader:		
	Total no of flap, mm	:	
	Length of flap, cm	:	
	Distance between flaps (left to right)	:	
	Spreader angle with horizontal, Degree	:	
	Spreader angle with line of travel,	:	
	degree		
	Spreader sheet thickness, mm	:	
	SMS sheet thickness, mm	:	
2.5	Overall dimensions (mm):		
	Length	:	
	Width	:	
	Height	:	
2.6	Overall Mass (kg)	:	
2.7	SAFETY REQUIREMENT FOR SMS:		
	Guards over all moving parts	:	
	RPM indicator of rotor	:	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

	Overlapping of flail and fixed serrated blade (The clearance should be adjustable)	:	
2.8	Details of labelling plate:		
2.0	Details of labelling place.		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

SELECTED PERFORMANCE AND OTHER HARACTERISTICS AS PER IS 15806-2018 (TO BE DECLARED BY THE APPLICANT)

S. No		Characteristics	Category (Evaluative/ Non evaluative)	Requirement	Tolerance	Declarati- on by applicant (Previous sample/ Present sample)	Remarks
1		2	3	4	5	6	7
1.	Prin	ne mover performance:					
	a)	Max. Power (absolute)- Average max. power observed during 2 hrs. max. power test in natural ambient condition, kW	Evaluative	To be declared by manufacturer	Declared value to be achieved with a tolerance of $\pm 5\%$		
	b)	Max. power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW	Evaluative	To be declared by manufacturer	-do-		
	c)	Power at rated engine speed, kW (under natural ambient condition)	Non- Evaluative	To be declared by manufacturer	-do-		
	d)	Specific fuel consumption corresponding to average maximum power under 2h maximum power test, g/kWh.	Evaluative	-do-	+5% (Max.)		
	e)	Max. smoke density (Bosch no.) at 80 percent load between the speed at max. power and 55 percent of speed at max. power or 1000 rpm whichever is higher	Evaluative	As per CMV rules.	Nil	-	
	f)	Max. crank shaft torque, (Nm) observed during the test after no load engine speed is adjusted as per manufacturer's recommendation for field work	Evaluative	To be declared by manufacturer	±8%		
	g)	Back up torque, %	Evaluative	7 percent, (Min.)	Nil	-	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

		2	3	4	5	6	7
	h)	Max. operating temperature					
	i)	Engine oil	Evaluative	To be declared by manufacturer	Nil		The observed value under the high ambient condition should not exceed maximum safe value specified by the oil company which will be provided by the applicant
	ii)	Coolant	Evaluative	To be declared by manufacturer	Nil		The declared value should not exceed the boiling temperature of coolant under the pressurized or otherwise and the observed value under high ambient condition should not exceed the declaration.
	i)	Lubrication oil consumption, g/kWh	Evaluative	Not exceeding 1 % of specific fuel consumption at maximum power under high ambient condition	Nil		The value would be based on the test conducted under high mbient condition
3ra	ake p	erformance at 24km/h or Ma	ximum Speed	whichever is less			
	a) -	Max. Stopping distance at a force equal to or less than 600 N on brake pedal (m) – (cold brake and hot brake)	Evaluative	As per CMV rules.	Nil		
	b)	Max. Force exerted on brake pedal to achieve a deceleration of 2.5 m/sec ²	Evaluative	≤ 600 N	Nil		
	c)	Effectiveness of parking brake at a force of 600 N at foot pedal or 400 N at Hand lever	Evaluative	As pre CMV rules.	Nil		Based on the test conducted, Yes/No as the case may be should beindicated

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar			
Signature :	Make:	Signature :			
Name :	Model:	Name:			
Designation:	Sheet No of	Designation:			
Date :		Date:			

1		2	3	4	5	6	7
3. M		ical vibration:					
	i)	Operator's platform	Non	120 μm max.	Nil		
			evaluative				
	ii)	Steering wheel	Non	150 μm max.	Nil		
			evaluative				
	iii)	Seat with driver seated	Non	120 μm max.	Nil		
			evaluative				
4. Ai	r clea	ner oil pull over:					
	i)	Max. oil pull over in percentage when tested in accordance with IS: 8122. (Part-2)-2000	Evaluative	0.20% max.	Nil		
5. No	oise m	easurement:			l l		<u> </u>
	i)	Max. ambient noise emitted by combine at by-stander's position, dB (A)	Evaluative	as per CMVR	Nil		As per road transport condition
	ii)	Max. noise at operator's ear Level, dB (A)	Evaluative	as per CMVR	Nil		In actual field condition
6. H	eader	Lifting Test:					
		Satisfactory completion of header lifting test	Evaluative	Satisfactory completion	Nil		The observed Hydraulic oil temp should not exceed maximum safe value specified by the oil company which will be provided by the applicant.
7. D i		limit:	Б 1 4	G1 11 .	NT'1		
	a)	Thickness of brake lining, mm	Evaluative	Should not exceed the values declared by the manufacturer	Nil		
	b)	Thickness of clutch plate, mm	Evaluative	-do-	Nil		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation :	Sheet No of	Designation:		
Date :		Date:		

1		2	3	4		5	6	7
8. Fi	ield p	erformance:						
	a)	Suitability for crops	Evaluative	(Wheel	type) Paddy (Track			
	b)	Processing losses (%)	Evaluative	Wheat Barley Rice Sorghum Maize Oil seed rape Soya- beans	: Max 3% : Max 4% : Max 3% : Max 4% : Max 4% : Max 5%	ó ó ó ó		
	c)	Threshing efficiency	Evaluative	-	: ≥ 98 % for wheat and paddy	Nil		
	d)	Cleaning efficiency	Evaluative	-	: ≥96 % for wheat and paddy	Nil		
	e)	Grain breakage in main grain tank	Evaluative	-	: ≤ 2.5 %	Nil		
	f)	Non collectable losses	Evaluative	-	: \leq 2.5 % for wheat, paddy and gram \leq 4.0 % for soyabe an	Nil		
9. Fi	ield p	erformance for Straw Mana	gement System (If fitted):	•			
	a)	Uniformity of straw spread, CV (Percent)	Evaluative	-	: 20, Max.	-		
	b)	Weighted mean size of chopped straw, cm	Evaluative	-	: 20, Max.	-		

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation:
Date :		Date:

		2	3	4	5	6	7
). S	afety	requirements:					
	a)	Guards against all moving parts/drives and hot part	Evaluative	Belt and chain drives, pulleys, hydraulic pipes (around ope rators workplace)			As per IS 12239 (Part 1)
	b)	Lighting arrangement	Evaluative	essential as per CMVR	-		
•	c)	Grain tank cover	Evaluative	Ess enti al	-		
•	d)	Spark arrester in engine's exhaust in case naturally aspirated engine	Evaluative	Ess enti al	-		
	e)	Stone trap before concave	Evaluative	Essential	-		
	f)	Rear view mirror	Evaluative	Essential	ı		
	g)	Fire extinguisher	Evaluative	Essential	ı		
	h)	Slip clutch at following drives – i) Cutting platform auger ii) Undershot conveyor drive iii) Grain & tailing elevator	Evaluative Non evaluative Non evaluative	Essential Optional Optional	-		
	i)	Anti slip surfaces at operator platform & ladder & proper gripping for the control levers.	Evaluative	Essential			As per 12239 (Part
	j)	Working clearance around the controls	Evaluative	Essential 70mm, min	-		As per 12239 (Part
	k)	Labelling of control and gauges and operating controls	Evaluative	Essential	-		As per 6283 (Part 1

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar		
Signature :	Make:	Signature:		
Name :	Model:	Name:		
Designation :	Sheet No of	Designation:		
Date :		Date:		

1		2	3	4	5	6	7	
11.		Material of blades for guards, knife blades and knife back	Non evaluative	Conforming to IS 6024,IS 6025 and IS 10378 respectively	ı	-	-	
12.		Material of blades for Straw ManagementSystem (SMS)	Non- Evaluative	The flail and fixed blades shall be manufactured from steel having the following chemical composition or such other composition as shall be agreed between the supplier and the purchaser: Carbon: 0.70 to 0.1 % Mnganese: 0.6 to 0.97 % Chrome: 0.1 % Nickle: 0.1 %	-			
13.		Bushes for flail blades	Non- Evaluative	Mild steel	-			
14.		Hardness of flail blades for StrawManagement System (SMS)	Non- Evaluative	Bush section: 20 to 35 HRC Edge section(Hardened zone): 48to 48 HRC Remainder zone: 20 to 35 HRC	1			
15.		Hardness of serratedblades for Straw Management System (SMS)	Non- Evaluative	Bush section: 20 to 35 HRC Edge section(Hardened zone): 48 to 58 HRC Remainder zone: 20 to 35 HRC	-			
16.		Safety Requirements for Straw Management System(if Fitted)						
	a)	Guards against all moving parts/drivesand hot parts	Evaluative	Essential				
	b)	RPM indicator for rotor	Evaluative	Desirable				
	c)	Overlapping of flail and fixed serratedblades	Evaluative	Essential			The clearance of the flail and fixed serrated blades should be adjustable	
Place: Signature				-				

Place:	Signature
Date:	Name of the applicant
	Designation
	Address

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date: