



## भारत सरकार /GOVERNMENT OF INDIA

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute ट्रैक्टर नगर, सिरसा रोड, हिसार )हरियाणा—(125001 TRACTOR NAGAR, SIRSA ROAD, HISAR (HARYANA)- 125 001 Website: http://nrfmtti.gov.in E-mail: fmti-nr@nic.in GSTIN:06AAAGN0273PIZ3 Tele./FAX: 01662-276984

## TECHNICAL SPECIFICATIONS FOR HTP ENGINE OPERATED SPRAYER/

	ENGINE OPERATED I	MI	SACK SI KATEK
1	General:		
	Name of the machine	:	
	Type of machine		
	Make	:	
	Model	:	
	Serial No.	:	
	Name of Manufacturer	:	
	Name of Applicant/Importer	:	
	Year of manufacture	:	
	Output capacity (l/min)	:	
	Country of origin	:	
2	Prime Mover:		
	Name & address of manufacturer	:	
	Name & address of importer (if any)	:	
	Type	:	
	Make	:	
	Model	:	
	Engine Sr. No.	:	
	Country of origin	:	
	Year of manufacture	:	
	Recommended engine speed Setting, (rpm):		
	-Low idle speed	:	
	-High idle speed	:	
	Max. power, (kW)	:	
	Speed at maximum power, (rpm)	:	
	Rated power, (kW)	:	
	Rated engine speed, (rpm)	:	
	Max. torque, (Nm)	:	
	Speed at maximum torque, (rpm)	:	
	Whether the prime mover has already been tested by authorized testing centre (Yes/No)	:	

Name of the Manufacturer/ Applicant Document No, if any Revision status		Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

	If yes, then specify the valid test report No.	:	
	and upload the copy of test report		
2.1	Cylinder & Cylinder Head:	•	
	Number	:	
	Disposition	:	
	Bore / Stroke, (mm)	:	
	Capacity, (cc)	:	
	Type of valve	:	
	Value clearance, (mm)		
	Inlet	:	
	Exhaust	:	
	Compression ratio	:	
2.2	Fuel Supply System:		
	Type of fuel feed	:	
2.3	Fuel Tank:		
	Material (1)	:	
	Capacity of fuel tank, (1)	:	
	Location of fuel tank Provision for draining of sediments/ water	:	
	Fuel filter	:	
	Fuel on/off	:	
2.4	Governor:	•	
	Make	:	
	Model	:	
	Type	:	
2.5	Carburetor:	•	
2.5	Make	:	
	Туре	:	
2.6	Fuel injection pump (if applicable):	:	
_,_	Make	:	
	Model	:	
	Serial number/ group combination number	:	
2.7	Injector (if applicable):		
	Make	:	
	Model	:	
	Type Serial number	_	
	Number of holes	:	
2.7	Air Intake System:		
2.7	Pre cleaner	:	
2.8	Air Cleaner:	•	
2.0			
	Type Make & Model	:	
		:	
	Location	:	
	Recommended service schedule	:	
	Recommended grade of oil	:	
2.9	Exhaust:	1	T
	Type of silencer	:	
	Location of silencer	:	
	Spark arresting device, if any	:	
			Name of the Test Agency: NDEMTTI Histor
	1		L Name of the Lest Agency: NPHMTTT High

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation :	Sheet No of	Designation :
Date :		Date :

2.10	<b>Lubricant System:</b>			 	
	Type		:		
	Oil capacity, (l)		:		
	Recommended grade of lubr	ricant oil	:		
	Oil change period, (h)		:		
2.11	Cooling System:				
	Type		:		
	Dia. of blower, mm		:		
	No. of vanes		:		
2.12	Starting System:		-		
	Type		:		
	Ignition system		:		
	Any other provision for easy	v starting	:		
	Aid for cold starting	, surreing	:		
2.13	Spark plug:		•		
2.13	Make		:		
	Model		:		
	Spark plug electrode gap, (m	nm)	:		
3	Chemical Tank (if applicat		:		
3	Material	DIE).	:		
	Capacity, (1)		:		
	Strainer at filing hole				
	Provision of drain plug in tar	nk	:		
	Provision of hose reel	IIK	:		
3.1	Frame (for stationery spra	aron).	:		
3.1	Type	iyer).	:		
			•		
	Size of angle iron, mm		:		
3.2	Size of angle iron, mm Dia. of pipe, (mm)		:		
3.2	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:		:		
3.2	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type		:		
3.2	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working	on	:		
	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation	on	:		
3.2	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:	on	:		
3.4	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make		:		
	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device: Type Method of working Method of pressure regulation  Spray Gun: Make  Discharge rate at 600 kPa		: : : : : : : : : : : : : : : : : : : :		
3.4	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa particular of the spray pattern		: : : : : : : : : : : : : : : : : : : :		
3.4	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parageters of the spray pattern  -Fine cone spray pattern		: : : : : : : : : : : : : : : : : : : :		
3.4	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa part of the spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)	pressure, (l/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parage spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and make	pressure, (l/min):	:		
3.4	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa part of the spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many Nozzle:	pressure, (l/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parage spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many Nozzle:  Type	pressure, (I/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa part of the spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many spray pattern  Nozzle:  Type  Discharge rate at 300 kPa part of the spray pattern	pressure, (I/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parage spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many spray spray spray spray pattern  Nozzle:  Type  Discharge rate at 300 kPa parage spray pattern	pressure, (I/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa part of the spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many Nozzle:  Type  Discharge rate at 300 kPa part of the spray pattern  Fine cone spray pattern  Fine cone spray pattern	pressure, (I/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parage spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many spray pattern  Nozzle:  Type  Discharge rate at 300 kPa parage spray pattern  Fine cone spray pattern  Fine cone spray pattern  Fine cone spray pattern  Fine cone spray pattern  Spray angle of nozzle, (°)	pressure, (l/min): marking pressure, (l/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa part of the spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many spray pattern  Nozzle:  Type  Discharge rate at 300 kPa part of the spray pattern  Fine cone spray pattern  Fine cone spray pattern  Spray angle of nozzle, (°)  Spray nozzle designation and many pattern	pressure, (l/min): marking pressure, (l/min):	: : : : : : : : : : : : : : : : : : : :		
3.4.1	Size of angle iron, mm Dia. of pipe, (mm)  Agitating Device:  Type  Method of working  Method of pressure regulation  Spray Gun:  Make  Discharge rate at 600 kPa parage spray pattern  -Fine cone spray pattern  Spray angle of gun, (°)  Spray gun designation and many spray pattern  Nozzle:  Type  Discharge rate at 300 kPa parage spray pattern  Fine cone spray pattern  Fine cone spray pattern  Fine cone spray pattern  Fine cone spray pattern  Spray angle of nozzle, (°)	pressure, (l/min): marking pressure, (l/min):	: : : : : : : : : : : : : : : : : : : :	Name of the Test Agency: NRFMTTI,H	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	rume of the Test rigolog. Tate 1711 Figure
Signature :	Make:	Signature :
Name :	Model:	Name:
Designation :	Sheet No of	Designation :
Date :		Date:

3.6	Pump:		
	Type	:	
	Make & model	:	
	Year of manufacture	:	
	Serial No.	:	
	Recommended Pump Speed for spraying,	:	
	(rpm)		
	Suction volume, (l/min)		
	Volumetric efficiency, (%)		
	Working pressure, (kg/cm <sup>2</sup> )	:	
	Pump discharge at working pressure, (l/min)	:	
	Rated pressure, (kg/cm <sup>2</sup> )	:	
	Pump discharge at rated pressure, (l/min)	:	
	Rated speed, (rpm)	:	
	Maximum achievable pressure, (kg/cm <sup>2</sup> )	:	
	Plunger dia./stroke, (mm)	:	
	Method of drive	:	
	Speed reduction from engine to pump	:	
	Pressure regulator		
	Method of mounting	:	
	Size of frame, (mm):		
	-Length	:	
	-Width	:	
	-Height	:	
	Country of origin	:	
3.7	Safety wear (for operator's safety during	:	
2.0	operation)		
3.8	Overall Dimensions, (mm):	1	Г
	Length (without hose)	:	
	Width	:	
	Height	:	
	Length of hose (m), (if applicable)	:	
4	Total mass, (kg)	:	
4.1	Mass with all accessories and without fuel,	:	
4.2	(kg) Mass with accessories and fuel tank full,	:	
4.2	(kg)	•	
5	Details of labeling plate	:	
		•	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI,Hisar
Signature :	Make :	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date:

## MATERIAL OF CONSTRUCTION OF COMPONENTS OF SPRAYER

[As per Table No.-1of IS: 11313-2007]

Sr. No.	Components	Materials	Material of the
1	2.	(As per IS:11313-2007)	component
1. i)	Pump cylinder	Brass, stainless steel	4.
ii)	Pressure chamber	Brass, stainless steel	
iii)	Piston rod	Stainless steel,	
iv)	Piston or plunger	Gunmetal, stainless steel, plastics, Rubber, vegetable tanned leather, chrome tanned leather	
v)	Spreader	Brass, stainless steel, plastics	
vi)	Valve assembly	Brass, Stainless Steel, Plastics	
vii)	Roller pump shaft	Stainless steel	
viii)	Pump rollers	Nylon filled with lead	
ix)	Pressure regulators	Brass, stainless steel	
x)	Suction strainer	Brass, stainless steel, Plastics	
xi)	Strainer body	Brass, plastics	
xii)	Gasket	Rubber, PVC, fibre, Leather	
xiii)	Spray nozzles	Brass, stainless steel	
xiv)	Spray boom	Mild steel, Galvanized, iron Braided rubber	
xv)	Hose	Synthetic rubber, P.V.C	
xvi)	Tank	Galvanized iron, Brass, Fiber glass reinforced plastics, plastics	
xvii)	Pipe for agitator	Galvanized iron, Brass, PVC	
xviii)	Piston (bucket) screw	Brass, stainless steel	
xix)	Crank case	Aluminum alloy	
xx)	Roller pump body	Nickel resistant cast iron	
xxi)	Roller pump and plate	Nickel resistant cast iron	
xxii)	Roller pump rotor	Nickel resistant cast iron	
xxiii)	Piston pump crank shaft	Carbon steel	
xxiv)	Pump inlet port end fitting	Brass	
xxv)	Piston rod guide	Brass, Aluminum alloy, Gunmetal, Nylon	
xxvi)	Connecting rod	Carbon steel	
xxvii)	Gudgeon pin	Carbon steel	
xxviii)	Big end bearing	Steel coated with tin base white metal	
xxix)	Small end bush	Gunmetal	

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation:	Sheet No of	Designation :
Date :		Date:

A	Engine parameter:	Declaration
i	Recommended engine speed Setting, (rpm)	
	-Low idle speed	
	-High idle speed	
	-Rated speed	
ii	Max. power, (kW)	
iii	Speed at maximum power, (rpm)	
iv	Rated power, (kW)	
v	Specific fuel consumption corresponding to maximum power, g/kWh	
vi	Maximum equivalent crankshaft torque,(Nm)	
/ii	Speed at maximum torque, (rpm):	
iii	Maximum temperatures(°C):	
	-Engine oil	
	-Coolant (water)/liner wall	
ix	Lubricating oil consumption (g/kwh)	
X	Coolant consumption (% of total Coolant capacity) (if applicable)	
xi	Smoke level (Bosch No.)	
В	Discard limit of Engine Critical Components:	Discard limit
<u>-</u> İ	Cylinder bore dia. (mm)	2 10 0002 07 1111110
i	Clearance between cylinder liner and piston (mm)	
ii	Piston dia. (mm)	
ii	Ring-end gap (mm):	
	-Top compression ring	
	-2 <sup>nd</sup> compression ring	
	-3 <sup>rd</sup> compression ring	
	- Oil ring	
v	Ring groove clearance (mm):	
	-Top compression ring	
	-2 <sup>nd</sup> compression ring	
	-3 <sup>rd</sup> compression ring	
	- Oil ring	
<i>V</i>	Clearance of main bearings (mm):	
	- Diametrical	
	Clearance of big end bearings (mm):	
	- Diametrical	
	- Axial	
⁄i	Crankshaft end float (mm)	
ii	Spring stiffness (kgf/mm)	
iii	Valve guide clearance (mm)	
	-Intake	
	-Exhaust	

Date:	
Place:	Signature:
	Name of signatory:
	Designation:

Name & address of firm:

Name of the Manufacturer/ Applicant	Document No, if any Revision status	Name of the Test Agency: NRFMTTI, Hisar
Signature :	Make:	Signature:
Name :	Model:	Name:
Designation :	Sheet No of	Designation:
Date :		Date: