

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या / No. : COMB-55/1258
माह/ Month : July, 2010



'NORTH INDIA- 749'
SELF PROPELLED COMBINE HARVESTER



भारत सरकार
कृषि मंत्रालय
(कृषि एवं सहकारिता विभाग)

**GOVERNMENT OF INDIA
MINISTRY OF AGRICULTURE
(DEPARTMENT OF AGRICULTURE & COOPERATION)**

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान
ट्रैक्टर नगर, सिरसा रोड, हिसार -125001 (हरियाणा)

**NORTHERN REGION FARM MACHINERY TRAINING AND TESTING INSTITUTE
TRACTOR NAGAR, SIRSA ROAD, HISAR-125001 (HARYANA)**

Telephone : 01662- 276824, 276172
Website : <http://dacnet.nic.in/nrfmtti>

Telefax No. : 01662-276984
E-Mail : fmti-nr@nic.in

18 SUMMARY OF OBSERVATIONS, COMMENTS AND RECOMMENDATIONS

18.1 Engine Performance Test:

Engine Brake power, kW (Ps)	Crankshaft torque, Nm(kgf-m)	Engine speed (rpm)	Hourly consumption kg/h / (l/h)	Fuel consumption	Specific fuel consumption kg/kwh (kg/hph)	Specific energy, kWh/l (hph/l)
i) Maximum power - 2 hours test:						
77.2 (105)	338.4 (34.5)	2280	26.50	20.96	0.286 (0.210)	2.91 (3.96)
61.1 (83.2)	387.7 (39.5)	1576	19.45	16.12	0.264 (0.194)	3.14 (4.27)**
ii) Power at rated engine speed (2200 rpm)						
75.1 (102.1)	341.5 (34.8)	2200	25.42	21.07	0.280 (0.206)	2.95 (4.01)
73.3 (99.7)	333.0 (34.0)	2200	25.36	20.81	0.284 (0.209)	2.89 (3.93)*
iii) Maximum torque:						
48.5 (66.0)	404.0 (41.2)	1200	15.7	13.07	0.269 (0.197)	3.07 (4.17)
46.4 (63.1)	404.0 (41.2)	1150	14.96	12.40	0.269 (0.198)	3.10 (4.21)**
46.3 (63.0)	385.8 (39.3)	1201	15.75	13.04	0.2814 (0.207)	2.94 (4.00)*
iv) Five hour rating test:						
a) Engine loaded to 90% of maximum power:						
69.02 (93.8)	297.6 (30.3)	2319	23.31	19.26	0.279 (0.205)	2.96 (4.03)
b) maximum power:						
74.4 (101.2)	330.6 (33.7)	2251	25.91	21.41	0.288 (0.212)	2.87 (3.90)

* Under high ambient condition.

** At no load speed corresponding to rated speed specified for field work.

Remarks:

- i) The maximum power output of the engine was observed as 77.2 kW (105 Ps) & 61.1 kW (83.1 Ps) at 2280 rpm and 1576 rpm of engine at full throttle and setting recommend for field operation respectively.
- ii) The specific fuel consumption corresponding to maximum power at full throttle and setting recommended for field operation was measured as 0.286 & 0.264 Kg/kwh (0.210 & 0.194 kg/hph).
- iii) The back-up torque of the engine was measured as 4.10 % under natural ambient field condition at recommended engine speed for field operation.

- iv) The maximum smoke density was recorded as 2.52 (Bosch No.) which is within specified limit.
- v) The maximum temperature of engine oil, coolant(water) and exhaust gas was observed as 126, 99 and 648 °C respectively.
- vi) The lubricating oil & coolant consumption during five hours rating test were measured as 0.285 (0.209) g/kWh (g/hph) and 15.3% of total coolant capacity respectively.

18.2 Turning ability:

The radius of turning circle of LHS and RHS was observed satisfactory.

18.3 Visibility:

The visibility around the cutter bar from operator's seat in normal sitting position is satisfactory.

18.4 Braking Performance:

- i) The mean deceleration and stopping distance corresponding to 187 N pedal force was measured as 2.52 m/sec² and 11.0 m respectively and the performance is in line with the IS 12207-1987.
- ii) The performance of parking brake was found satisfactory.

18.5 Mechanical Vibration:

The amplitude of mechanical vibration of components marked as (*) in chapter 13 of this report are on higher side. This calls for providing suitable remedial measures to dampen the vibration in order to improve the operational comfort and service life of various components & sub assemblies.

18.6 Noise measurement:

- i) The ambient noise emitted by the machine was measured as 87.8 dB(A) which is considered on normal side when compared to warning levels of 88 dB(A).
- ii) The noise at driver's ear level was measured as 96.1 dB(A) which may be considered on normal side when compared with warning and danger levels of 98 dB(A) respectively for an exposure of 8 hours per day specified by ILO.

18.7 Air cleaner oil pull over test

The maximum oil pull over was observed as 0.17 % which is normal.

18.8 Field Test:

18.8.1 Summary of field tests:

The results of the field test are summarized below:

Sl.No.	O b s e r v a t i o n	Wheat harvesting	Paddy harvesting
1.	Speed of operation, kmph	2.90 to 3.95	2.73 to 2.93
2.	Area covered, ha/h	0.678 to 1.161	0.747 to 0.873

3.	Fuel consumption: - l/h - l/ha	7.26 to 8.53 6.78 to 10.70	7.14 to 8.55 8.31 to 10.86
4.	Crop throughput, tonne/h	8.3 to 13.9	7.0 to 14.4
5.	Grain breakage in main grain outlet, %	0.905 to 1.418	0.542 to 1.300
6.	Header losses, %	0.532 to 1.206	0.525 to 1.105
7.	Total non-collectable losses, %	0.943 to 2.298	0.856 to 2.264
8.	Total collectable losses, %	0.200 to 1.006	0.712 to 2.100
9.	Total processing losses, %	1.846 to 2.858	2.024 to 4.329
10.	Threshing efficiency, %	98.6 to 99.8	97.1 to 99.2
11.	Cleaning efficiency, %	95.6 to 97.0	94.0 to 96.0

18.8.2 Harvesting of any other crops:

The performance of combine to harvest wheat, paddy crops was evaluated as the same were recommended by the applicant.

18.8.3 Ease of Operation and Safety Provision:

- i) The controls provided around the operator are within easy reach, but not labelled with symbols as per Indian standard. Therefore it is recommended that the symbols as per the requirement of IS-6283-1998 may be provided.
- ii) Spark arresting device is not provided in the engine exhaust system which is considered essential.
- iii) Safety device / slip clutches in knife drive auger etc. drive are considered essential from safety point of view which needs to be provided.
- iv) The mechanical arrangement for adjusting the reel speed though provided, needs to be modified such that the same could be controlled from operators position.
- v) Mechanical lock for reel in raised position needs to be provided to ensure safety while working on cutter bar.

18.8.4 Assessment of Wear:

- i) The discard limits for engine components i.e. cylinder liner, piston, piston rings, valves, valve guides, big-end bearings and main bearings have not been specified by the applicant. It is, therefore, not possible to ascertain their wear with reference to discard limit.
- ii) The transmission gears and components were found in normal working condition.
- iii) The timing gears, clutch lining, release bearing were found in normal working condition.
- iv) The condition of the components of brake, hydraulic system and steering system was observed to be normal.
- v) The condition of the bearing, chains, sprockets and belts was observed to be normal.
- vi) The components of starter motor and alternator were found in normal working condition.
- vii) The rate of wear of rasp bar and peg teeth of threshing cylinder & concave were observed to be normal.

18.9 Hardness and Chemical composition:

The Hardness & chemical composition of knife blade does not conform to IS . It should be incorporated at production level.

18.10 Maintenance/Service problems:

No noticeable maintenance/service problem was observed during the course of test at this Institute.

18.11 Labelling of Combine Harvester:

The labelling plate is not provided on the combine harvester. But it needs to be provided as per IS:10273-1999.

18.12 Literature supplied with the Machine:

18.12.1 The operator manual for combine harvester which comprises of operation, maintenance and repair of combine harvester is provided. It should be brought out in regional languages also as per relevant Indian standards.

19. SELECTED PERFORMANCE AND OTHER CHARACTERISTICS AS PER IS: 15806-2008.

S. No.	Characteristics	Requirement	Declared	Observed	Remark
1. Prime mover performance					
i)	Max. Power (absolute) Average max. power observed during 2 hrs. max. power test in natural ambient condition kW(Ps)	It should not be less than 5% of the declared value.	78.0(106.0)	77.2(105.0)	Conforms
ii)	Max. power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW(Ps)	Max. power observed must not be less than 5% of declared value.	Not specified	61.2(83.2)	Does not conform
iii)	Power at rated engine speed, kW(Ps)	The observed value must not be less than 5% of the declared value by the applicant.	78.0(106.0)	75.1(102.1)	Conforms
iv)	Specific fuel consumption g/kWh.	The average observed value during 2 hr. max. power test must be within $\pm 5\%$ of the declared value by applicant/ manufacturer.	Not specified	286	Does not conform

COMB - 55/1258

COMBINE HARVESTER-COMM.(ICT)
'NORTH INDIA - 749 (SELF PROPELLED)'

43

	v)	Max. smoke density (bosch no.) at 80% load between the speed at max. power & 55% of speed at max. or 1000 rpm which ever is higher, should be observed as per CMVR rule	For tractor :- 5.2 bosch no. or 75 hartridge For engine :- Free deceleration or natural aspirated or turbo charges - 65 hartridge	--	2.52	Conforms
	vi)	Max. crank shaft torque, (N-m) observed during the test after no load engine speed is adjusted as per manufacturer's recommendation for field work	It must not be less than 8% of declare value by manufacturer.	400@1500-1600 rpm	404	Does not conform
	vii)	Back up torque, %	7% min.	7.0	19	Conforms
	viii)	Max. operating temp. To be declared by manufacturer	i) engine oil ii) Coolant	120-130° C 100-105° C	126° C 99° C	Conforms
	ix)	Lubrication oil consumption, g/kWh	1% of SFC at 5hr. max. power test during high ambient condition	2.88 1% of (SFC) observed during high ambient	0.285	Conforms
2.	Brake performance					
	i)	Max. stopping distance at a force equal to or less than 600 N on break pedal, m	10 m or $S \leq 0.15V + V^2/130$ V= speed corresponding to 80% of design max. speed, kmph	--	5.83 in cold condition 5.94 in hot condition	Conforms
	ii)	Max. force exerted on brake pedal to achieve a deceleration of 2.5 m/sec ² .	$\leq 600N$.	--	187 in cold condition 177 in hot condition	Conforms
	iii)	Whether parking brake is effective at a force of 600 N at foot pedal or 400 N at Hand and lever	Yes or No	--	Yes	Conforms
3.	Mechanical vibration					
	i)	Operator's platform	120 μm max.	--	336	Does not conform

COMB - 55/1258

COMBINE HARVESTER-COMM.(ICT)
'NORTH INDIA - 749 (SELF PROPELLED)'

44

	ii)	Steering wheel	150 μm max.	--	424	Does not conform
	iii)	Seat with driver seated	120 μm max.	--	287	Does not conform
Air cleaner oil pull over						
	i)	Max. oil pull over in % age when tested in accordance with IS: 8122 pt. (II)-2000	0.25% max.	--	0.17	Conforms
Noise measurement						
	i)	Max. ambient noise emitted by combine dB (A)	88 dB (A) as per CMVR	--	87.8	Conforms
	ii)	Max. noise at operator's ear level dB (A)	98 dB (A) as per CMVR,	--	96.1	Conforms
Discard limit						
	i)	Cylinder bore diameter	Should not exceed the values declared by the manufacture	107.18	107.31	Does not conform
	ii)	Piston diameter	-do-	107.10	107.07	Does not conform
	iii)	Ring end gap	--do--	2.032	0.55	Conforms
	iv)	Ring groove clearance	--do--	0.254	0.13	Conforms
	v)	Diametrical and axial clearance of big end bearing	--do--	Diametrical – 0.178 Axial – 0.356	0.13 0.20	Conforms
	vi)	Diametrical and axial clearance of main bearings	--do--	Diametrical – 0.178 Axial – 0.356	0.12 0.15	Conforms
	vii)	Thickness of brake lining	--do--	Not specified	6.50	Does not conform
	viii)	Thickness of clutch plate	--do--	Not specified	10.5	Does not conform
Field performance						
	i)	Suitability for crops	Wheat & paddy essential	Wheat & paddy	Suitable for Wheat & paddy	Conforms
	ii)	Grain breakage in grain tank	$\leq 2.5\%$	--	Wheat- 0.905-1.418% (Avg. -1.267%) Paddy- 0.542-1.300% (Avg. 0.782%)	Conforms

COMB – 55/1258

COMBINE HARVESTER-COMM.(ICT)
'NORTH INDIA - 749 (SELF PROPELLED)'

45

	iii)	Non collectable losses	$\leq 2.5\%$ for wheat, paddy & gram $\leq 4.0\%$ for soybean	--	Wheat- 0.943-2.298% (Avg. -1.371%) Paddy- 0.856-2.264% (Avg. 1.542%)	Conforms Conforms
	iv)	Threshing efficiency	$\geq 98\%$ wheat & paddy	--	Wheat- 98.6-99.8% (Avg. -99.4%) Paddy- 97.1-99.2% (Avg. -98.6%)	Conforms Conforms
	v)	Cleaning efficiency	$\geq 96\%$ wheat & paddy	--	Wheat- 95.6-97.0% (Avg. -96.3%) Paddy- 94.0-96.0% (Avg. 94.8%)	Conforms Does not conform
8.	Safety requirement					
	i)	Guards against all moving parts	Essential	--	Provided	Conforms
	ii)	Lighting arrangement a) Head light b) Parking light c) Indication d) Reverse gear e) Brake f) Number plate	Essential as per CMVR	--	Provided as per CMVR report No. CMVR/Comb-SP/2009/16 dated 14.10.2009	Conforms
	iii)	Grain tank cover	Essential	--	Provided	Conforms
	iv)	Spark arrester in engine's exhaust	Essential	--	Not provided	Does not conform
	v)	Stone trap before concave	Essential	--	Provided	Conforms
	vi)	Rear view mirror	Essential	--	Provided	Conforms
	vii)	Slip clutch at following drives – a) Cutting platform b) under shout conveyor drive c) Grain & tailing elevator	Essential	--	Not provided	Does not conform
	viii)	Anti slip surfaces at operator platform & ladder & proper gripping for the control levers	Essential	--	Provided	Conforms
	ix)	Working clearance around the controls	Essential 70 mm, min.	--	Provided	Conforms

COMB - 55/1258

COMBINE HARVESTER-COMM.(ICT)
'NORTH INDIA - 749 (SELF PROPELLED)'

46

	x) Labelling of control gauge	Essential	--	Provided	Conforms
Material of construction :					
i)	Guard should conforms to IS: 6024 - 1983	The guard (except ledger plate) shall be manufactured from malleable iron casting (IS: 2108-1977), steel casting (IS: 1030-1974) or steel forging (IS: 2004-1978)	Not specified	C = 0.41 Si=0.20 Mn=0.65 P=0.053 S=0.041	Unascertai —nable as the limit of the elements as observed are not specified in relevant code.
ii)	Knife blade As per IS :6025 -1982	It must have Chemical composition as C= 0.70-0.95 % Mn =0.30-0.50 %	--	C=0.77 Mn.=0.65	Conforms Does not conform
iii)	Knife back Must meet the requirement IS:10378-1982	The knife back shall be manufactured from Carbon Steel having minimum carbon content of 0.35 %	--	C = 0.13 Si=0.16 Mn=0.41 P=0.057 S=0.041	Does not conform
10.	Labelling of combine harvester				
	It should conforms to IS: 10273-1987	Essential, It should mention make & model, Engine No. Chassis No., Year of manufacture, Power & SFC of engine	--	Provided	Conforms
11.	Break down (critical major & minor)				
		Essential as per IS: 15806-2008 Annexure A1, A2, A3	--	None	Conforms

TESTING AUTHORITY:

(J. P. MANDAL) AGRICULTURE ENGINEER	
(P. K. CHOPRA) SENIOR AGRICULTURAL ENGINEER	
A. N. MESHRAM -DIRECTOR-	

Applicant's comments :- Not received

NORTHERN REGION FARM MACHINERY TRAINING AND TESTING INSTITUTE, HISSAR