

ब्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: IMP-971/2255/2018
माह/Month : December, 2018

THIS TEST REPORT VALID UP TO : 31st December, 2025



**MASCHIO GASPARDO VIRAT SP 125, ROTAVATOR
(TRACTOR MOUNTED)**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

6.2 Chemical composition

The chemical composition of blades is tabulated as under:-

Constituents	As per IS: 6690-1981		Composition as observed (% of weight)	Remarks
	Carbon Steel	Silicon Manganese steel		
Carbon (C)	0.70 -0.85	0.50-0.60	0.2650	Does not conform
Silicon (Si)	0.10 -0.40	1.50-2.00	0.2807	Conforms
Manganese (Mn)	0.50 -1.0	0.50-1.00	1.0980	Does not conform
Sulphur (S)	0.05(max)	0.05(max)	0.0000	Conforms
Phosphorous (P)	0.05(max)	0.05(max)	0.0180	Conforms

7. FIELD PERFORMANCE TEST

The field tests of the implement comprising of wet land and dry land operation were conducted for 15.03 and 26.16 hours respectively to assess the performance of the implement. The performance of implement is reported in **Annexure-I & II** for wet land and dry land operations respectively.

Observations of field performance test are summarized in the ensuing table:

Summary of Field Performance Test

Sl. No.	Parameters/operations	Wet land operation (Puddling)	Dry land operation
I	II	III	IV
1.	Tractor used	Swaraj 735 XT	
2.	Gear used	L-1	L-2
3.	Type of soil (Refer IS:7926-1975)	Sandy loam	
4.	Average soil moisture (%)	-	12.5 to 14.6
5.	Average depth of standing water (cm)	10.8 to 11.7	-
6.	Bulk density of soil (g/cc)	-	1.32 to 1.52
7.	Average speed of operation (kmph)	2.31 to 2.35	2.83 to 3.20
8.	Avg. travel reduction /Avg. wheel slip (%)	-2.46 to -0.73	-2.51 to -0.90
9.	Average depth of puddle/ Average depth of cut (cm)	16.3 to 17.2	6.8 to 8.5
10.	Avg. working width (cm)	-	109 to 114
11.	Area covered (ha/h)	-	0.214 to 0.296
12.	Time required for one ha (h)	-	3.38 to 4.67
13.	Field efficiency (%)	-	69.5 to 81.1
14.	Puddling index (%)	72 to 78	-
15.	Fuel consumption		
		l/h	2.30 to 2.59
		l/ha	-
16.	Average PTO power utilized (kW)	-	8.18

8. EFFECTIVENESS OF SEALINGS

After completion of wet land operation for 15.03 hours, the implement was dismantled for checking the effectiveness of sealing provided against ingress of dust, and water/mud in various sub-assemblies/components. The observations are given in ensuing table:-

Sl. No.	Location	Whether ingress of mud and/or water was observed (Yes/No)
1.	Primary reduction gear box	No
2.	Secondary reduction gear box	No
3.	Rotor assembly (hub)	No

9. EASE OF OPERATION & ADJUSTMENTS

No noticeable difficulty was observed during the operation and adjustment of rotavator.

10. DEFECTS, BREAKDOWN AND REPAIRS

No any noticeable defect or breakdown was observed during 40.48 hours of field operation.

11. COMMENTS AND RECOMMENDATIONS

- 11.1** The labeling plate **MUST** be provided on machine with following information:-
 -Make
 -Model
 -Year of Manufacturer
 -Working Width
 -Recommended tractor power (KW)
 -Manufacturers address
- 11.2** The specifications of implement hitch, does not conform in toto to the 4468 (Part-1)-1997. Hence, it is recommended that implement should be provided with the hitch conforming to relevant Indian Standards.
- 11.3** Dimensions of PIC of implement do not conform in toto to IS: 4931-1995 and therefore, it should be looked in to for corrective action.
- 11.4** Hardness of the blade does not conform to IS: 6690:1981. This needs to be looked into for corrective action at production level.
- 11.5** The chemical composition blade does not conform to as per IS: 6690-1981. This needs to be looked into for corrective action at production level.
- 11.6** The material of the blade is not specified. It **MUST** be specified.



11.7 Technical literature:-

The following literature was supplied with rotavator during test

- i) Use & maintenance manual
- ii) Spare parts catalogue

The use & maintenance manual should be updated as per IS 8132-1999

TESTING AUTHORITY

R. K. NEMA SENIOR AGRICULTURAL ENGINEER	
P. K. PANDEY DIRECTOR	

12. APPLICANT'S COMMENTS

Para No	Our reference	Applicant's comments
12.1	4.4 Dimension 'M'	We will make changes in design and implement in mass production.
12.2	4.5.1 Dimension 'a, c & x'	We will make changes in design and implement in mass production.
12.3	4.5.3 Dimension D Φ	We will consider this in mass production.

