

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: IMP-983/2277/2019
माह/Month : February, 2019

THIS TEST REPORT VALID UP TO : 28th FEBRUARY, 2026



**RAJ AGROTECH RAJA-222, ROTAVATOR
(TRACTOR MOUNTED)**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

4.11 Lubricants:

Sl. No.	Particulars	As recommended by the manufacturer	As used during test
1	Primary Gear box	Not specified	Oil originally filled in the machine was not changed
2	Secondary Gear box	Not specified	
3	Rotor Hub	Not specified	Servo M.P grease
4	Propeller Shaft	Not specified	Servo M.P grease

5. RUNNING – IN

Not recommended by the manufacturer.

6. LABORATORY TEST**6.1 Hardness:** - The surface hardness of blade was recorded as under: -

Description	As per IS: 6690:1981 (HRC)	Hardness as observed (HRC)	Remarks
Edge portion	53 to 59	40.0 to 40.3	Does not conform
On shank portion	37 to 45	40.0 to 40.3	Conforms

6.2 Chemical composition

The chemical composition of blades is tabulated as under:-

Constituents	As per IS: 6690-1981		Composition as observed (% of weight)	Remarks
	Carbon Steel	Silicon Manganese steel		
Carbon (C)	0.70 -0.85	0.50-0.60	0.3028	Does not conform
Silicon (Si)	0.10 -0.40	1.50-2.00	0.4928	Does not conform
Manganese (Mn)	0.50 -1.0	0.50-1.00	1.1630	Does not conform
Sulphur (S)	0.05(max)	0.05(max)	0.0063	Conforms
Phosphorous (P)	0.05(max)	0.05(max)	0.0258	Conforms

7. FIELD PERFORMANCE TEST

The field tests of the implement comprising of wet land and dry land operation were conducted for 17.16 and 25.52 hours respectively to assess the performance of the implement. The performance of implement is reported in **Annexure-I & II** for wet land and dry land operations respectively.

Observations of field performance test are summarized in the ensuing table:

Summary of Field Performance Test

Sl. No.	Parameters/operations	Wet land operation (Puddling)	Dry land operation
I	II	III	IV
1.	Tractor used	Sonalika-750 DI III DC	
2.	Gear used	L-1	L-2
3.	Type of soil (Refer IS:7926-1975)	Sandy loam	
4.	Average soil moisture (%)	-	8 to 8.4
5.	Average depth of standing water (cm)	11 to 11.3	-
6.	Bulk density of soil (g/cc)	-	1.47 to 1.53
7.	Average speed of operation (kmph)	1.96 to 1.99	2.62 to 2.80
8.	Avg. travel reduction /Avg. wheel slip (%)	-1.00 to -0.55	-3.45 to -1.42
9.	Average depth of puddle/ Average depth of cut (cm)	19.8 to 20.8	5.8 to 7.35
10.	Avg. working width (cm)	-	241 to 244
11.	Area covered (ha/h)	-	0.485 to 0.564
12.	Time required for one ha (h)	-	1.77 to 2.06
13.	Field efficiency (%)	-	76.9 to 82.6
14.	Puddling index (%)	78 to 81	-
15.	Fuel consumption		
		l/h	2.14 to 2.23
		l/ha	5.58 to 7.48
16.	Average PTO power utilized (kW)	-	15.44

7.1 Wet Land operation**7.1.1 Quality of work**

- i) The depth of puddle was recorded as 19.8 to 20.8 cm.
- ii) The puddling index was recorded as 78 to 81 %.

7.2 Dry land operation**7.2.1 Rate of work**

- i) The rate of work was recorded as 0.485 to 0.564 ha/h, and the speed of operation varies from 2.62 to 2.80 kmph.
- ii) The time required to cover one hectare was recorded as 1.77 to 2.06 h.

7.2.2 Quality of work

- i) The depth of operation was recorded as 5.8 to 7.35 cm.
- ii) Average working width was observed as 241 to 244 cm.
- iii) Field efficiency was observed as 76.9 to 82.6 %.

7.3 Labour requirement

In all, two skilled operators are needed to ensure continuous operation of machine for day long period.

7.4 Wear analysis (on mass basis)

Wear of hatchet blades (on mass basis) was measured and recorded in ensuing table:

Percentage wear of rotavator blades on mass basis:

Sl. No.	Initial mass of blade (g)	Mass of blade after 42.68 hr. of operation (g)	Difference of weight (g)	Percentage of wear (%) after 42.68 hr.	Percentage of wear on hour basis (%)
1.	1013.3	968.7	44.6	4.40	0.10
2.	1027.4	991.1	36.3	3.53	0.08
3.	980.2	950.6	29.6	3.02	0.07
4.	969.7	939.0	30.7	3.16	0.07
5.	1014.4	967.0	47.4	4.67	0.11
6.	996.9	950.0	46.9	4.70	0.11
7.	992.0	966.4	25.6	2.58	0.06
8.	985.4	940.3	45.1	4.58	0.11
9.	1008.1	968.2	39.9	3.96	0.09
10.	1010.1	959.8	50.3	4.98	0.12

8. EFFECTIVENESS OF SEALINGS

After completion of wet land operation for 17.16 hours, the implement was dismantled for checking the effectiveness of sealing provided against ingress of dust, and water/mud in various sub-assemblies/components. The observations are given in ensuing table:-

Sl. No.	Location	Whether ingress of mud and/or water was observed (Yes/No)
1.	Primary reduction gear box	No
2.	Secondary reduction gear box	No
3.	Rotor assembly (hub)	No

9. EASE OF OPERATION & ADJUSTMENTS

No noticeable difficulty was observed during the operation and adjustment of rotavator.

10. DEFECTS, BREAKDOWN AND REPAIRS

No noticeable defect or breakdown was observed during 42.68 hours of field operation.

11. COMMENTS AND RECOMMENDATIONS

- 11.1** The labeling plate MUST be provided on machine with following information:-
- Make
 - Model
 - Year of Manufacturer
 - Working width
 - Recommended tractor power, kW
 - Manufacturer address

- 11.2 The specifications of implement hitch, does not conform in toto to the 4468 (Part-1)-1997. Hence, it is recommended that implement should be provided with the hitch conforming to relevant Indian Standards.
- 11.3 Dimensions of PIC of implement do not conform in toto to IS: 4931-1995 and therefore, it should be looked in to for corrective action.
- 11.4 Hardness of the blade does not conform to IS: 6690:1981. This needs to be looked into for corrective action at production level.
- 11.5 The chemical composition of blades does not conform to as per IS: 6690-1981. This needs to be looked into for corrective action at production level.
- 11.6 The safety device should be provided in propeller shaft against overload
- 11.7 The recommended grade of lubrication for primary and secondary gear box **MUST** be specified on rotavator.
- 11.8 The hitch pin was not provided during the test. It **MUST** be provided.
- 11.9 **Technical literature:-**
No literature was supplied with the rotavator during testing. The following literature should be developed and supplied with the rotavator.
- Operator manual
 - Spare parts catalogue
 - Service manual

TESTING AUTHORITY

R. K. NEMA SENIOR AGRICULTURAL ENGINEER	<i>Per</i>
P. K. PANDEY DIRECTOR	<i>U3n - m08h</i>

12. APPLICANT'S COMMENTS

No comments received from applicant.