

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: COMP-143/2382/2019

माह/Month: December, 2019

THIS TEST REPORT VALID UP TO : 31th DECEMBER, 2026



**NEW GURDEEP SUPER SMS, FITTED ON GILL PREET-962
SELF PROPELLED COMBINE HARVESTER**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

4. ROTOR BALANCING TEST

Date of test	:	26.11.2019
Make and model of Rotor balancing machine	:	PROTEQ and H - 1 K
Mass of the job (kg)	:	85.62
Service speed of the job rpm	:	1998
ISO balancing grade	:	G 16
Balancing speed rpm	:	1998

S.No.	Particulars	As permissible	As observed	Remark
	Unbalance weight (Left side plane) (g)	39.69	12.1	Balanced
	Unbalance weight (Right side plane) (g)	39.69	38.2	Balanced

Unbalance angle (Left side plane) (degree)	310.83
Unbalance angle (Right side plane) (degree)	338.31

5. FIELD PERFORMANCE TEST

- 5.1 The SMS fitted on Gill Preet-962 combine harvester was operation in the paddy field for 5.33 hrs, to assess (a) performance of SMS and, (b) performance of combine harvester with SMS.

The crop parameters recorded during the test were as under:-

Crop Parameters

Sl. No.	Parameters	Observations
1.	Average plant height, cm	98 to 105
2.	Average number of tillers/m ²	241 to 370
3.	Average length of ear head, cm	26 to 29
4.	Average straw/grain ratio	2.4
5.	Average moisture, %	
	- Grain	14.9
	- Straw	66.9

The results of field performance test of paddy crop harvesting are summarised in Table - 5 and presented in detail in Appendix – II to V.

**Table- 5 : SUMMARY OF LOSSES & EFFICIENCIES OBSERVED DURING FIELD
PERFORMANCE TEST.**

Crop variety	Collec table losses (%)	Non- collec table losses (%)	Total proces sing losses (%)	Thres hing efficie ncy (%)	Cleani ng efficie ncy (%)	Grain breakage in main grain tank (%)	Forwa rd speed (kmph)	Area cover ed (ha/h)	Fuel consumption		Grain out put (kg/h)	Crop thro ugh-put (t/h)
									(l/h)	(l/ha)		
1	2	3	4	5	6	7	8	9	10	11	12	13
PR- 1509	2.2	0.8	2.3	98.6	96.7	0.80	2.69	0.748	7.07	9.45	3848.96	13.1

SUMMARY OF FIELD PERFORMANCE OF SMS

Uniformity of straw spread, CV, (percent)	18.6
Weighted mean size of chopped strew, cm	8.9

6. DEFECTS, ADJUSTMENTS, BREAKDOWNS AND REPAIRS

No noticeable defect observed

7. SUMMARY OF OBSERVATIONS**7.1 Field test**

7.1.1	Performance of SMS with Gill Preet-962 Combine Harvester	
1	Uniformity of straw spread, CV, (percent)	18.6
2	Weighted mean size of chopped strew, cm	8.9

7.1.2 Performance of Gill Preet-962 combine harvester with New Gurdeep Super SMS

S. No	Parameters	Observations
1.	Speed of operation (kmph)	2.69
2.	Area covered (ha/h)	0.748
3.	Fuel consumption: - (l/h) - (l/ha)	7.07 9.45
4.	Crop throughput (tonne/h)	13.19
5.	Grain breakage in main grain outlet (%)	0.80
6.	Header losses (%)	0.68
7.	Total non-collectable losses (%)	0.8

COMP-143/2382/2019	NEW GURDEEP SUPER SMS, FITTED ON GILLPREET-962, SELF PROPELLED COMBINE HARVESTERS (COMMERCIAL)
---------------------------	---

8.	Total collectable losses (%) (un threshed + broken from main outlet)	2.2
9.	Total processing losses (%)	2.3
10.	Threshing efficiency (%)	98.9
11.	Cleaning efficiency (%)	96.7

8. SELECTED PERFORMANCE AND OTHER CHARACTERISTICS AS PER IS: 15806:2018

S. No	Characteristics	Category (Evaluative/ Non evaluative)	Requirement Declaration	Tolerance	Observed	Remark
1	2	3	4	5	6	7
8.1	Uniformity of straw spread, CV, (percent)	Evaluative	20 Max.	--	18.6	Conform
8.2	Weighted mean size of chopped strew, cm	Evaluative	20 Max.	--	8.9	Conform
8.3	Processing losses in rice (%)	Evaluative	Average 4%	Nil	2.3	Conform
8.4	Threshing efficiency (%)	Evaluative	≥ 98 %	Nil	98.9	Conform
8.5	Cleaning efficiency	Evaluative	≥ 96 %	Nil	96.7	Conform
8.6	Grain Breakage in main grain tank	Evaluative	≤ 2.5 %	Nil	0.80	Conform
8.7	Non-collectable losses	Evaluative	≤ 2.5 %	Nil	0.8	Conform
	i) Material of blades for straw management System (SMS)	Non evaluative	The flail and fixed blades shall be manufactured from steel having the following chemical composition or such other composition as shall be agreed to between the supplier and the purchaser. a) Carbon 0.70 to 1.0 percent.	--	Flail blade C- 0.5961 Mn- 0.2619 Cr- 0.0080 Ni- 0.5542 Fixed blade C- 0.5961 Mn- 0.2619 Cr- 0.0080 Ni- 0.5542	As the code itself accommodate the variation in chemical composition, there is little scope for declaration of conformity or otherwise

vi) Break down (critical, major & minor)					
Sr. No	Category of breakdowns	Category (Evaluative/ Non evaluative)	Requirements as per IS 15806:2018	As observed	Whether meets the requirements (Yes/No)
1.	Critical	Evaluative	No critical breakdown	None	Yes
2.	Major	Evaluative	Not more than two and neither of them should be repetitive in nature	None	Yes
3.	Minor	Evaluative	Not more than five and frequency of each should not be more than two	None	Yes
4.	Total breakdown	Evaluative	In no case total no of (major + minor) breakdowns exceed five	None	Yes

9. CRITICAL TECHNICAL SPECIFICATIONS

(Vide Ministry's communication F. No 9-1/2019 M&T (I&P) dated 20.08.2019)



Sl No.	Parameters	Specification	Observation	Remarks
Rotor				
1.	Rotor diameter, mm	165-170	165	Conforms
2.	No. of lugs on rotor in row	6	6	Conforms
3.	No. of rows in periphery	4	4	Conforms
4.	Length of pivotal flail, mm	170-180	176.3	Conforms
5.	Width of flail, mm	50 ± 1	50.3	Conforms
6.	Thickness of flail, mm	5.0 (Min.)	5.0	Conforms
7.	No of flails in one set	2	2	Conforms
8.	Spacing between flails of one set, mm	35 (Max)	37.8	Does not conform
9.	Distance between adjacent flails units, mm	200±10	200	Conforms
10.	No of rows/bars of serrated blades	1	1	Conforms
11.	No of serrated blades in row	20 (Min.)	24	Conforms
12.	Spacing between serrated blades, mm	50 (Max.)	50	Conforms
13.	Overlapping of pivotal blade on serrated blade, mm	60 (Min.) (adjustable)	62	Conforms
Spreader				
14.	Total no of flaps	6 + 2 (side)	6+2	Conforms
15.	Length of flaps, cm	38 (Min.)	38.5	Conforms
16.	Distance between flaps (left to right)	Adjustable	Adjustable	Conforms

17.	Spreader angle with horizontal, degree	Adjustable preferably downwards	Adjustable	Conforms
18.	Spreader angle with line of travel, degree	15 (Min.) (adjustable)	25° Max	Conforms
19.	Spreader sheet thickness, mm	2.5-3.0	3.0	Conforms
20.	SMS sheet thickness, mm	5.0 (Min.) for outer	5.5	Conforms
21.	Rotor balancing	Should be dynamically balanced	Balanced	Conforms
22.	Rotor rpm	Min. 1600	1998	Conforms
23.	Fitting of SMS on combine harvester	Rigidly fixed to the combine chassis	Rigidly fixed	Conforms
24.	Fitting of power transmission system on combine harvester	Rigidly fixed to the combine chassis	Rigidly fixed	Conforms
25.	Marking/labelling of machine	Labelling plate should be riveted on the body of machine having Name and address of manufacturer, Country of origin Make Model Year of manufacturer, Serial number, Type Size required size of prime mover (kW), Weight of the machine (Kgs)	Type and size is not specified	Does not conform in toto
26.	Literature	Operator manual, Service manual and Parts catalogue should be provided	Provided	Conforms

10. COMMENTS AND RECOMMENDATIONS

- 10.1 Field performance test**
No noticeable defect observed during field test.
- 10.2** Spacing between flails of one set **does not meet the requirement critical technical specification. It must be looked into.**
- 10.3** Marking/labelling of machine **does not meet the requirement critical technical specification. It must be looked into.**
- 10.4** Applicant has recommended Gillpreet-962 combine harvester for SMS field testing. This is vital information and therefore the same must be inscribed in labelling plate also for the guidance of users.
- 10.5** In the labelling plate, the power requirement is given as 75 kW, whereas the power of the combine harvester recommended is 85.10 kW. **This is misleading and therefore Must be looked into for corrective action.**
- 10.6 Ease of operation and safety provision**
No noticeable difficulties observed during operation of combine harvester.
- 10.7** The material of SMS blade is not specified. It should be specified.
- 10.8 Literature supplied with the machine**
Operator Manual cum spare parts catalogue cum service provided during testing. However, the same need to be updated as per IS-8132-1999

TESTING AUTHORITY

MAAN SINGH SENIOR TECHNICAL ASSISTANT	
P. K. PANDEY DIRECTOR	

Test report compiled by C. Veeranjanyulu, Senior Technician

11. APPLICANT'S COMMENTS

In future we will manufacture of Super SMS according to your comments

