

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: ROTAVATOR-324/2616/2020
माह/Month: December, 2020

THIS TEST REPORT VALID UP TO : 31st December, 2027



**JANTA 7 FEET, ROTAVATOR
(TRACTOR MOUNTED)**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

4.11 Lubricants:

Sl. No.	Particulars	As recommended by the manufacturer	As used during test
1	Primary Gear box	CL-140	Oil originally filled in the rotavator was not changed
2	Secondary Gear box	CL-140	
3	Rotor Hub	Not specified	M.P. Grease
4	Propeller Shaft	Not specified	

5. RUNNING – IN

Rotavator was run in for 1.42 hour before field performance test.

6. LABORATORY TEST**6.1 Hardness:** - The surface hardness of blade was recorded as under: -

Description	As per IS: 6690:1981 (HRC)	Hardness as observed (HRC)	Remarks
Edge portion	53 to 59	45	Does not conform
On shank portion	37 to 45	45	Conforms

6.2 Chemical composition

The chemical composition of blades is tabulated as under:-

Constituents	As per IS: 6690-1981		Composition as observed (% of weight)	Remarks
	Carbon Steel	Silicon Manganese steel		
Carbon (C)	0.70 -0.85	0.50-0.60	0.2306	Does not conform
Silicon (Si)	0.10 -0.40	1.50-2.00	0.4069	Does not conform
Manganese (Mn)	0.50 -1.0	0.50-1.00	0.8315	Conforms
Sulphur (S)	0.05(max)	0.05(max)	0.0408	Conforms
Phosphorous (P)	0.05(max)	0.05(max)	0.0272	Conforms

7. FIELD PERFORMANCE TEST

The field tests of the rotavator comprising of dry land and wet land operation were conducted for 26 and 10 hours respectively to assess the performance test is reported in **Annexure-I & II** for dry land and wet land operation respectively.

Observations of field performance test is summarized in the ensuing table:-

ROTAVATOR-324/2616/2020	JANTA 7 FEET, ROTAVATOR (TRACTOR MOUNTED) (COMMERCIAL)
-------------------------	---

Summary of Field Performance Test

Sl. No.	Parameters/operations	Dry land operation	Wet land operation (Puddling)
I	II	III	IV
1.	Tractor used	ACEDI-550	
2.	Gear used	L-1	L-1
3.	Type of soil	Sandy loam	
4.	Average soil moisture (%)	9.40 to 17.50	--
5.	Average depth of standing water (cm)	--	9.28 to 9.33
6.	Bulk density of soil (g/cc)	1.470 to 1.640	--
7.	Average speed of operation (kmph)	1.90 to 1.92	1.91 to 1.92
8.	Avg. travel reduction (%)	--	-1.66 to -0.62
9.	Avg. wheel slip (%)	-1.51 to 1.91	--
10.	Average depth of puddle (cm)	--	30.3 to 32.5
11.	Average depth of cut (cm)	9.22 to 10.06	--
12.	Avg. effective width (cm)	192 to 197	--
13.	Area covered (ha/h)	0.308 to 0.345	--
14.	Time required for one ha (h)	2.89 to 3.25	--
15.	Field efficiency (%)	83 to 93	--
16.	Puddling index (%)	--	79 to 82
17.	Fuel consumption		
	l/h	5.14 to 5.99	3.1 to 3.67
	l/ha	15.62 to 18.36	--

7.1 Dry land operation

7.1.1 Rate of work

- i) The rate of work was recorded 0.308 to 0.345ha/h, and the speed of operation varies from 1.90 to 1.92 kmph.
- ii) The time required to cover one hectare was recorded as 2.89 to 3.25 h

7.1.2 Quality of work

- i) The depth of operation was recorded as 9.22 to 10.06 cm.
- ii) Average effective width was observed as 192 to 197 cm.
- iii) Field efficiency was observed as 83 to 93 %.

7.2 Wet Land operation

7.2.1 The tractor was fitted with half cage wheel on rear pneumatic traction wheel for conducting the puddling operation. The brief specification of half cage wheel is given in Annexure-III

7.2.2 Quality of work

- i) The depth of puddle was recorded as 30.3 to 32.5 cm.
- ii) The puddling index was recorded as 79 to 82 %.

ROTAVATOR-324/2616/2020	JANTA 7 FEET, ROTAVATOR (TRACTOR MOUNTED) (COMMERCIAL)
--------------------------------	---

7.3 Labour requirement

In all, two skilled operators are needed to ensure continuous operation of rotavator for day long period.

7.4 Wear analysis (on mass basis)

Wear of hatchet blades (on mass basis) was measured and recorded in ensuing table:

Percentage wear of rotavator blades on mass basis

Sl. No.	Initial mass of blade (g)	Mass of blade after 37.58 hr. of operation (g)	Difference of weight (g)	Percentage of wear (%) after 37.58 hr.	Percentage of wear on hour basis (%)
1.	994.2	971.2	23	2.31	0.06
2.	1010.3	986.5	23.8	2.36	0.06
3.	1019.8	996.8	23	2.26	0.06
4.	1005.7	981.5	24.2	2.41	0.06
5.	1022.2	1001.9	20.3	1.99	0.05
6.	976.7	960	16.7	1.71	0.05
7.	1000.3	983.2	17.1	1.71	0.05
8.	1023.8	998.2	25.6	2.5	0.07
9.	989.1	969.5	19.6	1.98	0.05

8. EFFECTIVENESS OF SEALINGS

After completion of wet land operation for 10 hours, the rotavator was dismantled for checking the effectiveness of sealing provided against ingress of dust, and water/mud in various sub-assemblies/components. The observations are given in ensuing table:-

Sl. No.	Location	Whether ingress of mud and/or water was observed (Yes/No)
1.	Primary reduction gear box	No
2.	Secondary reduction gear box	No
3.	Rotor assembly (hub)	No

9. EASE OF OPERATION & ADJUSTMENTS

No noticeable difficulty was observed during the operation and adjustment of rotavator.

10. DEFECTS, BREAKDOWN AND REPAIRS

No noticeable defect or breakdown was observed during the test.



11. CRITICAL TECHNICAL SPECIFICATION

Deferred till 31.03.2021 vide Ministry O.M. No 13-13/2020 M&T, (I&P) dated 22.12.2020.

12. COMMENTS AND RECOMMENDATIONS

- 12.1** The Dimension of three point linkage of implement does not conform, in toto, to the requirements of IS: 4468(Part-1)-1997 and therefore, it may be looked into for corrective action.
- 12.2** The Dimensions of PIC of implement does not conform, in toto, to the requirements of IS: 4931-1995 and therefore, it may be looked into for corrective action.
- 12.3** Provision against overload on P.T.O drive shaft is not provided. It **MUST** be provided.
- 12.4** The dimension of PIC Yoke Bore of implement does not conform, in toto, to the requirements of IS:4931-1995 and therefore, it may be looked into for corrective action.
- 12.5** The grade of grease is not specified. It **MUST** be specified.
- 12.6** The stand is not provided. It **MUST** be provided.
- 12.7** The hardness of blades does not conform, in toto, to the requirements of IS: 6690-1981. This needs to be looked into for corrective action.
- 12.8** The chemical composition of blades does not conform, in toto, to the requirements of IS: 6690-1981. This needs to be looked into for corrective action.
- 12.9 Technical Literature:**
No technical literature provided by the applicant during the test. The following literature, therefore, **MUST** be provided as per IS: 8132-1999 for guidance of users.
- (i) Operator's manual
 - (ii) Service Manual
 - (iii) Part's catalog

TESTING AUTHORITY

SANJAY KUMAR AGRICULTURAL ENGINEER	
P. K. PANDEY DIRECTOR	

Draft test report compiled by Girdhari Lal, Technician

13. APPLICANT'S COMMENTS

No comment's received from the applicant.