

व्यावसायिक परीक्षण रिपोर्ट  
COMMERCIAL TEST REPORT

संख्या/ No.: IMP-1036/2624/2020  
माह/Month: December, 2020

**THIS TEST REPORT VALID UP TO : 31<sup>st</sup> December, 2027**



**GAHIR, CURVO-484  
LASER LAND LEVELER**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रेक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: [fmti-nr@nic.in](mailto:fmti-nr@nic.in)

Tele./FAX: 01662-276984

Page 1 of 25

**14. HARDNESS AND CHEMICAL COMPOSITION OF CRITICAL PARTS**

14.1 The result of test of Hardness of blade is tabulated in Table-VII.

**TABLE- VII**

As per IS :9813:2002	Hardness observed (HB)	Remark
353 to 421 (HB)	217.5 (Average)	<b>Does not conform</b>

14.2 Chemical composition

**TABLE- VIII.**

Sr. No.	Material	Requirement as per IS 9813:2002	As observed	Remark
1.	Carbon (C)	0.4 to 0.7	0.2939	<b>Does not conform</b>
2.	Silicon (Si)	--	0.3934	--
3.	Manganese (Mn)	--	0.5450	--
4.	Sulphur (S)	--	0.0564	--
5.	Phosphorous (P)	--	0.0357	--

**15. FIELD TEST**

The field tests of 27 hours with 5 replications were conducted. The field performance observations are given in Annexure-I.

The summary of field performance test is given in Table IX.

**TABLE-IX: Summary of field performance**

Sl. No.	Parameters	Observations	
i)	Tractor used	Mahindra, 655 DI	
ii)	Gear used	H-1	
iii)	Type of soil	Sandy loam	
iv)	Av. soil moisture, %	11.3 to 13.4	
v)	Av. bulk density of soil, g/cc	Before operation After operation	
		1.47 to 1.52 1.52 to 1.62	
vi)	Av. area covered, ha/h	0.037 to 0.071	
vii)	Av. time required for one hectare, h	14.08 to 27.03	
viii)	Av. fuel consumption		
	- l/h	4.39 to 5.71	
	- l/ha	67.52 to 136.29	
ix)	Av-total volume of cut, m <sup>3</sup>	7.75 to 129.29	
x)	Av- total volume of fill, m <sup>3</sup>	29.77 to 488.13	
xi)	Av- total volume of earth work	m <sup>3</sup>	119.43 to 495.88
		(m <sup>3</sup> /h)	34.12 to 100.79
		(m <sup>3</sup> /l)	5.98 to 20.65
xii)	Leveling Index before operation, cm	7.25 to 11.99	
xiii)	Leveling Index after operation, cm	0.49 to 0.82	
xiv)	Draft requirement, kg Range (Average)	739	

**15.1 Rate of Work**

**15.1.1** The field capacity in sandy loam soil was recorded as 0.037 to 0.071 ha/h.

**15.1.2** Av-total volume of cut 7.75 to 129.29 m<sup>3</sup>

**15.1.3** Av- total volume of fill 29.77 to 488.13 m<sup>3</sup>

<b>15.1.4</b>	Av- total volume of earth work	m <sup>3</sup>	119.43 to 495.88
		(m <sup>3</sup> /h)	34.12 to 100.79
		(m <sup>3</sup> /l)	5.98 to 20.65

**15.1.5** The time required to cover one hectare area was recorded as 14.08 to 27.03 h.

**15.2 Quality of work**

Leveling Index before and after field operation was observed from 7.25 to 11.99 and 0.49 to 0.82 respectively.

**15.3 Fuel Consumption:**

- l/h : 4.39 to 5.71

l/ha : 67.52 to 136.29

**16 CRITICAL TECHNICAL SPECIFICATIONS**

Deferred till 31.03.2021 vide Ministry O.M. No 13-13/2020 M&T, (I&P) dated 22.12.2020

**17. CONFORMITY TO INDIAN STANDARD**

<b>17.1</b>	<b>Table -X: Material for different components of leveler (As per IS: 9813-2002)</b>		
<b>S. No.</b>	<b>Components</b>	<b>Material(Requirements)</b>	<b>Observations</b>
I	Frame	Mild steel	Mild steel
ii	Strut hitch	Mild steel	Mild steel
iii	Hitch pin	Carbon steel	Carbon steel
Iv	Pitch adjusting screw	Carbon steel	N.A.
V	Mould board frame	Mild steel	Mild steel
Vi	Side plate	Mild steel	Mild steel
Vii	Mould board	Mild steel	Mild steel
viii	Scarifier	Carbon steel	N.A.
<b>17.2</b>	<b>Other requirements: (As per IS: 9813-2002)</b>		
<b>S.N.</b>	<b>REQUIREMENTS</b>	<b>Observations</b>	<b>Conformity</b>
i	The size of terracer shall be determined by the length, of blade plus the length of extension blade, if any, in meters. The nominal size of the terracer may be between 1.25 to 3.5 meter.	The size of terracer blade is 2.11 m.	Conforms
ii	The beveling shall be done on lower side of the blade. Both the upper and lower sides of the blade may be beveled to make it reversible.	Both upper and lower side beveling is provided	Conforms
iii	The blade shall be beveled. The length of beveling may be 10 mm. The thickness of the edge shall be as far as possible uniform and may be between 1.5 to 3 mm.	Length of beveling- 26	<b>Does not Conform</b>
		Thickness of beveling- 2.7	Conforms
iv	The corners of the square holes shall be slightly rounded.	Round hole provided	--

<b>17.4</b>	<b>Marking and packing:</b>		
	<p>Marking- Each terracer shall be marked with:</p> <p style="margin-left: 20px;">a) Manufacturer's name and trade-mark, if any.</p> <p style="margin-left: 20px;">b) Size; and</p> <p style="margin-left: 20px;">c) Batch or code number</p> <p>These particulars shall be stamped, embossed or engraved on metallic plate and rigidly fitted on a non-wearing part of terrace.</p>	<b>Not marked</b>	<b>Does not conform</b>

### 18. SOUNDNESS OF CONSTRUCTION

No noticeable breakdown occurred during field test.

### 19. COMMENTS & RECOMMENDATION

**19.1** The labeling plate **MUST** be riveted on the machine with following information

- i) Name and address of manufacture
- ii) Country of origin
- iii) Make
- iv) Model
- v) Year of manufacture
- vi) Serial number
- vii) Wt in kg
- viii) Tractor kW/hp

**19.2** The safety warnings, signs and pictograms are not provided on the machine. It should be provided for safety of the users.

**19.3** The hardness of the soil cutting blade does not conform to the requirement of IS: 9813-2002. It Should be looked into for corrective action



**19.4** The chemical composition of the soil cutting blade does not conform to the requirement of IS: 9813-2002. It should be looked into for corrective action

**19.5** The length of bevel of soil cutting blade does not conform to the requirement of IS: 9813-2020. It **MUST** be looked into for corrective action

**20 TECHNICAL LITERATURE**

One booklet entitled "operator/service and spare parts manual" was provided for reference during test. The same, however, needs to be updated as per IS- 8132-1999.

**TESTING AUTHORITY**

SANJAY KUMAR AGRICULTURAL ENGINEER	
P. K. PANDEY DIRECTOR	

Draft test report compiled by C. Veeranjanyulu, Senior Technician

**21. APPLICANT'S COMMENTS**

Para No.	Our reference	Applicant comment
21.1	19.1	We will replace the existing labeling plate with the additional required data.
21.2	19.2	We will provide safety decals in regular production.
21.3	19.3 & 19.4	Corrective action will be taken in regular production.
21.4	20.	We will provide technical literature in regular production.