

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: COMB-227/2650/2021
माह/Month: January, 2021

THIS TEST REPORT VALID UP TO : 31st January, 2028



**DASMESH-7100 DLX
SELF PROPELLED COMBINE HARVESTER**



सत्यमेव जयते

भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrftti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

15. FIELD TEST

15.1 Combine harvester was operated in field for 30.58 and 30.20 hours for wheat and paddy harvesting respectively. During the test, available varieties of crop were harvested to assess the field performance of combine with regard to quality of work, rate of work, fuel consumption, safety and soundness of construction etc. The crop and atmospheric conditions during field test are given in **Appendix - II & IV** respectively.

The crop parameters recorded during the test for all crops are as under:-

Crop Parameters

Sl. No.	Parameters		Observations	
			Wheat	Paddy
1.	Average plant height, cm	:	75 to 98	92 to 158
2.	Average number of tillers/m ²	:	229 to 347	197 to 350
3.	Average length of ear head, cm	:	10 to 11	26 to 31
4.	Average straw/grain ratio	:	0.8 to 1.3	0.9 to 1.8
5.	Average moisture, %			
	- Grain	:	9.0 to 10.9	15.5 to 17.3
	- Straw	:	8.7 to 11	48.68 to 66.71

The results of field performance test of wheat and paddy crops harvesting are summarised in Table – 5 and presented in detail in **Appendix – II to V**.

Table- 5 : SUMMARY OF LOSSES & EFFICIENCIES OBSERVED DURING FIELD PERFORMANCE TEST.

Crop variety	Collectable losses (%) (Max.)	Non-collectable losses (%) (Max.)	Total processing losses (%) (Max.)	Threshing efficiency (%) (Min.)	Cleaning efficiency (%) (Min.)	Grain breakage in main grain tank (Max.) (%)	Forward speed (kmph)	Area covered (ha/h)	Fuel consumption		Grain out put (kg/h)	Crop through-put (t/h)
									(l/h)	(l/ha)		
1	2	3	4	5	6	7	8	9	10	11	12	13
WHEAT												
HD-2967	2.9	1.1	2.9	99.2	96.9	2.20	2.86 to 3.03	0.662 to 0.791	6.07 to 7.38	8.03 to 11.14	3095.43 to 3762.03	6.76 to 7.26
PADDY												
Basmati -1509	2.0	1.3	2.3	98.9	96.2	1.01	1.85 to 1.89	0.357 to 0.480	6.99 to 9.49	19.60 to 19.76	2445.65 to 3340.96	5.10 to 9.25
ND 359	1.6	0.4	1.8	98.6	96.1	0.42	1.86 to 1.89	0.394 to 0.422	7.95 to 8.96	18.87 to 22.72	3684.49 to 4347.05	8.10 to 9.26
Basmati -17, 18	1.2	0.1	1.2	99.5	96.2	0.64	1.78	0.465	7.91	17.0	3733.90	9.08

18. SUMMARY OF OBSERVATIONS

18.1 ENGINE PERFORMANCE TEST

Table-1 : ENGINE PERFORMANCE TEST (NATURAL AMBIENT)

Brake Power kW	Engine speed (rpm)	Fuel consumption			Specific energy, kWh/l
		l/h	kg/h	Specific, kg/kWh	
(1)	(2)	(3)	(4)	(5)	(6)
a) Maximum power – 2 hours test					
64.9	2250	19.42	16.39	0.253	3.34
b) Power at rated engine speed: (2200 rpm)					
64.7	2200	19.02	16.05	0.248	3.40

*High idle at no load was 1650 rpm recommended for field operation.

Table-2 : ENGINE TEST (HIGH AMBIENT)

Brake power (kW)	Engine speed (rpm)	Fuel consumption			Specific energy, kWh/l
		l/h	kg/h	Specific, kg/kWh	
(1)	(2)	(3)	(4)	(5)	(6)
a) Maximum power -					
62.2	2250	19.07	16.10	0.259	3.26
b) Power at rated engine speed (2200 rpm)					
61.9	2200	18.41	15.54	0.251	3.36

18.2 Field test

18.2.1 Summary of field tests

The results of the field test are summarized below:-

S. No	Parameters	Observed range	
		Wheat harvesting	Paddy harvesting
1.	Range of average speed of operation (kmph)	2.86 to 3.03	1.78 to 1.89
2.	Range of average area covered (ha/h)	0.662 to 0.756	0.357 to 0.480
3.	Maximum average fuel consumption:		
	- (l/h)	6.07 to 7.38	6.99 to 9.49
	- (l/ha)	8.03 to 11.14	17.0 to 19.76
4.	Range of average crop throughput (tonne/h)	6.76 to 7.26	5.10 to 9.26
5.	Average of maximum grain breakage in main grain outlet (%)	2.20	1.01
6.	Average of maximum header losses (%)	1.02	0.75
7.	Average of maximum total non-collectable losses (%)	1.1	1.3
8.	Average of maximum total collectable losses (%) (un threshed + broken from main outlet)	2.9	2.0
9.	Average of maximum total processing losses (%)	2.9	2.3

10.	Average of minimum threshing efficiency (%)	99.2	98.6
11.	Average of minimum cleaning efficiency (%)	96.9	96.1
Performance of straw chopper cum spreader			
12	Uniformity of straw spread, CV	--	17.6
13	Weighted mean size of chopped straw, cm	--	12.7

18.3 Conformity to Indian Standard

- (i) IS: 6025-1982 (Reaffirmed 2014)-Specification for : **Does not conform in toto**
knife section for harvesting machine.
- (ii) IS: 6024-1983 (Reaffirmed 2014)-Specification for : **Does not conform in toto**
guards for harvesting machines.
- (iii) IS: 10378-1982 (Reaffirmed 2016)-Specification of : **Does not conform in toto**
knife back for harvesting machine.
- (iv) IS: 6283 (Part I & Part II)-2007(Reaffirmed 2014)- : **Does not conform in toto**
Tractors and machinery for agriculture and forestry-
symbol for operator controls and other displays.
- (v) IS: 8133-1983 (Reaffirmed 2014)-Guidelines for : **Does not conform in toto**
location & operation of operator controls on agricultural
tractors and machinery.
- (vi) IS: 15806-2018 (Combine Harvester recommendation : **Does not conform in toto**
on selected performance and other characteristics)

19. SELECTED PERFORMANCE AND OTHER CHARACTERISTICS

S. No	Characteristics	Category (Evaluative/Non evaluative)	Requirement Declaration	Tolerance	Observed	Remarks
1	2	3	4	5	6	7
I. Prime mover performance						
a)	Max. Power (absolute) Average max. Power observed during 2 hrs. Max. Power test in natural ambient condition, kW	Evaluative	60	±5% of declared value	64.9	Does not conform to IS: 15806-2018
b)	Max. Power observed during test after adjusting the no load engine speed as per recommendation of the manufacturer for field work, kW	Evaluative	54	±5% of declared value	56.1	Conforms

21. COMMENTS AND RECOMMENDATIONS

- 21.1 **Prime mover performance :**
i). The max. Power observed during 2 hrs max. Power test does not meet the requirement of evaluative requirement of IS: 15806-2018. It **MUST** be looked into.
ii). Max. Crank shaft torque at specified field setting does not meet the requirement of evaluative requirement of IS: 15806-2018. It **MUST** be looked into.
- 21.2 The power at rated engine speed does not meet the requirement of IS: 15806-2018. It should be looked into.
- 21.3 **Mechanical vibration**
The amplitude of mechanical vibration of components marked as (*) in chapter 13 of this report are observed on higher side. This calls for providing suitable remedial measures to dampen the vibration in order to improve the operational comfort and service life of various components & sub-assemblies.
- 21.4 **Field performance test**
No noticeable defect observed during field test.
Ease of operation and safety provision
i) No noticeable difficulties observed during operation of combine harvester.
ii) Slip clutch at undershot conveyor drive is not provided. It **MUST** be provided as per the requirement of IS 15806 : 2018
- 21.5 Discard limit of thickness of brake lining is not specified. It **MUST** be specified.
- 21.6 Discard limit of thickness of clutch plate is not specified. It **MUST** be specified.
- 21.7 After 1.55 hrs of operation in the wheat, oil leakage from steering pressure pipe, which falls under major break down. Mj-22. It **MUST** be looked into for corrective action.
- 21.8 The labelling of controls gauges and all operating controls does not conform, in toto, to the requirement of the IS: 15806-218. It **MUST** be looked into for take corrective action.
- 21.9 **Hardness and chemical composition**
Hardness & chemical composition of knife blade, knife guard and knife back is not within the limits specified in the relevant standards. It should be looked into for corrective action at regular production level.
- 21.10 Individual brake pedals for LHS & RHS brake is not provided. It may be considered for providing.
- 21.11 Material for bushes for flail blade is not specified. It should be specified as per the requirement of IS: 15806-2018.
- 21.12 There is no drive safety for grain unloading auger. It should be provided.
- 21.13 The discard limit of clearance between engine Inlet & Exhaust valve and valve guide is not specified. It **MUST** be specified.
- 21.14 Spring stiffness of inlet and exhaust valve discard limit is not specified. It **MUST** be specified.
- 21.15 Height of Slow moving vehicle emblem does not meet the requirement of CMVR. It **MUST** be looked into.

21.15 Literature supplied with the machine

The following literature was submitted by applicant during testing.



- i) Operator's manual for combine harvester
- ii) Operator's manual for engine
- iii) Part's catalogue for combine harvester

The following literature should be provided.

- i) Operator's manual for SMS
- ii) Service manual of SMS
- iii) Part's catalogue for SMS

However, the same need to be updated as per IS:-8132-1999

TESTING AUTHORITY

SANJAY KUMAR AGRICULTURAL ENGINEER	
P. K. PANDEY DIRECTOR	

Draft test report compiled by: Abhishek Verma, B.Tech. (Ag. Engg.)

22. APPLICANT'S COMMENTS

We will take corrective actions to meet the requirements of all Indian Standards.