

व्यावसायिक परीक्षण रिपोर्ट
COMMERCIAL TEST REPORT

संख्या/ No.: Powerweeder-131/2776/2022

माह/Month: January, 2022

THIS TEST REPORT VALID UP TO : 31st January, 2027



**XTRA POWER, XPW-750T (E)
POWER WEEDER**



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

उत्तरी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Northern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, सिरसा रोड, हिसार, (हरियाणा) - 125 001

Tractor Nagar, Sirsa Road, HISAR (Haryana)-125 001

[ISO 9001:2015 CERTIFIED]

Website: <http://nrfmtti.gov.in/>

E-mail: fmti-nr@nic.in

Tele./FAX: 01662-276984

11. RUNING - IN

The Power weeder was run-in for 1.50 hour before field performance test. All the fasteners were checked and tightened thereafter.

12. FIELD TEST

The field tests under dry land condition were conducted for 25.78 h. The field tests were conducted at the rated 3600 rpm. In all, 5 tests trials were conducted in sandy loam soil at NRFMTTI farm, Hisar. The summary of the field test for dry land operation is given in table-4.

Crop parameters

- i) Type of weed - Seasonal weeds
ii) Height of weed, cm - 1.8 to 12.0

Table 4: SUMMARY OF FIELD PERFORMANCE TEST

Sl. No.	Parameter	Range
i)	Type of soil	Sandy loam
ii)	Average Soil moisture, %	14.70 to 16.33
iii)	Average Bulk density of soil, g/cc	1.63 to 1.65
iv)	Average Speed of operation, kmph	1.71 to 2.00
v)	Average depth of cut (cm)	5.50 to 6.00
vi)	Average Width of cut, m	0.76 to 0.78
vii)	Average Area covered, ha/h	0.103 to 0.178
viii)	Average Time required for one ha	7.14 to 9.71
ix)	Average Fuel consumption	
	l/h	1.10 to 1.99
	l/ha	7.92 to 14.87
x)	Average Weeding efficiency, %	80.74 to 88.31
xi)	Average Field efficiency, %	76.30 to 92.11

13. ADJUSTMENT, DEFECTS, BREAKDOWNS & REPAIR

No noticeable defect/breakdown observed during test.

14. COMPONENTS/ASSEMBLY INSPECTION AND ASSESSMENT OF WEAR**14.1 Engine :**

The Engine and other assemblies were dismantled after 33 hours of engine operation.

14.1.1 Cylinder :**Cylinder bore dia. (mm)**

Top Position		Middle position		Bottom Position		Max. permissible wear limit
Thrust	Non-thrust	Thrust	Non-thrust	Thrust	Non-thrust	
69.98	70.00	69.98	70.00	69.99	69.98	70.35

Power weeder-131/2776/2022	XTRA POWER, XPW-750T (E) POWER WEEDER (COMMERCIAL)
----------------------------	---

14.1.2 Piston:						
Piston diameter (mm)						
Top position		At Skirt			Max. permissible wear limit (mm)	
Thrust side	Non-thrust side	Thrust side	Non-thrust side	Piston to cylinder clearance (mm)	Piston dia. At skirt	Piston to cylinder clearance
69.54	69.62	69.75	Not measured due to piston design constraint	0.25	--	1.05

14.1.3 Piston Rings end gap:				
Ring No.	Ring end gap (mm)			Max. permissible wear limit
	At top	At middle	At bottom	
1 st compression ring	0.25	0.20	0.15	0.40
2 nd compression ring	0.15	0.20	0.25	0.40
Oil ring	Not measured due to ring design constraint			--

14.1.4 Big end bearing					
Dia. of crank pin (mm)	Dia. of bearing (mm)	Clearance (mm)		Max. permissible wear limit (mm)	
		Diametrical	Axial	Diametrical	Axial
29.96	29.99	0.03	0.50	0.12	1.20

14.1.5 Main bearing of crank shaft:						
Sr. No.	Dia. of main Journal (mm)	Dia. of main bearing (mm)	Diametrical Clearance of main bearing	End float of crank shaft	Max. permissible wear limit (mm)	
					Diametrical	End float of crank shaft
Ball bearing is provided at both side hence not applicable						

14.1.6 Piston Rings groove clearance:		
Ring No.	Ring groove clearance (mm)	Max. permissible wear limit, mm
1 st compression ring	0.02	0.15
2 nd compression ring	0.01	0.15
Oil ring	Not measured due to ring design constraint	--

14.1.7 Valve guide clearance:							
Valve guide diameter(mm)		Valve stem diameter (mm)		Valve guide clearance (mm)		Max. permissible wear limit (mm)	
Inlet	Exhaust	Inlet	Exhaust	Inlet	Exhaust	Inlet	Exhaust
5.56	5.58	5.47	5.44	0.09	0.14	0.35	0.30

Power weeder-131/2776/2022	XTRA POWER, XPW-750T (E) POWER WEEDER (COMMERCIAL)
----------------------------	---

14.2 Valve guides and valve springs

Valve spring stiffness,

Kgf/mm :

Inlet valve : 0.58

Exhaust valve : 0.54

Discard limit

0.56 (Kgf/mm)

0.53 (Kgf/mm)

14.3 Timing gears : No noticeable defect observed.

14.4 Transmission : No noticeable defect observed.

14.5 Rotary drive unit : No noticeable defect observed.

14.6 Wear of blades:

14.6.1 Mass basis:

The wear of the rotary weeder blades was measured after 27.78 hrs. of field operation and the observations are as under:

Sl. No.	Initial mass (g)	Mass after 27.78 hrs.(g)	Loss of mass (g)	Percent wear (%)	Percent wear per hour
1	372.67	370.65	2.02	0.54	0.02
2	395.62	394.42	1.20	0.30	0.01
3	390.63	387.45	3.18	0.81	0.03
4	401.00	396.27	4.73	1.18	0.04
5	385.48	382.57	2.91	0.75	0.03
6	422.93	419.92	3.01	0.71	0.03

15. CRITICAL TECHNICAL SPECIFICATIONS

Vide Ministry O.M. No. 13-9/2019-M&T (I&P) dated 26.04.2019.

Sr. No.	Parameters	Specifications	Observed	Remarks
1.	Type	Self-propelled, walk behind	Self propelled, walk behind type	Conforms
2.	Working width, mm	300-1500	800	Conforms
3.	Type of engine	Compression/Spark ignition	Spark ignition	Conforms
4.	Starting method	Manual/recoil/self-starting	Recoil	Conforms
5.	Type of clutch	Dry/Wet	Dry	Conforms
6.	Type of primary gear box	Sliding/constant mesh or combination of both	Sliding mesh	Conforms

Power weeder-131/2776/2022	XTRA POWER, XPW-750T (E) POWER WEEDER (COMMERCIAL)			
----------------------------	---	--	--	--

7.	Type of secondary gear box	Gear type, chain & sprocket type	chain & sprocket type	Conforms
8.	Material for rotor shaft	SAE 1045 (CRS) / EN8 / EN9	High Carbon Steel	Conforms
9.	No. of flanges	4 - 10	6	Conforms
10.	Types of flanges	Square/circular/rectangular	Square	Conforms
11.	Distance between consecutive flanges, mm	80 to 150	120	Conforms
12.	No. of blades in each flange	3-6	04	Conforms
13.	No. of rotor blade	12 (min.)	24	Conforms
14.	Thickness of rotor blade, mm	5 (min.)	5.5	Conforms
15.	Material of blade	Boron (28MnCrB5) / High carbon steel EN 42j	High carbon steel	Conforms
16.	Hardness of Blade, HRC	38 (min.)	32 (Average)	Does not conform
17.	Shape of rotor blade	C / J shape	J shape	Conforms
18.	Provision for handle height adjustment	Must be provided	Provided	Conforms
19.	Provision for handle rotation	Must be provided	Provided	Conforms
20.	Provision for emergency stop of engine	Must be provided	Provided	Conforms
21.	Provision for easy start of engine	Must be provided	Provided	Conforms
22.	Provision for shield/cover to prevent flying of mud & stone from rotor	Must be provided	Provided	Conforms
23.	Depth control mechanism	Must be provided	Provided	Conforms
24.	Provision for transport wheels	Must be provided	Provided	Conforms
25.	Provision for cover on exhaust	Must be provided	Provided	Conforms
26.	Direction of exhaust emission away from operator	Must be provided	Provided	Conforms

Power weeder-131/2776/2022	XTRA POWER, XPW-750T (E) POWER WEEDER (COMMERCIAL)
----------------------------	---

27.	Marking/labeling machine	The labeling plate should be riveted on the body of machine having Name and address of manufacturer & Applicant, Country of origin, Make, Model, Year of manufacturer, Serial number, Engine number, Engine HP, rated rpm & SFC.	Provided	Conforms
28.	Literature	Operator manual, service manual and Parts catalogue should be provided.	Provided	Conforms

16. COMMENTS & RECOMMENDATIONS

16.1 Engine rating test

- i) The average rated power in rating test of engine was observed as 3.85 kW at 3300 rpm against manufacture declared power as 3.98 kW at 3300 rpm.
- ii) Specific fuel consumption at average rated power in rating test was observed as 401.04 g/kWh declared value of 378.00 g/kWh

16.2 Mechanical vibration

The amplitude of mechanical vibration marked as (*) on the relevant chapter, are on drastically higher side. It is not just directly concerned with operator's health, safety and comfort, but also adversely affect the useful life of the components. In view of above, this deserved to be given top priority for corrective action.

16.3 The chemical composition of blades does not conform in toto, to the requirements of IS: 6690-1981. This needs to be looked into for corrective action.

16.4 The hardness of blades does not conform in toto, to the requirements of IS: 6690-1981. This needs to be looked into for corrective action.

16.5 Rated rpm & SFC are not mentioned on labeling plate. It **MUST** be specified.





17. TECHNICAL LITERATURE

The following literatures are provided by the applicant.

- i) Operator Manual
- ii) Part's Catalogue
- iii) Service manual
- iv) Owner's Manual of engine

TESTING AUTHORITY

G.R. AMBALKAR AGRICULTURAL ENGINEER	
DR. MUKESH JAIN DIRECTOR	 18-01-2022

Test report compiled by Er. Dharmendra Kumar, Technical Assistant

18. APPLICANT'S COMMENTS

All modifications/improvement as per directions by authority will be made to meet the non-complementary

